

Avaya Contact Center Select Solution Description

© 2015 Avaya Inc. All Rights Reserved.

Notice

While reasonable efforts have been made to ensure that the information in this document is complete and accurate at the time of printing, Avaya assumes no liability for any errors. Avaya reserves the right to make changes and corrections to the information in this document without the obligation to notify any person or organization of such changes.

Documentation disclaimer

"Documentation" means information published by Avaya in varying mediums which may include product information, operating instructions and performance specifications that Avaya may generally make available to users of its products and Hosted Services. Documentation does not include marketing materials. Avaya shall not be responsible for any modifications, additions, or deletions to the original published version of documentation unless such modifications, additions, or deletions were performed by Avaya. End User agrees to indemnify and hold harmless Avaya, Avaya's agents, servants and employees against all claims, lawsuits, demands and judgments arising out of, or in connection with, subsequent modifications, additions or deletions to this documentation, to the extent made by End User.

Link disclaimer

Avaya is not responsible for the contents or reliability of any linked websites referenced within this site or documentation provided by Avaya. Avaya is not responsible for the accuracy of any information, statement or content provided on these sites and does not necessarily endorse the products, services, or information described or offered within them. Avaya does not guarantee that these links will work all the time and has no control over the availability of the linked pages.

Warranty

Avaya provides a limited warranty on Avaya hardware and software. Refer to your sales agreement to establish the terms of the limited warranty. In addition, Avaya's standard warranty language, as well as information regarding support for this product while under warranty is available to Avaya customers and other parties through the Avaya Support website: http://support.avaya.com or such successor site as designated by Avaya. Please note that if You acquired the product(s) from an authorized Avaya Channel Partner outside of the United States and Canada, the warranty is provided to You by said Avaya Channel Partner and not by Avaya.

Licenses

THE SOFTWARE LICENSE TERMS AVAILABLE ON THE AVAYA WEBSITE, HTTP://SUPPORT.AVAYA.COM/LICENSEINFO OR SUCH SUCCESSOR SITE AS DESIGNATED BY AVAYA, ARE APPLICABLE TO ANYONE WHO DOWNLOADS, USES AND/OR INSTALLS AVAYA SOFTWARE, PURCHASED FROM AVAYA INC. ANY AVAYA AFFILIATE, OR AN AVAYA CHANNEL PARTNER (AS APPLICABLE) UNDER A COMMERCIAL AGREEMENT WITH AVAYA OR AN AVAYA CHANNEL PARTNER. UNLESS OTHERWISE AGREED TO BY AVAYA IN WRITING, AVAYA DOES NOT EXTEND THIS LICENSE IF THE SOFTWARE WAS OBTAINED FROM ANYONE OTHER THAN AVAYA, AN AVAYA AFFILIATE OR AN AVAYA CHANNEL PARTNER; AVAYA RESERVES THE RIGHT TO TAKE LEGAL ACTION AGAINST YOU AND ANYONE ELSE USING OR SELLING THE SOFTWARE WITHOUT A LICENSE. BY INSTALLING, DOWNLOADING OR USING THE SOFTWARE, OR AUTHORIZING OTHERS TO DO SO, YOU, ON BEHALF OF YOURSELF AND THE ENTITY FOR WHOM YOU ARE INSTALLING, DOWNLOADING OR USING THE SOFTWARE (HEREINAFTER REFERRED TO INTERCHANGEABLY AS "YOU" AND "END USER"), AGREE TO THESE TERMS AND CONDITIONS AND CREATE A BINDING CONTRACT BETWEEN YOU AND AVAYA INC. OR THE APPLICABLE AVAYA AFFILIATE ("AVAYA").

Avaya grants You a license within the scope of the license types described below, with the exception of Heritage Nortel Software, for which the scope of the license is detailed below. Where the order documentation does not expressly identify a license type, the applicable license will be a Designated System License. The

applicable number of licenses and units of capacity for which the license is granted will be one (1), unless a different number of licenses or units of capacity is specified in the documentation or other materials available to You. "Software" means computer programs in object code, provided by Avaya or an Avaya Channel Partner, whether as stand-alone products, pre-installed on hardware products, and any upgrades, updates, patches, bug fixes, or modified versions thereto. "Designated Processor" means a single stand-alone computing device. "Server" means a Designated Processor that hosts a software application to be accessed by multiple users. "Instance" means a single copy of the Software executing at a particular time: (i) on one physical machine; or (ii) on one deployed software virtual machine ("VM") or similar deployment.

License type(s)

Concurrent User License (CU). End User may install and use the Software on multiple Designated Processors or one or more Servers, so long as only the licensed number of Units are accessing and using the Software at any given time. A "Unit" means the unit on which Avaya, at its sole discretion, bases the pricing of its licenses and can be, without limitation, an agent, port or user, an e-mail or voice mail account in the name of a person or corporate function (e.g., webmaster or helpdesk), or a directory entry in the administrative database utilized by the Software that permits one user to interface with the Software. Units may be linked to a specific, identified Server or an Instance of the Software.

Heritage Nortel Software

"Heritage Nortel Software" means the software that was acquired by Avaya as part of its purchase of the Nortel Enterprise Solutions Business in December 2009. The Heritage Nortel Software currently available for license from Avaya is the software contained within the list of Heritage Nortel Products located at http://support.avaya.com/Licenselnfo under the link "Heritage Nortel Products" or such successor site as designated by Avaya. For Heritage Nortel Software, Avaya grants You a license to use Heritage Nortel Software provided hereunder solely to the extent of the authorized activation or authorized usage level, solely for the purpose specified in the Documentation, and solely as embedded in, for execution on, or for communication with Avaya equipment. Charges for Heritage Nortel Software may be based on extent of activation or use authorized as specified in an order or invoice.

Copyright

Except where expressly stated otherwise, no use should be made of materials on this site, the Documentation, Software, Hosted Service, or hardware provided by Avaya. All content on this site, the documentation, Hosted Service, and the product provided by Avaya including the selection, arrangement and design of the content is owned either by Avaya or its licensors and is protected by copyright and other intellectual property laws including the sui generis rights relating to the protection of databases. You may not modify, copy, reproduce, republish, upload, post, transmit or distribute in any way any content, in whole or in part, including any code and software unless expressly authorized by Avaya. Unauthorized reproduction, transmission, dissemination, storage, and or use without the express written consent of Avaya can be a criminal, as well as a civil offense under the applicable law.

Third Party Components

"Third Party Components" mean certain software programs or portions thereof included in the Software or Hosted Service may contain software (including open source software) distributed under third party agreements ("Third Party Components"), which contain terms regarding the rights to use certain portions of the Software ("Third Party Terms"). As required, information regarding distributed Linux OS source code (for those products that have distributed Linux OS source code) and identifying the copyright holders of the Third Party Components and the Third Party Terms that apply is available in the products, Documentation or on Avaya's website at: http://support.avaya.com/Copyright or such successor site as designated by Avaya. You agree to the Third Party Terms for any such Third Party Components.

Preventing Toll Fraud

"Toll Fraud" is the unauthorized use of your telecommunications system by an unauthorized party (for example, a person who is not a corporate employee, agent, subcontractor, or is not working on your

company's behalf). Be aware that there can be a risk of Toll Fraud associated with your system and that, if Toll Fraud occurs, it can result in substantial additional charges for your telecommunications services.

Avaya Toll Fraud intervention

If You suspect that You are being victimized by Toll Fraud and You need technical assistance or support, call Technical Service Center Toll Fraud Intervention Hotline at +1-800-643-2353 for the United States and Canada. For additional support telephone numbers, see the Avaya Support website: http://support.avaya.com or such successor site as designated by Avaya. Suspected security vulnerabilities with Avaya products should be reported to Avaya by sending mail to: securityalerts@avaya.com.

Downloading Documentation

For the most current versions of Documentation, see the Avaya Support website: http://support.avaya.com, or such successor site as designated by Avaya.

Contact Avaya Support

See the Avaya Support website: http://support.avaya.com for product or Hosted Service notices and articles, or to report a problem with your Avaya product or Hosted Service. For a list of support telephone numbers and contact addresses, go to the Avaya Support website: http://support.avaya.com (or such successor site as designated by Avaya), scroll to the bottom of the page, and select Contact Avaya Support.

Trademarks

Avaya, the Avaya logo, Avaya one-X® Portal, Avaya Aura® Communication Manager, Avaya Aura® Experience Portal, Avaya Aura® Orchestration Designer, Avaya Aura® Session Manager, Avaya Aura® System Manager, and Application Enablement Services are either registered trademarks or trademarks of Avaya Inc. in the United States of America and/or other jurisdictions.

All non-Avaya trademarks are the property of their respective owners. Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries.

Contents

Chapter 1: Introduction	8
Related resources	8
Documentation	8
Viewing Avaya Mentor videos	10
Support	10
Chapter 2: New in this release	
Features	12
1140E and 1230 IP desk phone support	12
Avaya Aura [®] Experience Portal support	
Avaya Contact Center Select Business Continuity	
Communication Control Toolkit SDK support	
Dialed Number Identification Services	
IP Office resilience	14
Microsoft Lync 2013 support	14
Patch Scanner utility	
Support for a Windows domain	14
TLS communication	15
WebLM support	
Other changes	15
New documents	15
Chapter 3: Solution overview	16
Licensing	
User Data Synchronization	
Topology	
IP Office supported versions	
Overview of solution configuration	27
Simple voice call flow example	29
Sample Orchestration Designer voice flow applications	30
Multimedia contacts processing	
Simple email message flow	34
Call Recording	35
Remote Agents	36
Avaya Contact Center Select domain and workgroup support	
Avaya Security Advisories	
Upgrades and migrations	39
Reporting Source of Call Disconnect	
Limitations	
Chapter 4: Avaya Contact Center Select DVD	44
Platform Vendor Independence server specification.	

Entry-level single 4-core server specification	46
Mid-range dual 4-core server specification	
High-end server specifications	48
Server performance and BIOS settings	51
Avaya Contact Center Select DVD software specification	
Server naming requirements	
Microsoft security hotfixes	55
Operating system updates	55
Third-party software requirements	57
Guidelines for the use of antivirus software	58
Avaya Contact Center Select DVD licensing	60
Chapter 5: Avaya Contact Center Select software appliance	
Avaya Contact Center Select OVA	
Server naming requirements	
Microsoft security hotfixes	65
Operating system updates	65
Third-party software requirements	
Guidelines for the use of antivirus software	67
Avaya Media Server OVA	69
WebLM OVA	71
VMware host server specification	71
High-end dual 8–core server specification	72
High-end dual 10-core server specification	73
Virtualization considerations	74
VMware features	75
VMware vSphere Host considerations	
Server performance and BIOS settings	77
VMware networking best practices	
Avaya Contact Center Select VMware snapshot considerations	
Avaya Media Server VMware snapshot considerations	
Guidance for storage requirements	
Performance monitoring and management	
Troubleshooting VMware	
Software Appliance Licensing	84
Chapter 6: Avaya Contact Center Select hardware appliance	86
Hardware Appliance server specification	87
Avaya Contact Center Select hardware appliance software specifications	89
Server naming requirements	
Microsoft security hotfixes	90
Operating system updates	
Third-party software requirements	
Guidelines for the use of antivirus software	
Hardware Appliance Licensing	95

Chapter 7: Solution capacity limits and supported features	. 97
Avaya Contact Center Select maximum capacity limits	. 97
Avaya Contact Center Select maximum configuration limits	100
Avaya Contact Center Select supported features	101
Supported Telephony Features	107
Supported Telephony Devices	115
Remote access support	
Communication Control Toolkit supported functionality	117
Chapter 8: Avaya Aura [®] Experience Portal Integration	121
Data transfer methods	122
Avaya Aura® Experience Portal Orchestration Designer	122
Voice XML	123
Call Control XML	123
SIP-enabled Avaya Contact Center Select	123
P-Intrinsic SIP Header	124
User-to-User Information	125
Universal Call Identifier	
Front-end Avaya Aura® Experience Portal and SIP-enabled Contact Center	
CenterBack-end Avaya Aura [®] Experience Portal and SIP-enabled Contact Center	12/
Call flow example using back-end Avaya Aura Experience Portal and SIP-enabled	
	129
Back-end Avaya Aura® Experience Portal using Context Creation and SIP-enabled Contact	130
CenterCall flow example using back-end Avaya Aura [®] Experience Portal with the Context	130
Creation sample application	133
Avaya DevConnect	
•	
Chapter 9: Administration client computer requirements	
Client operating system requirements	
Administration Client Citrix support	
Third-party software requirements	
. ,	
Chapter 10: Agent Desktop computer requirements	
Agent Desktop localized languages	
Client operating system requirements	
Agent Desktop client network infrastructure requirements	
Client Citrix support	
Agent Desktop network ports	
Chapter 11: Avaya Contact Center Select port matrix	
Contact Center Manager Server port requirements	
· · · · · · · · · · · · · · · · · · ·	150

Communication Control Toolkit port requirements	153
Contact Center Multimedia port requirements	153
Avava Media Server port requirements	155

Chapter 1: Introduction

This document provides a technical description of Avaya Contact Center Select Release 6.4. It describes the product features, specifications, licensing, and interoperability with other supported products.

This document is intended for personnel who want to understand how this solution meets customer requirements.

Related resources

The following are some additional Avaya Contact Center Select related resources.

Documentation

The following table lists some of the documents related to Avaya Contact Center Select. Download the documents from the Avaya Support website at http://support.avaya.com.

Category	Title	Description	Audience
Overview	Avaya Contact Center Select Solution Description	This document provides a technical description of Avaya Contact Center Select. It describes the product features, specifications, licensing, and interoperability with other supported products.	This document is intended for personnel who determine the best design to meet the business needs of a customer.
Deployment	Deploying Avaya Contact Center Select DVD	This document contains information about Avaya Contact Center Select DVD installation, initial configuration, and verification. This document contains information about maintaining	This document is intended for personnel who deploy, commission, and test the Avaya Contact Center Select DVD.

Table continues...

Category	Title	Description	Audience
		and troubleshooting the Avaya Contact Center Select server.	
Deployment	Deploying Avaya Contact Center Select Software Appliance	This document contains information about Avaya Contact Center Select Software Appliance (VMware OVA) preparation, deployment, initial configuration, and verification. This document contains information about maintaining and troubleshooting the software appliance.	This document is intended for personnel who deploy, commission, and test the Avaya Contact Center Select software appliance.
Deployment	Deploying Avaya Contact Center Select Hardware Appliance	This document contains information about Avaya Contact Center Select Hardware Appliance (physical server) installation, initial configuration, and verification. This document contains information about maintaining and troubleshooting the hardware appliance.	This document is intended for personnel who deploy, commission, and test the Avaya Contact Center Select hardware appliance.
Deployment	Avaya Contact Center Select Business Continuity	This document contains information about Avaya Contact Center Select Business Continuity.	This document is intended for personnel who deploy, commission, and test Avaya Contact Center Select Business Continuity.
Administration	Administering Avaya Contact Center Select	This document contains information and procedures to configure the users, skillsets, and contact center configuration data. This document contains information about creating Avaya Contact Center Select real-time displays and historical reports.	This document is intended for personnel who perform the day-to-day administration of Avaya Contact Center Select.
Administration	Avaya Contact Center Select Advanced Administration	This document contains information about managing Avaya Contact Center Select licensing and multimedia configuration.	This document is intended for personnel who manage Avaya Contact Center Select.

Table continues...

Introduction

Category	Title	Description	Audience
Administration	Upgrading and patching Avaya Contact Center Select	This document contains information about upgrading and patching Avaya Contact Center Select.	This document is intended for personnel who maintain Avaya Contact Center Select.
User guide	Avaya Contact Center Select Agent Desktop Guide	This document contains information about using Agent Desktop.	This document is intended for Avaya Contact Center Select Agents and Agent Supervisors.

Viewing Avaya Mentor videos

Avaya Mentor videos provide technical content on how to install, configure, and troubleshoot Avaya products.

About this task

Videos are available on the Avaya Support website, listed under the video document type, and on the Avaya-run channel on YouTube.

Procedure

- To find videos on the Avaya Support website, go to http://support.avaya.com and perform one of the following actions:
 - In Search, type Avaya Mentor Videos to see a list of the available videos.
 - In **Search**, type the product name. On the Search Results page, select **Video** in the **Content Type** column on the left.
- To find the Avaya Mentor videos on YouTube, go to www.youtube.com/AvayaMentor and perform one of the following actions:
 - Enter a key word or key words in the Search Channel to search for a specific product or topic
 - Scroll down Playlists, and click the name of a topic to see the available list of videos posted on the website.



Videos are not available for all products.

Support

Go to the Avaya Support website at http://support.avaya.com for the most up-to-date documentation, product notices, and knowledge articles. You can also search for release notes,

downloads, and resolutions to issues. Use the online service request system to create a service request. Chat with live agents to get answers to questions, or request an agent to connect you to a support team if an issue requires additional expertise.

Chapter 2: New in this release

This section describes the new features and changes in Avaya Contact Center Select Release 6.4.2.

Features

See the following sections for information about feature changes:

- 1140E and 1230 IP desk phone support on page 12
- Avaya Aura Experience Portal support on page 13
- Avaya Contact Center Select Business Continuity on page 13
- Communication Control Toolkit SDK support on page 13
- Dialed Number Identification Services on page 14
- IP Office resilience on page 14
- Microsoft Lync 2013 support on page 14
- Patch Scanner utility on page 14
- Support for a Windows domain on page 14
- TLS communication on page 15
- WebLM on page 15

1140E and 1230 IP desk phone support

Avaya Contact Center Select and IP Office Release 9.1 support 1140E (Model NTYS05) and 1230 (Model NTYS20) IP series desk phones with IP Office SIP firmware.

For more information about the supported telephony devices, see <u>Supported Telephony Devices</u> on page 115.

Avaya Aura® Experience Portal support

Avaya Aura[®] Experience Portal is an open standards-based self-service software platform which offers industry leading reliability and scalability to help reduce costs and simplify operations.

Avaya Aura[®] Experience Portal Release 7.0.1 is deployed on standard Linux servers and it supports integration with SIP-enabled systems, including Avaya Contact Center Select and IP Office.

For more information about Avaya Contact Center Select integration with Avaya Aura[®] Experience Portal Release 7.0.1 and IP Office Release 9.1, see <u>Avaya Aura Experience Portal integration</u> on page 121.

Avaya Contact Center Select Business Continuity

Business Continuity is an Avaya Contact Center Select (ACCS) licensed feature. ACCS solutions that support Business Continuity have two ACCS servers. One server, called the active server, processes customer contacts. The other ACCS server (standby or Remote Geographic Node) shadows the active server. If the active server fails, the other ACCS server can take over contact processing. This feature therefore provides ACCS redundancy, data resiliency, and disaster recovery.

For more information about Avaya Contact Center Select Business Continuity, see *Avaya Contact Center Select Business Continuity*.

Communication Control Toolkit SDK support

Avaya Contact Center Select Communication Control Toolkit application software is used for installed and browser-based client integrations. Communication Control Toolkit delivers a cross-portfolio multichannel Application Programming Interface (API) that facilitates the integration of Contact Center solutions for your client applications.

The Application programming interface (API) is published as Microsoft .NET types and is distributed as a Windows assembly, which is referenced by application developers.

You can use Communication Control Toolkit as the next generation of computer telephony integration (CTI) middleware and CTI toolkit. On the client, the API provides a group of interfaces, collectively known as the full Communication Control Toolkit API.

For more information about using the Communication Control Toolkit API, see the Avaya Communication Control SDK Programmers Reference Guide. This guide is a help file that accompanies the Software Development Kit. You must join the developer partner program and purchase the Communication Control Toolkit SDK to download the documentation from the Avaya Support web site.

Agent Desktop is an example of a client application that uses the full Communication Control Toolkit API.

Dialed Number Identification Services

Avaya Contact Center Select now supports Dialed Number Identification Services (DNIS). DNIS is an optional service that allows Avaya Contact Center Select to identify the phone number dialed by the incoming caller, and route calls to appropriate skillsets or agents based on the number dialed. For more information about DNIS, see *Administering Avaya Contact Center Select*.

IP Office resilience

IP Office Server Edition Release 9.1 solutions provide voice platform resiliency. IP Office resilience is a licensed feature.

IP Office Server Edition Release 9.1 provides voice platform resilience and supports Avaya Contact Center Select Business Continuity.

For more information about Avaya Contact Center Select Business Continuity, see *Avaya Contact Center Select Business Continuity*.

Microsoft Lync 2013 support

Avaya Contact Center Select supports Microsoft Lync 2013 for peer-to-peer Instant Messaging (IM). Avaya Contact Center Select does not support routed IM contacts.

Patch Scanner utility

The Avaya Patch Scanner utility is available with Avaya Contact Center Select Release 6.4.2. You can download the Patch Scanner as a standalone utility from the Avaya Support website. Alternatively, you can download the Patch Scanner as part of an ACCS Service Pack from the Avaya Support website. The Patch Scanner utility scans the Contact Center system and compares the list of currently installed patches with those available in the most recent Service Packs. For more information about the Patch Scanner utility, see *Upgrading and patching Avaya Contact Center Select*.

Support for a Windows domain

The Avaya Contact Center Select server is supported in a workgroup or in a Windows domain.

After you deploy the Avaya Contact Center Select Hardware Appliance or Software Appliance, you can add the Avaya Contact Center Select server to a Windows domain.

You can add the Avaya Contact Center Select server to a Windows domain before or after you install the Avaya Contact Center Select software using the Avaya Contact Center Select DVD.

The Avaya Contact Center Select configuration Ignition Wizard creates only local workgroup user accounts. The Avaya Contact Center Select configuration Ignition Wizard does not create Windows domain accounts.

TLS communication

Avaya Contact Center Select supports TLS communication with IP Office Release 9.1. For more information about configuring TLS communication between Avaya Contact Center Select and IP Office, see *Avaya Contact Center Select Advanced Administration*.

WebLM support

Avaya Contact Center Select supports WebLM Release 6.3.2 and Release 6.3.8.

Other changes

See the following section for information about other changes:

New documents on page 15

New documents

The following documents are new for Avaya Contact Center Select Release 6.4.2:


- Avaya Contact Center Select Business Continuity
- Upgrading and patching Avaya Contact Center Select

Chapter 3: Solution overview

Avaya Contact Center Select is a context-sensitive, collaborative, voice and multimedia customer experience solution that allows small to midsize enterprises to anticipate, accelerate, and enhance customer interactions. Avaya Contact Center Select uses the Avaya IP Office telephone system to provide a real-time telephony platform. Avaya IP Office is a flexible and scalable phone system designed specifically for small and midsize enterprises. IP Office supports a wide range of phones and devices for use in contact centers.

Avaya Contact Center Select uses SIP and CTI interfaces to communicate with the IP Office platform. This integration gives Avaya Contact Center Select access to and control of a wide range of IP Office phones and features. Customers integrating Avaya Contact Center Select with the IP Office platform gain skill-based routing, call treatments, reporting, unified agent management, and the graphical Orchestration Designer utility. Agent Desktop supports specified IP Office phones and also supports multimedia contact types.

The following diagram shows a typical contact center solution using voice and multimedia enabled Avaya Contact Center Select and the Avaya IP Office voice phone system.



Avaya Contact Center Select provides a feature rich voice and multimedia solution with integrated routing and reporting for the small to midsize enterprises. Avaya Contact Center Select provides unified contact center and IP Office phone user account management for agents and supervisors. Voice-enabled agents and supervisors created in Avaya Contact Center Select are automatically

added to the IP Office platform. Avaya Contact Center Select synchronizes user (agent and supervisor) information between Avaya Contact Center Select and the IP Office platform.

Avaya Contact Center Select is offered in the following deployment types:

- Avaya Contact Center Select DVD; The Avaya Contact Center Select DVD contains the
 application software. The Avaya Contact Center Select DVD deployment option supports
 Platform Vendor Independence (PVI). The customer supplies the Microsoft Windows 2008
 operating system license and server hardware that meets one of the Avaya Contact Center
 Select PVI server specifications.
- Avaya Contact Center Select software appliance; The Avaya Contact Center Select software appliance is a set of VMware Open Virtual Appliance (OVA) virtualized servers; an Avaya Contact Center Select OVA, an Avaya Media Server OVA, and a WebLM OVA. The customer supplies the VMware resources and operating system licenses for the VMware quests.
- Avaya Contact Center Select hardware appliance; The Avaya Contact Center Select
 hardware appliance is a physical server with the application software already loaded and
 partially preconfigured. Avaya supplies the server hardware and a license for the Microsoft
 Windows 2008 operating system.

Avaya Contact Center Select supports the following routed contact types:

- Voice
- Email
- Outbound
- Web communications (Web chat)
- SMS text messages
- Fax messages
- Scanned documents
- Voice mail messages

Avaya Contact Center Select also supports peer-to-peer Instant Messaging and Presence Notifications. To support the email-based contact types, you must add an email server to your solution. To support the Web communications contact type, you must add a Web communications server to your solution.

The Avaya Contact Center Select server is supported in a workgroup or in a Windows domain.

Avaya Contact Center Select is quick to deploy and offers a feature rich voice and multimedia solution. Avaya Contact Center Select provides sample configuration data to support rapid deployment and integration with IP Office. You can modify the sample data to meet your solution's requirements and add to the data as your solution expands. You can also use the sample data to learn more about Avaya Contact Center Select. The sample data includes the following data:

- Supervisors and agents
- Skillsets
- Orchestration Designer voice flow applications

- · Activity codes
- CDN (Route Points)
- · Multiplicity Presentation Classes
- · Real-time reports
- Historical reports
- · User data synchronization account for IP Office

Avaya Contact Center Select provides a simplified voice prompt management utility. The contact center supervisor can perform prompt management work without requiring administrator access to the Avaya Media Server server. Avaya Contact Center Select provides a number of status monitoring utilities to monitor the integration points with the IP Office platform. Avaya Contact Center Select also provides an always-on graphical troubleshooting dashboard running on the server.

Licensing

Avaya Contact Center Select supports the following licensed agent packages:

Name	Description	Notes
Agent licenses	Agent licenses determine the number of agents that can log on to Contact Center.	
	Licensing is available for the following types of agents:	
	voice agent	
	outbound agent	
	email agent (covering FAX messages, SMS text messages, voice mail messages, and scanned document messages)	
	Web communications agent (or Web chat agent)	

Avaya Contact Center Select supports the following licensed features:

Name	Description	Notes
Multiplicity	Multiplicity is the ability of an agent to handle multiple concurrent multimedia contacts. At any one time an agent can be active on a voice and multimedia contact. However, when one contact is active; the others automatically are on hold. The maximum number of concurrent multimedia or non-voice contacts that an agent can be assigned is five.	
Web Based Statistics	If Web Reporting server is enabled, agents and supervisors can use Agent Desktop to view real-time reports for call	

Table continues...

Name	Description	Notes
	handling, skillset data, and state information on Agent Desktop.	
Remote Agent	Remote Agent is a solution that extends a Contact Center to an agent's preferred environment, allowing them to handle skillset calls regardless of location. Remote Agent solutions connect contact center calls to the agent's telephone (home telephone or mobile), without the agent needing special hardware.	
Outbound	Use the Multimedia server and the Outbound Campaign Management Tool in Contact Center Manager Administration to create progressive outbound campaigns on which calls are passed to agents and made from the Contact Center.	

For Avaya Contact Center Select (ACCS) integration with IP Office Server Edition, IP Office Server Edition requires the following licenses:

- One Avaya IP Endpoint license for Avaya Contact Center Select integration.
- One Power User license for every ACCS agent or supervisor agent that is configured for any of the following:
 - configured to use IP Office Release 9.1.x Avaya Communicator for Windows.
 - configured to use IP Office Release 9.0 Softphone.
 - configured to operate as an ACCS Remote Agent.
 - configured to use an IP Office physical phone with IP Office remote worker functionality.
 Only IP Office physical phones using IP Office remote worker functionality require a Power User license; other physical phone users do not require a Power User license.
- One Server Edition Release 9.1 license. One license for each node in the Small Community Network (SCN).
- IP Endpoint licenses either Avaya or Third-Party depending on the IP phones used in your solution. Provision one IP Endpoint license for each configured endpoint.
 - IP Office Release 9.1.x Avaya Communicator for Windows users do not require an IP endpoint license, only an IP Office user license.
 - IP Office Release 9.0 Softphone users do not require an IP endpoint license, only an IP Office user license.
 - If your solution uses digital phones only from an IP Office 500V2 Expansion then you do not require endpoint licenses.
- One CTI Pro license or Third Party API license for IP Office Release 9.1.x.
- One ACCS license if using IP Office Release 9.1.x.
- Voicemail Pro Additional Voicemail Channels, up to a maximum of 350.
- SIP Trunk licenses or channels to support the trunks used in your solution.

 Voicemail Pro Recording Administrators. One instance on each node of the SCN that the call are recorded from. If all recording is to be done on the Primary node then one instance is required. This license enables Contact Recorder.

For Avaya Contact Center Select (ACCS) integration with IP Office 500V2 (non-Server Edition), IP Office 500V2 requires the following licenses:

- One Avaya IP Endpoint license for Avaya Contact Center Select integration.
- One Power User license for every ACCS agent or supervisor agent that is configured for any of the following:
 - configured to use IP Office Release 9.1.x Avaya Communicator for Windows.
 - configured to use IP Office Release 9.0 Softphone.
 - configured to operate as an ACCS Remote Agent.
 - configured to use an IP Office physical phone with IP Office remote worker functionality.
 Only IP Office physical phones using IP Office remote worker functionality require a Power User license; other physical phone users do not require a Power User license.
- Advanced Edition license. Required only for IP Office 500V2 Release 9.0.x Not required for IP Office 500V2 Release 9.1.x.
- · Preferred Edition License.
- · Essential Edition License.
- IP Endpoint licenses either Avaya or Third-Party depending on the IP phones used in your solution.
 - IP Office Release 9.1.x Avaya Communicator for Windows users do not require an IP endpoint license, only an IP Office user license.
 - IP Office Release 9.0 Softphone users do not require an IP endpoint license, only an IP Office user license.
 - If your solution uses only digital telephones then you do not require endpoint licenses.
- One CTI Pro license.
- Voicemail Pro Additional Voicemail Channels.
- SIP Trunk licenses or channels licenses to support the trunks used in your solution.
- Voicemail Pro Recording Administrators. One instance on each node of the Small Community Network (SCN) that the calls are recorded from. If all recording is to be done on the Primary node then one instance is required. This license enables Contact Recorder. Contact Recorder requires a separate Application Server.

When Avaya Contact Center Select is deployed with an IP Office Release 9.1.x or 9.1.x Select Resilience pair, ensure the IP Office Secondary system contains the following licenses to enable Avaya Contact Center Select connectivity:

- One Avaya IP End point license
- · One CTI Pro license

This applies to both Avaya Contact Center Select standalone and Avaya Contact Center Select Business Continuity configurations. The IP Office Secondary system does not require the inclusion of Voicemail Pro Recordings Administrators license system or Voicemail Pro licenses, because the Call Recording functionality is licensed from the IP Office Primary system.

The Avaya Contact Center Select base software bundle provisions one Contact Recorder system license plus 1 Voicemail Pro port for every voice agent for Call Recording.

An Avaya Contact Center Select voice agent license provisions one Voicemail Pro port for Call Recording.

Avaya Contact Center Select uses Avaya WebLM as the license provider. Each Avaya WebLM instance supports a single Avaya Contact Center Select.

Hotdesking / Free-seating

Hot desking / Free-seating environments are supported with ACCS and IP Office physical phones and softphones.

Hotdesking with physical phones

Each physical IP phone requires an IP Endpoint license.

Power User licenses are not required to use IP Office physical phones unless using the IP Office remote worker functionality.

Example:

Requirement: 100 seat ACCS with 100 IP physical phones and 200 possible agents:

- Order 100 ACCS voice agents + 100 IP Endpoint licenses.
- If all agents require IP Office remote worker functionality also order 200 Power User licenses.

Hotdesking with softphones

Each ACCS agent requires a Power User license.

IP Endpoint licenses are not required for the softphones.

Example:

Requirement: 100 seat ACCS with 100 softphones and 200 possible agents:

Order 100 ACCS voice agents + 200 Power User licenses.

Maximum number of supported nodes

Avaya Contact Center Select supports the following maximum number of IP Office nodes:

- For IP Office 9.0.x Server Edition, ACCS supports 32 nodes in total, consisting of a Primary, a Secondary, and 30 expansions.
- For IP Office 9.1 Server Edition, ACCS supports 32 nodes in total, consisting of a Primary, a Secondary, and 30 expansions.
- For IP Office 9.1 Select Server Edition, ACCS supports 150 nodes in total, consisting of a Primary, a Secondary, and 148 expansions.

User Data Synchronization

Avaya Contact Center Select provides unified administration for contact center agents and IP Office users. The users (agents and supervisors) that you configure in Avaya Contact Center Select are automatically mirrored to the connected IP Office.

When you create an agent in Contact Center Manager Administration, you can choose to create a local Windows user account on the Avaya Contact Center Select server or map to an existing Windows domain user account. Avaya Contact Center Select automatically creates a matching user account in IP Office.

When you modify agent details in Avaya Contact Center Select, the corresponding IP Office user details are automatically updated. If you delete an agent in Avaya Contact Center Select, the corresponding IP Office user is not deleted.

The data synchronization mechanism works in one direction; from Avaya Contact Center Select to IP Office. The Avaya Contact Center Select administrator can manually force a data synchronization from Avaya Contact Center Select.

Topology

In a contact center solution using Avaya Contact Center Select and an IP Office telephone system, the following network and connectivity topology considerations apply.

Avaya Contact Center Select (ACCS) supports the following deployment options:

- Avaya Contact Center Select DVD
- Avaya Contact Center Select Software Appliance
- Avaya Contact Center Select Hardware Appliance




Figure 1: Typical Avaya Contact Center Select DVD deployment




Figure 2: Typical Avaya Contact Center Select software appliance solution




Figure 3: Typical Avaya Contact Center Select hardware appliance solution

The following connectivity and network layout conditions apply to all Avaya Contact Center Select solutions:

- The Avaya Contact Center Select server is supported in a workgroup or in a Windows domain.
- Each Avaya Contact Center Select connects to a single IP Office Server Edition Primary server. Avaya Contact Center Select does not support connecting to an IP Office Secondary server. Alternatively, each Avaya Contact Center Select can connect to a single IP Office 500V2 Standard Mode with an Advanced Edition license.
- A Small Community Network (SCN) is a system of networked IP Office telephone systems that
 can, among other features, share extension numbers and user names. Each IP Office SCN
 supports a single connected Avaya Contact Center Select. Avaya Contact Center Select
 connects to the IP Office Server Edition Primary server of the SCN.
- To support an IP Office SCN, Avaya Contact Center Select must connect to an IP Office Server Edition Primary server in that SCN network.
- The Avaya Contact Center Select server and the connected IP Office telephone system must be located in the same campus location.
- To support the email-based multimedia contact types, you must install and commission an email server in your solution.
- To support the Web Communications (Web chat) contact type, you must install and commission a Web chat server in your solution.
- Each Avaya WebLM instance supports a single Avaya Contact Center Select.

- Each Avaya Media Server instance supports a single Avaya Contact Center Select.
- A single instance of Contact Center Manager Administration (CCMA) can manage only a single Avaya Contact Center Select.
- If you are using the Avaya Contact Center Select Software Appliance, the Avaya Contact Center Select virtual machine, the WebLM virtual machine, and the Avaya Media Server virtual machine must all be hosted on VMware servers located at the same campus location. The Avaya Contact Center Select Software Appliance supports hosting the Avaya Contact Center Select virtual machine, the WebLM virtual machine, and the Avaya Media Server virtual machine on one VMware host server. The Avaya Contact Center Select virtual machine host server and the connected IP Office telephone system must be located at the same campus location.
- In a virtualized solution, the Avaya Contact Center Select Software Appliance and the connected IP Office telephone system must be hosted on separate VMware host servers.
- Each Supervisor client computer communicates with the Avaya Contact Center Select server. Each Agent Supervisor client computer has Agent Desktop software and Microsoft Internet Explorer installed on it. The Supervisor uses Internet Explorer to access the Contact Center Manager Administration Web client. The Supervisor uses Contact Center Manager Administration to perform basic agent configuration and to run reports. The Agent Supervisor uses Agent Desktop software to handle customer calls, to accept emergency or supervisor calls from agents and to observe calls or Web communication contacts. Each Supervisor computer with Agent Desktop requires an associated IP Office telephone.
- Each Agent client computer communicates with the Avaya Contact Center Select server. Each
 Agent computer has Agent Desktop software and Microsoft Internet Explorer installed on it.
 The Agent uses Internet Explorer to download the Agent Desktop client software. The Agent
 uses Agent Desktop software to handle customer calls. Each Agent computer requires an
 associated IP Office telephone.
- Multicast or Unicast must be enabled on the underlying data network between the clients and the Avaya Contact Center Select server for supervisor and agents.
- Avaya Contact Center Select Business Continuity adds additional network connectivity and layout considerations to the solution. For more information, see *Avaya Contact Center Select Business Continuity*.

IP Office supported versions

Each Avaya Contact Center Select connects to a single IP Office Server Edition Primary server. Avaya Contact Center Select Business Continuity-enabled solutions support connecting to an IP Office Secondary server. A Small Community Network (SCN) is a system of networked IP Office telephone systems that can share extension numbers and user names. Each IP Office SCN supports a single connected Avaya Contact Center Select. The Avaya Contact Center Select server and the connected IP Office server must be located at the same campus location.

To support an IP Office SCN, Avaya Contact Center Select must connect to an IP Office Server Edition Primary server in that SCN network.

Avaya Contact Center Select supports only the following versions of IP Office:

- IP Office Server Edition Release 9.0.3, 9.0.4, and Release 9.1.
- IP Office 500V2, Release 9.0.3, 9.0.4, and Release 9.1 software, Standard Mode, Advanced Edition license

Avaya Contact Center Select does not support other versions of IP Office.

Avaya Contact Center Select does not support IP Office 500V2 Basic mode.

Avaya Contact Center Select Business Continuity is supported only with IP Office Server Edition Release 9.1. For more information, see *Avaya Contact Center Select Business Continuity*.

Avaya Contact Center Select supports TLS communication with IP Office Server Edition Release 9.1. For more information about configuring TLS security certificates, see *Avaya Contact Center Select Advanced Administration*.

Overview of solution configuration

This section provides an overview of how to install and commission an Avaya Contact Center Select and IP Office platform-based solution. By describing the commissioning steps, this section also describes how Avaya Contact Center Select integrates with IP Office.

Avaya Contact Center Select uses the IP Office TAPID interface and SIP open standards to integrate with the IP Office platform. Avaya Contact Center Select uses the IP Office TAPID interface to monitor and control the agent endpoints of the IP Office platform. The IP Office TAPID interface gives Avaya Contact Center Select CTI call control of the IP Office users and extensions representing Avaya Contact Center Select agents. Avaya Contact Center Select uses a SIP User Extension Number to register and integrate with IP Office. This gives Avaya Contact Center Select SIP session management of the IP Office voice calls.

IP Office configuration for Avaya Contact Center Select

Configure IP Office to support integration with Avaya Contact Center Select. This configuration overview does not include IP Office basic configuration for system settings, licensing, or networking.

Using the IP Office Manager:

- 1. Configure the Avaya Contact Center Select Service User account details. On the System > ACCS tab, configure the CCMA Address, CCMA Username, and CCMA Password.
- 2. Configure the System Voice over IP (VoIP) Domain Name. The Avaya Contact Center Select server uses this domain name for treatments and contact routing.
- 3. Add a user with the following specifications. Avaya Contact Center Select uses this SIP User Extension Number to register with IP Office:
 - a. Device type set to All Other Phone Types.

- b. Extension type set to SIP Extension. For example, 6000.
- c. A numerical *Base Extension* number.
- d. On the User, enable Call Waiting On.
- e. On the User > Telephony > Supervisor Settings tab, configure the *Login Code*.
- 4. Configure an IP Office solution short code to map a telephone number to the Avaya Contact Center Select SIP User Extension Number. For example, create a short code 6000|>>3000. All customer calls to telephone number 3000 are forwarded to 6000 and routed to Avaya Contact Center Select. If 3000 is configured as a CDN (Route Point), Avaya Contact Center Select treats the customer call and routes it to a contact center agent.
- 5. Add a H.323 or SIP extension for each Avaya Contact Center Select agent. Avaya Contact Center Select agents use these IP Office extensions to handle voice contacts.

Avaya Contact Center Select installation

During deployment, configure Avaya Contact Center Select to connect to IP Office.

Using the Avaya Contact Center Select Ignition Wizard (configuration utility):

- 1. Configure the IP Office platform details.
- 2. Configure the Service User account details.
- 3. Configure the *Domain Name* to match the IP Office VoIP domain name.
- 4. Configure a CDN (Route Point) number to match the *Code* number used by the IP Office short code.
- 5. Configure the SIP User Extension Number to match the above IP Office user with a SIP extension.
- 6. Configure the Avaya Contact Center Select server details, licensing, and optional multimedia settings.
- 7. Start Avaya Contact Center Select.

At start up, Avaya Contact Center Select uses the SIP User Extension Number details to register itself as a SIP device with IP Office. This registration permits the following functionality:


- Incoming calls destined for an Avaya Contact Center Select Route Point are delivered to the Avaya Contact Center Select server.
- Authorizes the Avaya Contact Center Select server to send outgoing SIP calls to IP Office (for agent routing of Avaya Contact Center Select calls).
- Enables Avaya Contact Center Select specific functionality on the IP Office platform.

Continue to commission Avaya Contact Center Select by adding option features as appropriate. Install Agent Desktop software on all agent computers. Continue to maintain Avaya Contact Center Select by making frequent data backups.

Simple voice call flow example

The following example shows how a customer call to IP Office is treated by Avaya Contact Center Select and then routed to an agent. By describing a sample call flow, this section also describes how Avaya Contact Center Select integrates with IP Office.

The following diagram shows the communication links between Avaya Contact Center Select and IP Office.



- 1. A Customer dials a number and the call arrives at an IP Office platform. For example, the customer dials 3000.
- 2. An IP Office short code (for example, 6000|>>3000) reroutes the customer call to Avaya Contact Center Select.
- 3. IP Office sends a SIP INVITE message to Avaya Contact Center Select.
- 4. When the SIP INVITE message arrives at Avaya Contact Center Select, it matches the call to one of its configured Route Point URIs and then anchors the customer call on an Avaya Media Server conference port.
- 5. The Avaya Media Server establishes a Real-Time Transport Protocol (RTP) media and voice path with the customer. Avaya Contact Center Select treats the customer's call using this conference port for the remainder of the call lifetime.
- 6. When Avaya Contact Center Select has identified a suitable available agent to handle this call, it sends a SIP INVITE message to IP Office. When the SIP INVITE message arrives at IP Office, it is sent to the destination agent H.323 desk phone.

- 7. IP Office sends a H.323 request to the agent desk phone to indicate that a new customer call has arrived. The agent phone rings and IP Office sends a SIP 180 Ringing message (and a corresponding TAPID Offering CTI message) back to Avaya Contact Center Select. Avaya Contact Center Select uses this trigger to inform the Agent Desktop that a call is alerting on the desk phone. In this way, both the agent desk phone and the Agent Desktop software client show the customer call as ringing.
- 8. When the agent answers the customer call using Agent Desktop software, Avaya Contact Center Select sends a TAPID AnswerCall request to IP Office. This causes the agent desk phone to go off hook and answer the call. IP Office sends a SIP 200 OK message (and corresponding TAPID Connected CTI message) to Avaya Contact Center Select. Avaya Contact Center Select uses CTI to notify Agent Desktop that the customer call has been answered.
- 9. When the call is answered, Real-Time Transport Protocol (RTP) is sent from the agent desk phone to Avaya Media Server. Avaya Media Server conferences the agent and the customer, the customer and the agent can now communicate. The agent has answered the customer's phone call.
- 10. The call remains active until the customer or the agent releases the call.

Sample Orchestration Designer voice flow applications

Avaya Contact Center Select provides a number of sample Orchestration Designer flow applications that treat and route customer voice contacts. Orchestration Designer flow applications contain instructions that determine the sequence of steps that a contact follows after the contact arrives at Avaya Contact Center Select. These steps can include call treatments (such as music or ringback), call routing (such as skill-based routing), or interaction with the caller (entering account numbers).

Applications perform two major functions: they define the path a contact follows, and they provide treatments to a contact as the contact moves through Contact Center. You can also use the applications to track and record information about each step in the progress of a contact, and use this information to analyze how your contact center functions to improve service. Orchestration Designer flow applications are stored in an Avaya Contact Center Select database. Task Flow Executor, a component and service of Avaya Contact Center Select, runs the flow applications to treat customer contacts. A contact is not always answered immediately by an agent. You can provide treatments to the voice contacts while they wait in a queue. These treatments can tell callers the estimated amount of time before their call is answered, or play music to callers while they wait in queue. Additionally, you can use time of day, day of week, or contact center activity to determine how a contact is handled.


Avaya Contact Center Select provides a number of sample voice Orchestration Designer flow applications:

- Customer Service. This is the main application. It welcomes the customer to the contact center, performs some basic boundary checking, and plays a menu offering the customer a small selection of options (talk to the help desk, talk to support, enter your PIN, or leave a message).
- Voice Skill1. This application forwards customer calls to voice skillset Skill1.

- Voice Skill2. This application forwards customer calls to voice skillset Skill2.
- Collect_Digits. This application asks the customer to enter their PIN number using the digits on their phone. The application then plays the number back to the customer and asks them to confirm the PIN number.

Avaya Contact Center Select also provides a number of sample multimedia Orchestration Designer flow applications for the supported multimedia contact types.

The following diagram shows how customer voice contacts to Avaya Contact Center Select are routed and treated by the sample Orchestration Designer flow applications.



Sample Voice Prompt variables

The following table shows the audio media files used by the sample Orchestration Designer flow applications. Orchestration Designer uses these audio .WAV files to play messages (prompts) to the customer. The table shows which Orchestration Designer flow application uses each media file. The table also provides a transcript of the audio in each media file.

Prompt name	Prompt variable name in Orchestration Designer	Prompt transcript	Orchestration Designer flow using this prompt
Welcome_CS	Welcome_CS	"Welcome to the Contact Center."	Customer_Service
Menu_Selection_CS	Menu_Selection_CS	 "Press 1 to speak to an agent at the help desk. Press 2 to speak to an agent in the support center. 	Customer_Service

Table continues...

Prompt name	Prompt variable name in Orchestration Designer	Prompt transcript	Orchestration Designer flow using this prompt
		Press 3 to Enter your Pin Number or any 8 Digits of your choosing.	
		Press 4 to leave a voice mail.	
		Press * to repeat this menu."	
Voicemail_CS	Voicemail_CS	"Please wait while we direct you to our voice messaging system mailbox."	Customer_Service
EnterDigits_CD	EnterDigits_CD	"Please enter your pin number or digits up to a maximum of 8 digits followed by the # key."	Collect_Digits
ConfirmDigits_CD	ConfirmDigits_CD	"The digits you entered were"	Collect_Digits
ValidateDigits_CD	ValidateDigits_CD	"If that is correct press 1 followed by the # key or press 2 if you wish to retry followed by the # key."	Collect_Digits
InvalidEntry_CS	InvalidEntry_CS	"That is an invalid entry please try again."	Customer_Service
NoData_Entry_CS	NoData_Entry_CS	"You have not entered any data Please try again."	Customer_Service
Emergency_CS	Emergency_CS	"The contact center is now in emergency mode and closed. We will reopen shortly."	Customer_Service
OutOfHours_CS	OutOfHours_CS	"The contact center is now closed as it is out of hours."	Customer_Service
Holidays_CS	Holidays_CS	"The contact center is now closed for holidays."	Customer_Service
OutOfService_CS	OutOfService_CS	"All departments are out of service at this time. Please call back at a later time."	Customer_Service

Table continues...

Prompt name	Prompt variable name in Orchestration Designer	Prompt transcript	Orchestration Designer flow using this prompt
PromptSubmenu_CS	PromptSubmenu_CS	"Press 0 to speak to an agent, Press 1 to leave a voice mail, press, Press 9 to return to the main menu."	Customer_Service – submenu 1 and 2
FirstRAN_CD	FirstRAN_CD	"This is the first announcement. Please wait while we try to connect you to our agents."	Collect_Digits – Queuing Tab
SecondRAN_CD	SecondRAN_CD	"This is the second announcement. All our agents are still busy please wait."	Collect_Digits – Iterate Queue Tab

You can modify these media files and replace them with your own recordings. You can record your own voice prompts for the customer, or record voice prompts suitable for your locale (language and dialect). Avaya Contact Center Select provides optimum playback performance with .WAV files encoded as Linear 16-bit PCM, 8KHz Mono with a sampling rate of 128kbits/sec.

Multimedia contacts processing

Contact Center receives multimedia contacts through two external interface points: the email server and the External Web server.

Email server contacts

Email server contacts are retrieved from a POP3 or IMAP capable email server using the Inbound Message Handler (IMH). The IMH runs at regular intervals. You can configure the settings for the IMH (such as the time between intervals and the number of email retrieved from each mailbox during each run) using Contact Center Manager Administration.

The IMH logs on to the mailboxes on the email server as listed in the Email Manager. It parses email in the mailboxes and stores them in the Contact Center Multimedia database. Any attachments associated with an email are stored in the Inbound attachment folder, as specified in Contact Center Manager Administration. After an email is successfully stored in the Contact Center Multimedia database, it is deleted from the email server.

The IMH passes a received email to the Contact Center Multimedia rules engine, which applies rules relevant to the email based on the To address, and invokes the Outbound Message Handler (OMH) to send automatic responses, if any.

External Web server transactions

Contact Center Multimedia receives contacts from the External Web server through the Contact Center Multimedia Web services. The Web services provide a Java API. This enables contacts to be

written into the Contact Center Multimedia database, retrieved from the database, and have their status queried.


Contacts received through the Web services do not pass through the Rules Engine. The External Web server determines the skillset and priority assigned to the contact.

A set of sample pages is distributed with Contact Center Multimedia to provide Java Server Pages (JSP) script examples of how a Web server can access the Web services. You must create your own Web pages, with customized look, feel, and business logic.

Simple email message flow

Avaya Contact Center Select provides routed contact support for email messages. Customers send email messages requesting information or support to a published email address. Avaya Contact Center Select connects to the hosting email server and scans this mailbox (published email address) at regular intervals. Avaya Contact Center Select retrieves the customer's email messages from the email server, processes them (by keywords), and stores them in the database. Avaya Contact Center Select then generates a multimedia (email) contact for each email stored in the database, and routes it to an appropriate and available agent.

The following diagram shows how Avaya Contact Center Select retrieves customer email messages and routes the messages as multimedia contacts to contact center agents.



When you install Avaya Contact Center Select, you configure the email server and a default recipient mailbox. The default settings ensure email messages go only to an agent with the ability to handle email messages. You can customize your contact center with additional skillsets, rule groups and email servers.

To further enhance your customer service, you can configure routing rules to use in rule groups. Use keyword groups and sender groups to decide how to route contacts. Configure which skillset and priority the email contact is assigned to based on the input for routing contacts. Use automatic suggestions for the agent to reply quickly to an email or automatic responses to send a reply to the customer without agent interaction. You can close the contact immediately after the automatic response.

Avaya Contact Center Select supports Email Open Interfaces. You can develop a custom Web service that the Avaya Contact Center Select Email Manager can call when an email message is processed. The custom Web service can perform custom tasks such as manipulating the originating email and modifying the rule routing options.

For more information about configuring Avaya Contact Center Select email contacts and enhancing the customer experience, see *Avaya Contact Center Select Advanced Administration*.

Call Recording

Avaya Contact Center Select supports IP Office Call Recording. IP Office Call Recording provides regulatory type recording, including the option to pause automatic recording for Payment Card Industry (PCI) security compliance. Avaya Contact Center Select supports the Call Recording pause and resume feature when it is initiated from a physical phone set. By default, Avaya Contact Center Select agents have both inbound and outbound call recording enabled.

IP Office Call Recording has two main components:

- Voicemail Pro Voice Recording Library (VRL) records the inbound and outbound agent calls.
- IP Office Contact Recorder stores the recorded calls and associated meta data.

The recorded calls are stored in industry standard .WAV files. When each call is completed, Contact Recorder compresses the audio .wav file and updates the database with a record of the call. These files are stored in a hierarchy of folders on the IP Office server. Each recording results in a .wav file and the associated metadata stored in an XML file:

- Each .wav file contains the actual audio of the recording. Use the Contact Recorder Search and Replay application to locate and playback these recordings.
- Each .xml file contains metadata about the associated .wav recording file. The following are some examples of call recording metadata parameters:
 - Original CLI (P-Asserted-Identity)
 - Agent name
 - Skillset
 - Agent number
 - conference parties
 - start time of the recorded call
 - end time of the recorded call

IP Office Call Recording is a licensed feature. Recordings consume Voicemail Pro channel licenses.

Pause Recording when on Hold: If an Avaya Contact Center Select call is being recorded and the agent puts the call on hold, IP Office Call Recording puts the recording in a suspended state (not terminated), adds a short beep to the recording, and when the call is retrieved from hold the recording is resumed. This entire call is stored in a single .wav file.

User Pause recording: If an Avaya Contact Center Select call is being recorded, and if the agent needs to collect payment card details from a customer, the agent can pause the recording to comply with Payment Card Industry (PCI) requirements. IP Office Call Recording puts the recording in a suspended state (not terminated) and adds a short beep to the recording. After collecting the payment card details, the agent resumes call recording. This entire call is recorded and stored in a single .wav file.

The Agent Desktop user interface does not have a pause button. Agents and agent supervisors must use their physical phone to pause and resume voice contact recording.

Remote Agents

Avaya Contact Center Select (ACCS) supports Remote Agents. This feature allows agents at remote locations to use a phone and Agent Desktop software to handle customer voice contacts routed from ACCS.

ACCS supports the following types of Remote Agent:

- Remote Agents using an IPsec compliant Avaya VPN Router and an Avaya IP desk phone. The Internet Protocol Security (IPsec) compliant Virtual Private Network (VPN) router extends the ACCS network across a public network such as the internet, giving the remote agents secure access to the contact center solution. In this solution type, the agent has a computer, an Avaya IP desk phone, and an Avaya VPN Router in their home or at their remote workplace location. The agent's Avaya IP desk phone and Agent Desktop computer connect to the Avaya VPN Router. The VPN Router connects to ACCS using the internet. The agent uses their Avaya IP desk phone and Agent Desktop software to handle customer voice and multimedia contacts.
- Remote Agents using an IPsec compliant Avaya VPN Router and an Avaya IP Office softphone. The Internet Protocol Security (IPsec) compliant Virtual Private Network (VPN) router extends the ACCS network across a public network such as the internet, giving the emoe agents secure access to the contact center solution. In this solution type, the agent has a computer and an Avaya VPN Router in their home or at their remote workplace location. The agent's Agent Desktop computer and IP Office softphone connect to the Avaya VPN Router. The VPN Router connects to ACCS using the internet. The agent uses Agent Desktop software and the IP Office softphone to handle customer voice and multimedia contacts. ACCS Remote Agent supports IP Office Release 9.0 Softphone and IP Office Release 9.1 Avaya Communicator for Windows.
- Remote Agents using their existing third-party telephones. In this solution type, the agent has a standard residential analog phone and a computer in their home or at their remote workplace location. The agent's phone connects to ACCS using the Public Switched Telephone Network (PSTN) and the Agent Desktop software connects to ACCS using the internet. This type of Remote Agent uses the Telecommuter mode of operation. The agent uses a standard analog phone and Agent Desktop software to handle customer voice and multimedia contacts.

To enable Remote Agent Telecommuter mode:

- 1. Purchase and install a Remote Agent license.
- 2. Enable the Offsite Agent feature in Server Configuration Licensing
- 3. For each remote agent, enable Offsite Agent Allowed for each remote agent in CCMA.
- 4. The agents can then use Agent Desktop to log on from home or another remote location. Agents log on using one of their configured remote phone numbers.

To use Remote Agent, ACCS agents must have a suitable laptop or desktop computer in their home or at their remote workplace location. The agents install Agent Desktop software on this computer. The agents must have a fast and reliable internet connection to the contact center solution. For more information, see *Avaya IP Office Manager*.

Remote Agents log on to Agent Desktop using the *Other Phone* mode. When they log on, the agent telephone rings. This is a nail-up call. Agents must answer this call on their telephone to complete the logon to Agent Desktop. After the logon completes, the agent phone is nailed-up and agents must use Agent Desktop for all subsequent telephony operations. When the agent logs out of ACCS by using the Log Out button on Agent Desktop, ACCS disconnects the nailed-up call. Multimedia contact types appear to a remote agent in exactly the same way as they do to an onsite agent.

Avaya Contact Center Select domain and workgroup support

The Avaya Contact Center Select server is supported in a workgroup or in a Windows domain.

After you deploy the Avaya Contact Center Select Hardware Appliance or Software Appliance, you can add the Avaya Contact Center Select server to a Windows domain.

You can add the Avaya Contact Center Select server to a Windows domain before or after you install the Avaya Contact Center Select software using the Avaya Contact Center Select DVD.

In an Avaya Contact Center Select Business Continuity enabled solution, the Avaya Contact Center Select servers must be in the same Windows domain. To support Business Continuity resiliency, the Avaya Contact Center Select agents must each have an associated Windows domain user account in the same Windows domain as the active and standby servers. Avaya Contact Center Select agents are also supported in domains with a two-way trust relationship with the Avaya Contact Center Select server domain. Avaya Contact Center Select Business Continuity is not supported in a workgroup.

Avaya Contact Center Select domain considerations

Avaya Contact Center Select supports only a Windows Server 2003 Active Directory domain or a Windows Server 2008 Active Directory domain. Avaya Contact Center Select supports a single forest implementation. Avaya Contact Center Select supports agent integration within only those domains in the same forest as the Avaya Contact Center Select domain. Avaya Contact Center Select does not support agent integration across multiple forests, or in domains outside the Avaya Contact Center Select forest.

All Avaya Contact Center Select servers must be in the same Windows Active Directory domain. All Avaya Contact Center Select servers must be registered with the same Windows Active Directory Domain Controller. All Agent Desktop clients must be registered in this domain, or in domains with a two-way trust relationship with this Avaya Contact Center Select server domain.

The Avaya Contact Center Select firewall policy defines the services, network ports, and Windows accounts necessary for contact center voice and multimedia functionality. Avaya Contact Center Select does not provide or install a group policy. A group policy manages and configures software applications and user settings in a given environment. Avaya Contact Center Select cannot be customized to accommodate individual corporate domain structures or group policies, so corporate domains must meet Avaya Contact Center Select requirements.

If you plan to apply a corporate or custom group policy to the Avaya Contact Center Select (ACCS) servers and solution, you must first perform the following:

- Understand the ACCS services, ports, and user account requirements as specified by the ACCS firewall. For more information, see Microsoft Windows Firewall and Advanced Security on your ACCS server to view the inbound/outbound rules.
- Understand the ACCS network ports and transport types. For more information, see <u>Avaya</u> <u>Contact Center Select port matrix</u> on page 150.
- Design or modify your group policy to accommodate these existing ACCS services, ports, user accounts, and transport type requirements.
- Domain group policies and security policies can be configured to automate MS Windows
 updates, server backups, and password expiry rules for local users. These automated features
 are not supported by ACCS. If your group policies or security policies implement these
 automated features, place the ACCS servers in an Active Directory organizational unit (OU)
 container that protects the servers from these automated features.
- During Avaya Contact Center Select commissioning or during a maintenance window, apply and test your group policy. Ensure Avaya Contact Center Select call control, administration and maintenance capabilities are preserved. Do not apply an untested group policy to an Avaya Contact Center Select production environment. If necessary, modify your group policy to preserve Avaya Contact Center Select functionality.
- After successful testing, place ACCS back into production, and continue to monitor the contact center for adverse side effects of your group policy.

For more information about the Avaya Contact Center Select firewall policy and compatibility with corporate domain group policies, see *Avaya Aura Contact Center Security*.

Avaya Contact Center Select servers do not support Dynamic Host Configuration Protocol (DHCP). All Avaya Contact Center Select servers must have a static IP address. Agent Desktop client computers support both DHCP and static IP addresses.

Avaya Security Advisories

Avaya Security Advisories are posted on the Avaya Security Support web site at https://support.avaya.com/security. From the Avaya Support web site, you can register to receive email notifications of Avaya Security Advisories.

The amount of time it takes to receive an Avaya Security Advisory varies depending on the vulnerability classification of the advisory. For more information about vulnerability classifications, responses, and maintenance policies, refer to the following documents:

- Avaya's Product Security Vulnerability Response Policy
- Avaya's Security Vulnerability Classification
- Avaya's Maintenance Contract Requirements for Product Support
- · Avaya Product Security Support Flow

Upgrades and migrations

Migrating from Avaya Contact Center Select to Avaya Aura® Contact Center is not supported.

Migrating from Avaya NES Contact Center to Avaya Contact Center Select is not supported.

Migrating from an Avaya Aura[®] Contact Center AML-based solution to Avaya Contact Center Select is supported.

You can upgrade from Avaya Contact Center Select Release 6.4.1 to Release 6.4.2 by applying the most recent Service Pack. For more information, refer to the Avaya Contact Center Select Service Pack Release Notes.

Reporting Source of Call Disconnect

Avaya Contact Center Select (ACCS) records which party on a contact center call is the first to disconnect from the call. In a typical contact center call, the person who disconnects or hangs up first is the source of call disconnect (SOCD). ACCS supports SOCD monitoring and reporting for inbound contact center contacts. In some countries the agent must not hang-up on a contact center caller. For example, the Brazilian Presidential Decree 6.523 requires that an agent must not disconnect the call while talking to a caller who rang the contact center. Therefore, ACCS records the source of call disconnect (SOCD).

The SOCD information appears in the *Associated Data* field in the Call by Call and Contact Summary reports. The SOCD feature provides the following information about routed contact center contacts:

- Called Party: identifies that the agent disconnected the call
- · Calling Party: identifies that the caller disconnected the call
- Transfer: identifies that an agent transferred the call and completed the transfer
- Conference Party: identifies that the caller or an agent dropped from a call that the initial agent conferenced

- Conference Tear Down: identifies that either the caller or the last agent dropped a call that an agent conferenced
- System: identifies that a system generated event released the call
- If a customer abandons the call, the 'Disconnect Source' is UNKNOWN but a 'Final Disposition' of abandoned is populated.

The following are some limitations of SOCD reporting:

- For direct (non contact center) calls to or from logged-in agents, SOCD is displayed as Unknown for all these call types.
- SOCD is recorded only for logged in ACCS agents. SOCD is not recorded if the ACCS agent is not logged in.
- If the agent that originally received the call starts a conference with another agent, and then drops from the conference, all subsequent SOCD information messages are Conference Tear Down. In this case, reports cannot show accurately which party dropped the call.

Limitations

The following are some of the limitations of Avaya Contact Center Select (ACCS) solutions:

- ACCS registers with IP Office as a SIP User. ACCS must refresh this active registration repeatedly every 180 seconds to prevent the registration expiring. If ACCS fails to refresh the registration, IP Office begins to terminate all active ACCS calls.
 - In the event of an ACCS service or network outage of less than 180 seconds, SIP registration with IP Office might expire and active ACCS calls might begin to terminate.
 - In the event of an ACCS service or network outage of greater than 180 seconds, SIP registration with IP Office expires and IP Office begins to terminate all active ACCS calls.
- If an ACCS agent is directly part of an IP Office conference call and the agent invokes hold on this call, music-on-hold is not streamed by IP Office even if the number of parties on this conference drops to two. Agents can identify whether they are part of this scenario by checking their phone set display for the 'Conference' keyword.
- For CDN to CDN conference, join, barge-in, or emergency call scenarios, if an IP Office softphone agent is a party on this multi-party conference call and invokes hold, music-on-hold might be played into the active multi-party audio stream for a short period of approximately 500 milliseconds before being terminated.
- If a customer dials an agent and this first agent then initiates a consultation with a second agent, the second agent's phone displays the customer's phone number while the consultation call is ringing. After the second agent answers the consultation call, their phone then displays the phone number of the first agent. This is how IP Office processes consultations.
- Call Intrude: The IP Office Call Intrude feature permits an agent to join or barge-in on another
 agent's call. ACCS implements Call Intrude as a Join conference. The intruded agent's call is
 briefly placed on-hold to allow the conference to complete. The intruded party might notice the

- Held state change and consult call leg appear briefly as the operation completes. Hold music might be played briefly to the Intruded party call.
- Manual transfer from softphone: A transfer completed manually on the IP Office softphone appears to Agent Desktop as a Join transfer where a Join is carried out on the main and consult calls with the transferring party then dropped from the call.
- IP Office supports third-party integrations using the IP Office TAPI interface. These third-party
 integrations can potentially interfere with the operation of Avaya Contact Center Select. You
 must configure, implement, and monitor third-party integrations to avoid interfering with Avaya
 Contact Center Select. Third-party applications implementing the IP Office TAPID interface are
 not supported for controlling Agent devices.
- Not all features invoked on the physical phoneset are reflected in Agent Desktop. The following scenarios are some examples of this:
 - Paging: Agents receiving an incoming Page call cannot answer this call using Agent
 Desktop. A Page call can be answered only on the user's phone. A Page call which is
 alerting on a user's phone is displayed in Agent Desktop as a connected call. Agent Desktop
 displays this call as connected if the user answers the Page. Agent Desktop drops this Page
 call if another user answers the Page.
 - Hold Reminder: If a call remains in the Held state longer than the IP Office system wide Hold Timeout configuration setting, then a Hold Reminder notification is displayed on the user's phone. A Hold Reminder notification can be an audio or visual notification. Agent Desktop does not support Hold Reminder notifications; in Agent Desktop the call remains in the Held state. Agents can use Agent Desktop to unhold the held call.
- When an ACCS agent logs on to an IP Office softphone, there is a short delay before the agent can use Agent Desktop software to control that softphone. This short delay can be up to 12 seconds long. Agents using an IP Office softphone are unable to answer incoming calls in Agent Desktop immediately after connecting the softphone to IP Office. However agents can answer these calls on their softphone. This limitation applies only to calls routed to the user in the immediate period after logging on to their softphone. If an agent attempts to answer a call in Agent Desktop during the short timeframe where answer is unavailable an error message is displayed in Agent Desktop. After the answer feature is available any subsequent attempts to answer a call in Agent Desktop are successful. But there is a limitation in that there is no notification in Agent Desktop that the Answer feature is now available.
- When an agent makes an outbound call using Agent Desktop, the Agent Desktop Hold button is immediately available. However, until the remote party answers the call and is connected, any attempt to Hold the call in Agent Desktop results in an error message being displayed.
- Avaya Contact Center Select does not support agent operation from the telephone only. This is commonly referred to as Telephone Mode only support. All Avaya Contact Center Select agents must use Agent Desktop for agent functionality.

The following are call flows that can experience limitations:

- Agent initiated calls (originate or transfer) to a Voicemail Pro call flow which invokes 'assisted transfer' telephony action to a Route Point CDN, are rejected by ACCS.
 - A workaround for this limitation is to use "Transfer" (blind transfer) on Voicemail Pro.

- Agent conferencing a call to a Voicemail Pro call flow which invokes any transfer telephony
 action ('assisted transfer' or 'transfer') to a Route Point CDN, may experience redirection
 limitations such as looping, redirected call being rejected by ACCS, incorrect CLID for the
 redirected call.
- Agent initiated calls to a remote expert where the remote expert forwards the call to a Route Point CDN, may be rejected by ACCS. The call may fail and can be retried.
- An agent conferencing a call (CC call or personal call) on ringing to a user which subsequently redirects the call to a Route Point CDN, causes ACCS to reject this redirected call. The agent remains on the call with the original caller and can reattempt the conference if desired.
- An agent transferring a call (CC call or personal call) on ringing to a user which subsequently redirects the call to a Route Point CDN, can intermittently cause the CLID of the redirected call to be intermittently incorrect. The agent that routed this redirected call may notice an incorrect CLID.

ACCS does not support single-step transfer of Contact Center (CDN) calls to another ACCS agent. The agent receiving the transferred call can answer the call on their phone, but the call is not presented in Agent Desktop and the agent appears as idle in reporting.

· ACCS agents using Avaya Communicator.

When working on a call in Avaya Communicator, selecting the 'Transfer' option from the drop-down menu associated with the call results in a single-step transfer. This is not supported by ACCS. The workaround is to use Agent Desktop to transfer CDN calls. Alternatively, instead of selecting the 'Transfer' option from the drop-down menu in Avaya Communicator, make an unrelated outbound call to the CDN. Then, in Avaya Communicator, drag the two calls together and select 'Transfer' from the resulting menu.

ACCS agents using 1140E/1230 SIP desk phones.

When transferring a call manually using 1140E/1230 SIP desk phones, the user is prompted Yes/No to consult with the destination party. Selecting 'No' results in a single-step transfer. This is not supported by ACCS. The workaround is to use Agent Desktop to transfer CDN calls. Alternatively, when using 1140E/1230 SIP desk phones to transfer calls, select 'Yes' to consult with the destination party.

ACCS agents must not configure Forward on No Answer (FONA) to the DN of another ACCS agent. A Contact Center (CDN) call transferred on ringing to an ACCS agent with FONA configured to another ACCS agent is not supported by ACCS. When FONA is applied and the call is forwarded, the ACCS agent receiving the forwarded call can answer the call on their endpoint but the call is not presented in Agent Desktop and the agent appears to be idle in reporting.

ACCS agents using IP Office Softphones can experience some limitations when performing Hold/ Unhold in Agent Desktop after being transferred to another party. The limitation occurs only when an ACCS agent using IP Office Softphone is transferred to an IP Office user who is also using an IP Office Softphone or Avaya 1140E/1230 desk phones. In Agent Desktop, the Hold/Unhold request does not work, the call state does not change on the IP Office Softphone, and Agent Desktop does not display an error message. In a limited number of cases, due to a limitation of the IP Office Softphone, the call can drop after a period of time. This limitation does not apply to customer calls or when either leg of the transfer operation is a Contact Center (CDN/Route Point) call. To avoid this

limitation, Avaya recommends that ACCS agents using IP Office Softphone perform Hold/Unhold operations using the IP Office Softphone.



Note:

Ensure the Avaya Contact Center Select Redirection feature is enabled. To enable redirection, log on to Contact Center Manager Administration and navigate to Configuration > Global **Settings > Redirection Settings > Media Shuffling on Transfer.**


Chapter 4: Avaya Contact Center Select DVD

The Avaya Contact Center Select DVD software provides a context-sensitive, collaborative, voice and multimedia customer experience solution that allows small to midsize enterprises to anticipate, accelerate, and enhance customer interactions. Avaya Contact Center Select uses the Avaya IP Office telephone system to provide a real-time telephony platform. Avaya IP Office is a flexible and scalable phone system designed specifically for small and midsize enterprises. IP Office supports a wide range of phones and devices for use in contact centers.

The Avaya Contact Center Select DVD deployment option supports Platform Vendor Independence (PVI). PVI gives the customer the flexibility to purchase a server that meets the Avaya Contact Center Select server requirements and conforms with the customer's own corporate standards. To use the Avaya Contact Center Select DVD deployment option, the customer must provide the following:

- Server hardware that meets the Avaya Contact Center Select Platform Vendor Independence (PVI) specification.
- Microsoft Windows 2008 Release 2 with Service Pack 1 64–bit Standard Edition or Enterprise Edition operating system and license.

The following diagram shows the topology of a typical Avaya Contact Center Select solution:



Avaya Contact Center Select is preloaded with sample users, skillsets, and contact center parameters. You can use this sample data to rapidly commission the solution and make the first routed call and email contact. Avaya Contact Center Select delivers quick and simplified contact center deployment. After the basic telephony features are working, you can then configure multimedia contacts, multiplicity, custom prompts, other enhanced features and functions to improve your customer's experience.

To deploy Avaya Contact Center Select software using the DVD software, perform the following:

- Obtain a server that meets the Avaya Contact Center Select PVI requirements.
- Configure the server and format the hard disk partitions to the required specifications.
- Install the Microsoft Windows 2008 Release 2 with Service Pack 1 64-bit Standard Edition or Enterprise Edition operating system.
- License and activate the Microsoft Windows 2008 operating system.
- Obtain an Avaya Contact Center Select DVD and license.
- Use the Avaya Contact Center Select DVD to install the software components and applications.
- Use the Avaya Contact Center Select Configuration Ignition Wizard to rapidly deploy a functional contact center solution.

The Avaya Contact Center Select DVD is supported only on the Microsoft Windows 2008 Release 2 with Service Pack 1 64–bit operating system.

The Avaya Contact Center Select server is supported in a workgroup or in a Windows domain.



The Avaya Contact Center Select DVD deployment option does not support VMware.

Platform Vendor Independence server specification

The Avaya Contact Center Select DVD deployment option supports Platform Vendor Independence (PVI). PVI gives the customer the flexibility to purchase a server that meets the Avaya Contact Center Select server requirements and conforms with the customer's own corporate standards. To use the Avaya Contact Center Select DVD deployment option, the customer must provide server hardware that meets the Avaya Contact Center Select PVI specification.

The Avaya Contact Center Select DVD deployment option supports the following PVI server specifications:

- Entry-level server specification on page 46
- Mid-range server specification on page 47
- High-end server specifications on page 48

The high-end server specifications support the same maximum agent capacity and call rate figures. The mid-range server specification supports a reduced agent capacity and call rate.

For information about achieving the maximum performance from your server hardware, see <u>Server performance and BIOS settings</u> on page 51.

Entry-level single 4-core server specification

The following table lists the minimum specifications for an entry-level single 4-core server.

Specification	Configuration	Comment
CPU	High Speed Quad Core CPU Intel® Xeon® E3-1220 3.1GHz	Select a CPU that exceeds the benchmark rating for the High Speed Quad Core CPU Intel® Xeon® E3-1220 3.1GHz. Relative benchmark comparisons only apply for CPUs with the same number of cores. You can make CPU comparisons by viewing the benchmarked CPU passmark rankings here: http://www.cpubenchmark.net • AMD processors are not supported.
RAM	32 GB minimum	For maximum performance, Avaya recommends that all DIMM slots are populated.

Table continues...

Specification	Configuration	Comment	
Disk Type and Speed	ESATA, SAS, minimum 10000 RPM	15000 RPM disks recommended.	
		IDE drives are not supported.	
		Solid State Drives (SSDs) are not supported.	
Total Disk size	900 GB		
RAID	Hardware RAID-1	Battery backed hardware RAID controller and duplicate drives with identical specifications required.	
DVD Drive	One dual-layer DVD drive	16X or faster recommended. DVD/Blu-Ray combo drives are supported.	
Network Interface	Dual NIC 1 Gbit/s or faster	Only Ethernet is supported.	

Note:

For information about achieving the maximum performance from your server hardware, see Server performance and BIOS settings on page 51.

For servers operating at 40% or above the rated capacity figures for the server type, Avaya recommends that you use a physical database disk drive, separate from the Contact Center application and Operating System disk drives. Variations are allowed for the Windows and Application partitions providing there is sufficient capacity to prevent excessive disk fragmentation.

Mid-range dual 4-core server specification

The following table lists the minimum specifications for a mid-range dual 4–core server.

Specification	Configuration	Comment
CPU	Dual Quad Core Xeon X5667 3.07 GHz	Select a CPU that exceeds the benchmark rating for the Dual Quad Core Xeon X5667 3.07 GHz CPU. Relative benchmark comparisons only apply for CPUs with the same number of cores. You can make CPU comparisons by viewing the benchmarked CPU passmark rankings here: http://www.cpubenchmark.net • AMD processors are not supported.
RAM	32 GB minimum	For maximum performance, Avaya recommends that all DIMM slots are populated.
Disk Type and Speed	ESATA, SAS, minimum 10000 RPM	15000 RPM disks recommended.

Table continues...

Specification	Configuration	Comment
		IDE drives are not supported.
		 Solid State Drives (SSDs) are not supported.
Total Disk size	900 GB	
RAID	Hardware RAID-1	Battery backed hardware RAID controller and duplicate drives with identical specifications required.
DVD Drive	One dual-layer DVD drive	16X or faster recommended. DVD/Blu- Ray combo drives are supported.
Network Interface	Dual NIC 1 Gbit/s or faster	Only Ethernet is supported.
		 Quad NICs are required for virtualized environments where this server is a VMware ESXi host.

Note:

For information about achieving the maximum performance from your server hardware, see Server performance and BIOS settings on page 51.

For servers operating at 40% or above the rated capacity figures for the server type, Avaya recommends that you use a physical database disk drive, separate from the Contact Center application and Operating System disk drives. Variations are allowed for the Windows and Application partitions providing there is sufficient capacity to prevent excessive disk fragmentation.

High-end server specifications

The Avaya Contact Center Select DVD supports the following high-end PVI server specifications:

- High-end server with dual 6-core CPU
- High-end server with dual 8-core CPU
- High-end server with dual 10-core CPU

These high-end server specifications support the same maximum agent capacity and call rate figures.

For servers operating at 40% or above the rated capacity figures for the server type, Avaya recommends that you use a physical database disk drive, separate from the Contact Center application and Operating System disk drives. Variations are allowed for the Windows and Application partitions providing there is sufficient capacity to prevent excessive disk fragmentation.

For information about achieving the maximum performance from your server hardware, see Server performance and BIOS settings on page 51.

High-end dual 6-core server specification

The following table lists the minimum specifications for a high-end server with dual 6-core CPU.

High-end server specification for servers with dual 6–core CPU			
Specification	Configuration	Comment	
CPU	Dual 6–Core Xeon X5680 3.33GHz	Select a CPU that exceeds the benchmark rating for the Dual 6-Core Xeon X5680 3.33GHz CPU. Relative benchmark comparisons only apply for CPUs with the same number of cores. You can make CPU comparisons by viewing the benchmarked CPU passmark rankings here: http://www.cpubenchmark.net • AMD processors are not supported.	
RAM	32 GB minimum	For maximum performance, Avaya recommends that all DIMM slots are populated.	
Disk Type and Speed	ESATA, SAS, minimum 10000	15000 RPM disks recommended.	
	RPM	IDE drives are not supported.	
		Solid State Drives (SSDs) are not supported.	
Total Disk size	900 GB		
RAID	Hardware RAID-1	Battery backed hardware RAID controller and duplicate drives with identical specifications required.	
DVD Drive	One dual-layer DVD drive	16X or faster recommended. DVD and Bluray combo drives are supported.	
Network Interface	Dual 1 Gbit/s or faster	Only Ethernet supported.	
		Quad NICs are required for virtualized environments where this server is a vMware ESXi host.	
		Avaya Media Server configurations require a NIC that supports Receiver Side Scaling (RSS) with a minimum of 4 queues.	

High-end dual 8-core server specification

The following table lists the minimum specifications for a high-end server with dual 8-core CPU.

<u> </u>	High-end server specification for servers with dual 8–core CPU			
Specification	Configuration	Comment		
CPU	Dual Intel Xeon E5-2670 2.60GHz (or faster)	Select a CPU that equals or exceeds the benchmark rating for the Dual 8–core In Xeon E5-2670 2.60GHz CPU. Relative benchmark comparisons only apply for CPUs with the same number of cores. Ye can make CPU comparisons by viewing benchmarked CPU passmark rankings here: http://www.cpubenchmark.net • AMD processors are not supported.		
RAM	32 GB minimum	For maximum performance, Avaya recommends that all DIMM slots are populated.		
Disk Type and Speed	ESATA, SAS, minimum 10000	15000 RPM disks recommended.		
	RPM	IDE drives are not supported.		
		 Solid State Drives (SSDs) are not supported. 		
Total Disk size	900 GB			
RAID	Hardware RAID-1	Battery backed hardware RAID controller and duplicate drives with identical specifications required.		
DVD Drive	One dual-layer DVD drive	16X or faster recommended. DVD and Bluray combo drives are supported.		
Network Interface	Dual 1 Gbit/s or faster	Only Ethernet is supported.		
		 Quad NICs are required for virtualized environments where this server is a VMware ESXi host. 		
		 Avaya Media Server configurations require a NIC that supports Receiver Side Scaling (RSS) with a minimum of 4 queues. 		

High-end dual 10-core server specification

The following table lists the minimum specifications for a high-end server with dual 10-core CPU.

High-end server specification for servers with dual 10–core CPU			
Specification	Configuration	Comment	
CPU	Dual Intel Xeon E5-2680 v2 2.8GHz (or faster)	Select a CPU that equals or exceeds the benchmark rating for the Dual 10–core Intel Xeon E5-2680 v2 2.8GHz CPU. Relative benchmark comparisons only apply for	

Table continues...

High-end server specification for servers with dual 10-core CPU			
Specification	Configuration	Comment	
		CPUs with the same number of cores. You can make CPU comparisons by viewing the benchmarked CPU passmark rankings here: http://www.cpubenchmark.net	
		AMD processors are not supported.	
		Note:	
		CPUs based on more than ten cores are not supported	
RAM	32 GB minimum	For maximum performance, Avaya recommends that all DIMM slots are populated.	
Disk Type and Speed	ESATA, SAS, minimum 10000	15000 RPM disks recommended.	
	RPM	IDE drives are not supported.	
		Solid State Drives (SSDs) are not supported.	
Total Disk size	900 GB		
RAID	Hardware RAID-1	Battery backed hardware RAID controller and duplicate drives with identical specifications required.	
DVD Drive	One dual-layer DVD drive	16X or faster recommended. DVD and Bluray combo drives are supported.	
Network Interface	Dual 1 Gbit/s or faster	Only Ethernet is supported.	
		 Quad NICs are required for virtualized environments where this server is a VMware ESXi host. 	
		 Avaya Media Server configurations require a NIC that supports Receiver Side Scaling (RSS) with a minimum of 4 queues. 	

Server performance and BIOS settings

The Basic Input Output System (BIOS) of a server configures the hardware components and boots the operating system from a storage device. The server operating system (OS) then uses the BIOS to control the server hardware. You must configure the server BIOS settings to ensure optimum performance from the underlying server hardware. For most BIOS settings, you must choose between optimizing a server for power savings or for server performance. For real-time applications such as Avaya Contact Center Select, you must always choose the server BIOS settings that ensure the optimum performance from the underlying server hardware.

Server manufacturers provide their own motherboards, BIOS, hardware, and firmware. Determining the BIOS configuration for your server's hardware can be challenging. There are several BIOS settings that can significantly impact the system performance. When optimizing for system performance, you must select the BIOS settings that enhance the system performance over those that contribute to power savings. Other BIOS settings and recommendations are not as straight forward. Start by consulting the manufacturer's technical data for your server. Avaya recommends that you then test your solution in order to make the best BIOS configuration decisions.

Configure the server hardware, firmware, and Operating System settings to select system performance over power savings.

Server firmware

Firmware is a computer program that is stored on the server motherboard or on an add-on hardware controller. The firmware stored on the server motherboard is called the Basic Input Output System (BIOS). The BIOS is responsible for the behaviour of the system when it is first switched on and for passing control of the server to the operating system. Firmware is also stored in hardware components such as Redundant Array of Independent Disks (RAID) controllers.

Routinely consult the manufacturer's technical data for your servers and, where appropriate, apply the most recent BIOS and firmware updates. The steps required to update firmware or a system BIOS vary depending on the hardware vendor and the component to be updated. Typically, the manufacturer supplies a firmware updating utility. Keeping your server BIOS and firmware at a supported level can improve reliability, serviceability, and help ensure optimum performance.

Power and performance management

For real-time applications such as Avaya Contact Center Select, you must always select the hardware, BIOS, firmware, and Operating System settings that enhance the system performance over those that contribute to power savings.

Intel Xeon CPUs offer two main power management options: C-states and Intel Turbo Boost.

- Disabling C-states lowers latencies to activate the CPUs from halt or idle states to full power on
- Intel Turbo Boost steps up the internal frequency of the processor if the workload requires more power.

These settings depend on the OEM make and model of the server. The BIOS parameter terminology for current Dell and HP servers are described below. Other server makes and models can have other terminology but equivalent BIOS settings.

The following are the recommended BIOS settings for the Dell PowerEdge servers:

- Set the Power Management Mode to Maximum Performance.
- Set the CPU Power and Performance Management Mode to Maximum Performance.
- Processor Settings: set Turbo Mode to enabled
- Processor Settings: set C States to disabled

The following are the recommended BIOS settings for the HP ProLiant servers:

• Set the Power Regulator Mode to Static High Mode.

- Disable Processor C-State Support
- Disable Processor C1E Support
- Disable QPI Power Management
- Enable Intel Turbo Boost

Configure the server hardware, firmware, and Operating System settings to select system performance over power savings.

Disk caching and RAID

Hard disk drives use cache memory to improve read and write access to the disk drives. In write-back mode caching, the disk or RAID controller writes data from the server to cache memory and acknowledges write completion to the server. The server is free to perform other tasks while the disk controller transfers the data from the write cache to the disk drives. This approach significantly increases write performance.

Avaya Contact Center Select supports hardware RAID-1 and RAID-5. RAID technology provides disk data redundancy as well as error detection and correction. For maximum security and mission-critical solutions, Avaya recommends that all Contact Center servers contain a RAID controller. Hardware RAID-1 and RAID-5 are the only levels and types of RAID supported.

Read the hardware documentation for your server to determine how to configure disk caching. Typically, disk caching can be configured as a BIOS setting, a RAID setting, a RAID controller setting, or as an Operating System setting. Some RAID controllers expose the ability to manipulate the Caching Policy through the OS and therefore the OS level setting can override the BIOS level setting. Refer to your hardware documentation for more information about configuring disk caching. Avaya Contact Center Select does not support Operating System level disk caching, software disk caching, or software RAID. Avaya Contact Center Select requires battery backed hardware RAID caching to avoid data loss and possible database corruption on power outage.

Non-Uniform Memory Architecture (NUMA) and memory

Non-uniform memory access (NUMA) is a computer memory design used in multiprocessing, where the memory access time depends on the memory location relative to the processor. Using NUMA, a processor can access its own local memory faster than non-local memory (memory local to another processor or memory shared between processors). For Avaya Contact Center Select, the server must support and implement NUMA.

In the server BIOS settings, configure the memory operating mode for performance optimization and disable Node Interleaving. For example, for a Dell server configure "Memory Operating Mode" as "Optimizer Mode", and configure "Node Interleaving" as "Disabled". Refer to your hardware documentation for more information about NUMA and memory performance.

Hyper-Threading

Hyper-Threading is Intel's proprietary technology for increasing parallel computational power (processor multi-tasking) by allowing the operating system (OS) to see and address each physical processor core as if it were two virtual processors. It also enables the OS and applications to share work between those virtual processors whenever possible, thereby making full use of the available resources.

Enable Hyper-Threading to improve server and Avaya Contact Center Select performance.

Unused hardware devices

On the server, disconnect or disable unused and unnecessary physical hardware devices such as: COM ports, LPT ports, USB controllers, Network interfaces, and Storage controllers. You must retain some USB devices for the mouse and keyboard. Disabling unnecessary hardware devices improves server performance and security. Consult the manufacturer's technical data for your servers for information about disabling unused hardware devices in the BIOS.

Summary

For real-time applications such as Avaya Contact Center Select, choose server BIOS settings that optimize for performance in preference to power savings. Start by consulting the manufacturer's technical data for your server. Avaya recommends that you then test your solution in order to make the best BIOS configuration decisions. Avaya recommends that you enable CPU Hyper-Threading. By enabling BIOS options such as CPU Prefetchers and CPU Hyper-Threading, the system performance can be improved effectively. When tuning system BIOS settings for performance, you must consider the various processor and memory options. Experiment with other options to find the optimum setting for your specific hardware and Contact Center solution.

Configure the server hardware, BIOS, firmware, and Operating System settings to select system performance over power savings.

Avaya Contact Center Select DVD software specification

The Avaya Contact Center Select DVD contains the following software components:

- Contact Center Manager Server (CCMS)
- Contact Center Manager Administration (CCMA)
- Communication Control Toolkit (CCT)
- Contact Center License Manager (LM)
- Contact Center Manager Server Utility (SU)
- Orchestration Designer (OD)
- Contact Center Multimedia (CCMM)
- Avaya Media Server (Avaya MS) MS Windows version
- Contact Center Services for Avaya Media Server
- Avaya Contact Center Select Firewall policy
- Default Avaya Contact Center Select configuration data
- Configuration Ignition Wizard

The Avaya Contact Center Select DVD is supported only on the Microsoft Windows 2008 Release 2 with Service Pack 1 64–bit operating system.

Server naming requirements

Server names must adhere to RFC1123 (Requirements for Internet Hosts), which specifies that a host name must adhere to the following:

- Use only characters a to z, A to Z, and 0 to 9 can be used in a host name.
- You can use a hyphen (-), but not to start or end the host name.
- Host names must be 6 to 15 characters in length.
- Host names must not start with a number.
- Do not use the underscore character (_) and period character (.).
- Do not use spaces in the host name.

The Contact Center server must be able to resolve the host name or computer name of all other servers within the configuration. If you have a Domain Name Service (DNS) server, make sure an entry exists for each server. If you do not have a DNS server, manually update the HOSTS file on each server with the host name or computer name of all other servers to ensure that all clients can interpret the server names.

If network connectivity on your network requires the use of Fully Qualified Domain Names (FQDN), then the FQDN of each computer must be resolvable between all servers associated with Contact Center.

Microsoft security hotfixes

You must operate your server with the most current Microsoft patches.

- Review the Contact Center Portfolio Service Packs Compatibility and Security Hotfixes Applicability List (available from Technical Support Web site) for the list of applicable Microsoft security hotfixes to apply.
- Back up the entire server, and then shut down all Contact Center services before you apply any Microsoft security hotfixes using the Microsoft instructions.
- Apply Microsoft security updates on a timely basis.

Operating system updates

Operating system updates includes service updates and service packs.

Service updates

Given the number of operating system security service updates and the complexity inherent in any network, create a systematic and accountable process for identifying and applying service updates. To help create such a process, you can follow a series of best practices guidelines, as documented in the National Institute of Standards and Technology (NIST) Special Bulletin 800-40, Procedures for Handling Security Patches.

This bulletin suggests that if an organization has no central group to coordinate the storage, evaluation, and chronicling of security service updates into a library, then system administrators or the contact center administrator must fulfill this role. In addition to these guidelines, whenever possible, follow Microsoft recommendations regarding newly discovered vulnerabilities and that you promptly install Microsoft security service updates.

Whenever possible, Avaya incorporates the most recent operating system security recommendations and service updates in an integrated solutions testing strategy during each test cycle. However, due to the urgent nature of security service updates when vulnerabilities are discovered, follow Microsoft guidelines as they are issued, including any Microsoft installation procedures and security service update rollback processes.

Finally, you must perform a full system backup before you update the system to ensure that a rollback is possible, if required. If a Contact Center application does not function properly after you apply a Microsoft security service update, you must remove the service update and revert to the previous version of the application (from the backup you made before applying the service update). For added security, always determine whether Avaya verified the Microsoft service update for compatibility with Contact Center Manager.

For more information about updating, see the *Contact Center Portfolio Service Packs Compatibility* and *Security Hotfixes Compatibility List* on www.avaya.com/support.

Service packs

Avaya has a policy to implement co-residency testing of all new operating service packs for compatibility with the suite of Contact Center applications as soon as they are available. In practice, because a service pack can contain a significant amount of new content, Avaya requires that you wait until compatibility testing is complete before you apply the service pack. Note that operating system service packs are typically tested with the most recent Contact Center application SP and, therefore, an upgrade to a new service pack requires an upgrade to the most recent Avaya SP.

Before you upload a new service pack, you must perform a full system backup (for system rollback as in the updating scenario).

Important:

Service pack compatibility for all Contact Center applications is documented in the *Contact Center Portfolio Service Packs Compatibility and Security Hotfixes Applicability List* on the Web site at www.avaya.com/support.

Java Runtime Environment updates

Contact Center supports only specific versions of Java Runtime Environment (JRE). The Contact Center Installer installs a supported JRE version, and Contact Center service packs install required JRE updates. During installation, Contact Center disables JRE automatic updates on the contact center servers.

Important:

Updating to an unsupported version of JRE can cause the contact center to stop working and can require the reinstallation of the contact center server.

Dynamic Host Configuration Protocol support

Contact Center applications (CCMS, CCMA, CCT, CCMM, LM, and Avaya Media Server) do not support Dynamic Host Configuration Protocol (DHCP). All Contact Center servers must have a static IP address.

Agent Desktop client computers support both DHCP and static IP addresses.

Third-party software requirements

Due to the mission-critical, real-time processing that Contact Center applications perform, you must not install any other application class software on the server. You can install certain utility class software on the server, providing it conforms to the guidelines in this section.

Application class software generally requires a certain amount of system resources and must not be installed on a server running Contact Center applications. The installation of third-party applications can cause Contact Center applications to operate outside of the known engineering limits and can create potential unknown system problems (for example, CPU contentions, increased network traffic loading, disk access degradations).

Certain third-party utility class software applications, such as hardware diagnostics or backup tools, generally require less system resources during the normal operation of Contact Center applications and are permitted. Exceptions are utilities such as screen savers, which can cause system problems and degrade performance.

Antivirus software is classified as a utility and is subject to the generic guidelines in the following section.

Generic guidelines for utility-class software applications

The following are generic guidelines for utility-class software:

- During run-time, the utility must not degrade the contact center application beyond an average percentage of CPU use (see each specific application section in this document for the recommended maximum CPU usage level). Furthermore, the utility must not lower the minimum amount of free hard disk space required by contact center application and the Windows Operating system.
- The utility must not cause improper software shutdowns or out-of-sequence shutdowns.
- The utility must not administer the contact center application.
- If the utility has a database, it must not affect the contact center application database.
- Disk compression utilities must not be used.
- Memory tweaking utilities used to reclaim memory that is unused by Microsoft must not be used.
- The installation or uninstallation of the third-party software must not impact or conflict with the contact center application (for example, it must not cause DLL conflicts). If such conflicts are discovered, a server rebuild might be necessary.
- The implementation personnel must perform tests to ensure these conditions and recommendations are met before you place the Contact Center application into production.

Support personnel can ask for the results of the testing during fault diagnosis. As part of fault diagnosis, the distributor or end user might be asked to remove third-party software.

 HyperTerminal must not be installed on the server as it interferes with the operation of Contact Center.

Guidelines for the use of antivirus software

This section describes the Avaya Contact Center Select antivirus software requirements.

Avaya Contact Center Select supports the following antivirus products:

- Symantec AntiVirus 11.0.5, 11.0.6, or 12
- McAfee 8.8
- Microsoft ForeFront 2010

You can deploy antivirus products from other vendors subject to the following guidelines:

- Infected file quarantine policy on the server and client: antivirus software can be configured to
 clean up the detected virus automatically and files must be quarantined if infected files cannot
 be cleaned. Contact Avaya to verify whether the quarantine file is part of our product files or
 dependent system file. If a virus is detected, remove the server from the network immediately
 during virus eradication to prevent further virus propagation.
- Do not connect a contact center application platform directly to the Internet to download virus
 definitions or updated files. Furthermore, Avaya recommends that you do not use a contact
 center application client PC to connect to the Internet. Instead, download virus definitions and
 updated files to another location on the customer network and manually load them from this
 interim location onto the contact center application platform.
- Perform the previous steps to download Contact Center application service packs (SP). This method limits access to the Internet, and thus reduces the risk of downloading infected files.
- Scan all SP files, DVD-ROMs, and floppy disks before you upload or install to the server. This practice minimizes any exposure to infected files from outside sources.
- Capacity considerations: running virus scan software can place an additional load on a contact center application platform. The implementation personnel must run the performance monitor tool on the server to gauge CPU usage. If the antivirus software scan causes the platform average CPU usage to exceed the recommended percentage for longer than 20 minutes, the antivirus software must not be loaded onto the contact center application platform.
- Product Support do not provide support on the configuration of antivirus software, but offer guidance where possible. Direct questions or problems on antivirus software to the appropriate vendor.
- If performance or functionality issues are raised to Avaya support personnel as part of the fault diagnosis, you might be asked to remove third-party utility software or antivirus software.

Several maintenance tasks are automatically activated at 12:00 midnight. Therefore, you must schedule virus scans at a time other than midnight.

Avaya recommends that you exclude the following files and folders from scans (both real-time and scheduled):

- F:\Avaya\Contact Center\Database\
- <additional database drive>:\Avaya\Database\
- TSM_OAM files located in the following folders:
 - D:\Avaya\Contact Center\Manager Server\iccm\bin\data
 - D:\Avaya\Contact Center\Manager server\iccm\data
 - D:\Avaya\Contact Center\Manager Server\iccm\sdm\log
- OAMContainer*.log located at D:\Avaya\Contact Center\Common Components\CMF
- D:\Avaya\Contact Center\Manager Server\bin\tools2.exeFile access errors occur in the Scan Activity log if you do not exclude this file from scanning.
- D:\Avaya\Contact Center\Manager Server\iccm\logs (SIP logs)
- D:\Avaya\Contact Center\Manager Server\iccm\sgm\config\(SIP log configuration files)
- D:\Avaya\Contact Center\Common Components\CMF
- The folder where you store Server Packs and patches

Contact Center Multimedia interacts with an external email system and enables agents to send attachment files from their computers to the Avaya Contact Center Select server. Both methods of retrieving data are potential sources of software infection.

Avaya recommends the following guidelines for antivirus software:

- Antivirus software must be installed on the email server to ensure that problems are caught at source.
- Agent computers require antivirus software to ensure that attachments sent to the Avaya Contact Center Select server do not have a virus. Contact Center Multimedia does not block specific attachment file types. Third-party antivirus software must be installed on the Portal Server according to guidelines in this document for such utilities.
- Ensure the antivirus software is configured to permit outbound email messages. For example, configure the McAfee antivirus software Access Protection option not to block Prevent mass mailing worms from sending mail.
- Exclude the Contact Center Multimedia partition from being scanned.
- If firewalls on individual computers are enabled on the Agent Desktop computer, the Report
 Listener might be flagged as trying to access the Internet. The properties must be configured to
 allow access for the Report Listener to Contact Center Multimedia through the firewall.
- You must not enable the Microsoft Updater to Auto-Run. Microsoft Updater is configured to alert level so you can schedule updates for off- peak hours.



Warning:

Running a Virus Scan on the Contact Center Multimedia attachment folder, which contains thousands of files, can use significant CPU time on a server and can cause drastic slowdown in agent's response times. Avaya recommends that you run scans, if necessary, during off-peak hours.

To avoid database integrity problems, Avaya recommends that you exclude all CACHE.DAT files, journal files, the cache.cpf file, and any Caché-related files from antivirus scans.

Caché software is installed in <Install drive>: \Avaya\Cache\CacheSys. Databases and journal files are installed in <Install drive>:\Avaya\Contact Center\Databases.

Avaya Contact Center Select DVD licensing

The Avaya Contact Center Select DVD deployment option uses a Nodal Enterprise license delivered as a WebLM XML file. This license file is used to control access to licensed features such as multimedia contacts and multiplicity.

Contact Center License Manager provides central control and administration of licensing for Avaya Contact Center Select. Each Contact Center License Manager includes a local instance of WebLM. When the Contact Center License Manager service starts, it extracts WebLM license keys from the local WebLM instance. Contact Center License Manager then converts the WebLM license keys into local PLIC license keys and distributes the keys the Avaya Contact Center Select applications as required.

- Obtain the network interface MAC address of the Avaya Contact Center Select server.
- Use the MAC address to obtain a nodal WebLM license file from the Avaya Product Licensing and Delivery System (PLDS).
- You load the license file onto the Avaya Contact Center Select server as you run the configuration utility when you are deploying the Avaya Contact Center Select server. When Contact Center License Manager loads the license, if the unique number in the license does not match the Avaya Contact Center Select server MAC address, then License Manager shuts down and Avaya Contact Center Select cannot process contacts. If the unique number in the license matches the Avaya Contact Center Select server MAC address, then License Manager provides license keys, and Avaya Contact Center Select processes customer contacts.


Chapter 5: Avaya Contact Center Select software appliance

For increased productivity, efficiency, and flexibility, Avaya Contact Center Select supports the VMware Open Virtual Appliance (OVA) deployment method. A virtual appliance contains a preinstalled, preconfigured Operating System and an application stack optimized to provide a specific set of services. You can use a single Open Virtual Appliance (OVA) package to distribute a Virtual Appliance. An Avaya Contact Center Select OVA package includes all of the Open Virtualization Format (OVF) information required to create an Avaya Contact Center Select Virtual Appliance on a VMware host.

The Avaya Contact Center Select software appliance consists of the following VMware Virtual Appliances:

- Avaya Contact Center Select OVA
- Avaya Media Server OVA
- Avaya WebLM OVA

The following diagram shows a typical virtualized contact center solution using the Avaya Contact Center Select, Avaya Media Server, and Avaya WebLM Virtual Appliances installed on a single VMware host server:



You can use VMware vSphere or vCenter and these Avaya Contact Center Select OVA packages to create virtual machines in your virtualized environment. The OVA packages are created as VMware hardware version 8 archives.

The Avaya Contact Center Select Virtual Appliances are supported only with the following virtualization environments:

- ESXi 5.0
- ESXi 5.1
- ESXi 5.5

Avaya Contact Center Select supports the Avaya WebLM guest co-resident on the same VMware host server or deployed on a separate VMware host server.

Avaya Contact Center Select supports the Avaya Media Server guest co-resident on the same VMware host server or deployed on a separate VMware host server.

In a virtualized solution, the Avaya Contact Center Select Software Appliance and the connected IP Office telephone system must be hosted on separate VMware host servers.

For more information about the Avaya Contact Center Select software appliance Open Virtual Appliance (OVA) packages, see the following:

- Avaya Contact Center Select OVA on page 63
- Avaya Media Server OVA on page 69
- Avaya WebLM OVA on page 71

Avaya Contact Center Select OVA

Deploy the Avaya Contact Center Select OVA to provide context-sensitive and skill-based routing for customer voice and multimedia contacts.

The Avaya Contact Center Select OVA creates and configures a virtual machine (guest) containing contact center application software. The resulting virtual machine contains a Microsoft Windows operating system, hard disk drive partitions, third-party components, system configuration, and Avaya Contact Center Select application software.

The Avaya Contact Center Select Open Virtual Appliance (OVA) contains the following software:

- Microsoft Windows 2008 Release 2, Service Pack 1, Standard Edition, 64-bit operating system
- Contact Center Manager Server (CCMS)
- Contact Center Manager Administration (CCMA)
- Communication Control Toolkit (CCT)
- Contact Center Multimedia (CCMM)
- Contact Center License Manager (LM)
- Contact Center Manager Server Utility (SU)
- Orchestration Designer (OD)
- Default Avaya Contact Center Select configuration data
- Firewall policy
- Configuration Ignition Wizard
- VMware Tools. Do not update the VMware Tools software unless instructed to do so by Avaya.

The Windows 2008 operating system on the Avaya Contact Center Select OVA is not activated.

Important:

You must supply and install a valid Windows operating system license on the server and activate it within 30 days of the initial power-up. Otherwise the Avaya Contact Center Select server stops working.

The following table shows the operating system on the Avaya Contact Center Select OVA.

Operating System	International Versions Supported	Minimum Service Pack Supported
Windows Server 2008 Release 2, Standard Edition, 64-bit, Service Pack 1.	English	Service Pack 1

The Avaya Contact Center Select OVA package has the following hardware characteristics:

vCPU	Minimum CPU speed	Virtual memory reservation	Number of NICs	Virtual disk storage reservation		on
4	_	16GB	1	Drive	Letter	Size (GB)
				os	C:	80
				CC software	D:	120
					CCMS/CCT database	F:
				CCMM database	H:	200
						610 GB total
				HD drive speed 10000 RPM minimum Deploy the Avaya Contact Center Select OV Thick Provision Lazy Zeroed. Avaya Contact Select does not support thin provisioning.		M minimum
						vaya Contact Center

Note:

Do not change any of these Avaya Contact Center Select OVA VMware guest settings.

Each Avaya Contact Center Select solution requires a Linux-based Avaya Media Server. Each Avaya Contact Center Select solution also requires an additional, separate, Avaya WebLM licensing manager server.

Server naming requirements

Server names must adhere to RFC1123 (Requirements for Internet Hosts), which specifies that a host name must adhere to the following:

- Use only characters a to z, A to Z, and 0 to 9 can be used in a host name.
- You can use a hyphen (-), but not to start or end the host name.
- Host names must be 6 to 15 characters in length.
- Host names must not start with a number.
- Do not use the underscore character () and period character (.).
- Do not use spaces in the host name.

The Contact Center server must be able to resolve the host name or computer name of all other servers within the configuration. If you have a Domain Name Service (DNS) server, make sure an entry exists for each server. If you do not have a DNS server, manually update the HOSTS file on each server with the host name or computer name of all other servers to ensure that all clients can interpret the server names.

If network connectivity on your network requires the use of Fully Qualified Domain Names (FQDN), then the FQDN of each computer must be resolvable between all servers associated with Contact Center.

Microsoft security hotfixes

You must operate your server with the most current Microsoft patches.

- Review the Contact Center Portfolio Service Packs Compatibility and Security Hotfixes Applicability List (available from Technical Support Web site) for the list of applicable Microsoft security hotfixes to apply.
- Back up the entire server, and then shut down all Contact Center services before you apply any Microsoft security hotfixes using the Microsoft instructions.
- Apply Microsoft security updates on a timely basis.

Operating system updates

Operating system updates includes service updates and service packs.

Service updates

Given the number of operating system security service updates and the complexity inherent in any network, create a systematic and accountable process for identifying and applying service updates. To help create such a process, you can follow a series of best practices guidelines, as documented in the National Institute of Standards and Technology (NIST) Special Bulletin 800-40, Procedures for Handling Security Patches.

This bulletin suggests that if an organization has no central group to coordinate the storage, evaluation, and chronicling of security service updates into a library, then system administrators or the contact center administrator must fulfill this role. In addition to these guidelines, whenever possible, follow Microsoft recommendations regarding newly discovered vulnerabilities and that you promptly install Microsoft security service updates.

Whenever possible, Avaya incorporates the most recent operating system security recommendations and service updates in an integrated solutions testing strategy during each test cycle. However, due to the urgent nature of security service updates when vulnerabilities are discovered, follow Microsoft guidelines as they are issued, including any Microsoft installation procedures and security service update rollback processes.

Finally, you must perform a full system backup before you update the system to ensure that a rollback is possible, if required. If a Contact Center application does not function properly after you apply a Microsoft security service update, you must remove the service update and revert to the previous version of the application (from the backup you made before applying the service update). For added security, always determine whether Avaya verified the Microsoft service update for compatibility with Contact Center Manager.

For more information about updating, see the *Contact Center Portfolio Service Packs Compatibility* and *Security Hotfixes Compatibility List* on www.avaya.com/support.

Service packs

Avaya has a policy to implement co-residency testing of all new operating service packs for compatibility with the suite of Contact Center applications as soon as they are available. In practice, because a service pack can contain a significant amount of new content, Avaya requires that you wait until compatibility testing is complete before you apply the service pack. Note that operating system service packs are typically tested with the most recent Contact Center application SP and, therefore, an upgrade to a new service pack requires an upgrade to the most recent Avaya SP.

Before you upload a new service pack, you must perform a full system backup (for system rollback as in the updating scenario).

Important:

Service pack compatibility for all Contact Center applications is documented in the *Contact Center Portfolio Service Packs Compatibility and Security Hotfixes Applicability List* on the Web site at www.avaya.com/support.

Java Runtime Environment updates

Contact Center supports only specific versions of Java Runtime Environment (JRE). The Contact Center Installer installs a supported JRE version, and Contact Center service packs install required JRE updates. During installation, Contact Center disables JRE automatic updates on the contact center servers.

Important:

Updating to an unsupported version of JRE can cause the contact center to stop working and can require the reinstallation of the contact center server.

Dynamic Host Configuration Protocol support

Contact Center applications (CCMS, CCMA, CCT, CCMM, LM, and Avaya Media Server) do not support Dynamic Host Configuration Protocol (DHCP). All Contact Center servers must have a static IP address.

Agent Desktop client computers support both DHCP and static IP addresses.

Third-party software requirements

Due to the mission-critical, real-time processing that Contact Center applications perform, you must not install any other application class software on the server. You can install certain utility class software on the server, providing it conforms to the guidelines in this section.

Application class software generally requires a certain amount of system resources and must not be installed on a server running Contact Center applications. The installation of third-party applications can cause Contact Center applications to operate outside of the known engineering limits and can create potential unknown system problems (for example, CPU contentions, increased network traffic loading, disk access degradations).

Certain third-party utility class software applications, such as hardware diagnostics or backup tools, generally require less system resources during the normal operation of Contact Center applications and are permitted. Exceptions are utilities such as screen savers, which can cause system problems and degrade performance.

Antivirus software is classified as a utility and is subject to the generic guidelines in the following section.

Generic guidelines for utility-class software applications

The following are generic guidelines for utility-class software:

- During run-time, the utility must not degrade the contact center application beyond an average percentage of CPU use (see each specific application section in this document for the recommended maximum CPU usage level). Furthermore, the utility must not lower the minimum amount of free hard disk space required by contact center application and the Windows Operating system.
- The utility must not cause improper software shutdowns or out-of-sequence shutdowns.
- The utility must not administer the contact center application.
- If the utility has a database, it must not affect the contact center application database.
- Disk compression utilities must not be used.
- Memory tweaking utilities used to reclaim memory that is unused by Microsoft must not be used.
- The installation or uninstallation of the third-party software must not impact or conflict with the contact center application (for example, it must not cause DLL conflicts). If such conflicts are discovered, a server rebuild might be necessary.
- The implementation personnel must perform tests to ensure these conditions and recommendations are met before you place the Contact Center application into production. Support personnel can ask for the results of the testing during fault diagnosis. As part of fault diagnosis, the distributor or end user might be asked to remove third-party software.
- HyperTerminal must not be installed on the server as it interferes with the operation of Contact Center.

Guidelines for the use of antivirus software

This section describes the Avaya Contact Center Select antivirus software requirements.

Avaya Contact Center Select supports the following antivirus products:

- Symantec AntiVirus 11.0.5, 11.0.6, or 12
- McAfee 8.8
- Microsoft ForeFront 2010

You can deploy antivirus products from other vendors subject to the following guidelines:

 Infected file quarantine policy on the server and client: antivirus software can be configured to clean up the detected virus automatically and files must be quarantined if infected files cannot be cleaned. Contact Avaya to verify whether the quarantine file is part of our product files or dependent system file. If a virus is detected, remove the server from the network immediately during virus eradication to prevent further virus propagation.

- Do not connect a contact center application platform directly to the Internet to download virus
 definitions or updated files. Furthermore, Avaya recommends that you do not use a contact
 center application client PC to connect to the Internet. Instead, download virus definitions and
 updated files to another location on the customer network and manually load them from this
 interim location onto the contact center application platform.
- Perform the previous steps to download Contact Center application service packs (SP). This method limits access to the Internet, and thus reduces the risk of downloading infected files.
- Scan all SP files, DVD-ROMs, and floppy disks before you upload or install to the server. This practice minimizes any exposure to infected files from outside sources.
- Capacity considerations: running virus scan software can place an additional load on a contact center application platform. The implementation personnel must run the performance monitor tool on the server to gauge CPU usage. If the antivirus software scan causes the platform average CPU usage to exceed the recommended percentage for longer than 20 minutes, the antivirus software must not be loaded onto the contact center application platform.
- Product Support do not provide support on the configuration of antivirus software, but offer guidance where possible. Direct questions or problems on antivirus software to the appropriate vendor.
- If performance or functionality issues are raised to Avaya support personnel as part of the fault diagnosis, you might be asked to remove third-party utility software or antivirus software.

Several maintenance tasks are automatically activated at 12:00 midnight. Therefore, you must schedule virus scans at a time other than midnight.

Avaya recommends that you exclude the following files and folders from scans (both real-time and scheduled):

- F:\Avaya\Contact Center\Database\
- <additional database drive>:\Avaya\Database\
- TSM_OAM files located in the following folders:
 - D:\Avaya\Contact Center\Manager Server\iccm\bin\data
 - D:\Avaya\Contact Center\Manager server\iccm\data
 - D:\Avaya\Contact Center\Manager Server\iccm\sdm\log
- OAMContainer*.log located at D:\Avaya\Contact Center\Common Components\CMF
- D:\Avaya\Contact Center\Manager Server\bin\tools2.exeFile access errors occur in the Scan Activity log if you do not exclude this file from scanning.
- D:\Avaya\Contact Center\Manager Server\iccm\logs (SIP logs)
- D:\Avaya\Contact Center\Manager Server\iccm\sgm\config\(SIP log configuration files)
- D:\Avaya\Contact Center\Common Components\CMF

The folder where you store Server Packs and patches

Contact Center Multimedia interacts with an external email system and enables agents to send attachment files from their computers to the Avaya Contact Center Select server. Both methods of retrieving data are potential sources of software infection.

Avaya recommends the following guidelines for antivirus software:

- Antivirus software must be installed on the email server to ensure that problems are caught at source.
- Agent computers require antivirus software to ensure that attachments sent to the Avaya Contact Center Select server do not have a virus. Contact Center Multimedia does not block specific attachment file types. Third-party antivirus software must be installed on the Portal Server according to guidelines in this document for such utilities.
- Ensure the antivirus software is configured to permit outbound email messages. For example, configure the McAfee antivirus software Access Protection option not to block Prevent mass mailing worms from sending mail.
- Exclude the Contact Center Multimedia partition from being scanned.
- If firewalls on individual computers are enabled on the Agent Desktop computer, the Report Listener might be flagged as trying to access the Internet. The properties must be configured to allow access for the Report Listener to Contact Center Multimedia through the firewall.
- You must not enable the Microsoft Updater to Auto-Run. Microsoft Updater is configured to alert level so you can schedule updates for off- peak hours.



Warning:

Running a Virus Scan on the Contact Center Multimedia attachment folder, which contains thousands of files, can use significant CPU time on a server and can cause drastic slowdown in agent's response times. Avaya recommends that you run scans, if necessary, during off-peak hours.

To avoid database integrity problems, Avaya recommends that you exclude all CACHE.DAT files, journal files, the cache.cpf file, and any Caché-related files from antivirus scans.

Caché software is installed in /Lache Sys. Databases and journal files are installed in <Install drive>:\Avaya\Contact Center\Databases.

Avaya Media Server OVA

Deploy the Avaya Media Server OVA to provide the conference services required by Avaya Contact Center Select.

The Avaya Media Server OVA creates and configures a virtual machine (guest) containing Avaya Media Server software. The resulting virtual machine contains a Linux operating system, hard disk drive, third-party components, system configuration, firewall settings, and Avaya Media Server application software.

You can deploy the Avaya Media Server OVA on the same VMware host server as the Avaya Contact Center Select OVA and the Avaya WebLM OVA. Alternatively, you can deploy the Avaya Media Server OVA standalone on a separate VMware host server.

The Avaya Media Server OVA contains information about the guest server specification, guest operating system, and application software. This OVA contains the following components:

- Red Hat Enterprise Linux 6.6 64bit
- Avaya Media Server 7.6 software
- Contact Center Services for Avaya Media Server
- IP tables firewall file application
- VMware Tools. Do not update the VMware Tools software on this virtual machine unless instructed to do so by Avaya.

The Avaya Media Server OVA is not supported in High Availability solutions. Virtualized Avaya Media Server does not support High Availability.

Avaya Media Server is a software based media processing platform. Avaya Contact Center Select includes an enhanced version of Avaya Media Server which contains an additional component— Contact Center Services for Avaya Media Server. The Contact Center Services packaged application provides the conference services required by SIP-enabled Contact Center.

The Avaya Media Server OVA package has the following default hardware configuration:

vCPU	Minimum CPU speed	Virtual memory required	Number of NICs	Virtual disk stora	ge required
8	_	12GB	1	Size	80 GB
				using Thick Provis	Media Server OVA sion Lazy Zeroed. ver does not support



Note:

Do not change any of these Avaya Media Server OVA VMware guest settings.

In a virtualized Avaya Contact Center Select environment, you can use VMware to load the Avaya Media Server OVA package into a virtual machine (guest) in your contact center solution. The virtualized Avaya Contact Center Select server can then use the virtualized Avaya Media Server as a voice media processor.

The Avaya Media Server OVA creates two Linux accounts; root and amsuser (for Element Manager). You must use VMware console to log on to the Avaya Media Server guest as the root administrator and set an initial password, before you can gain access to the system either locally, using SSH, or using Element Manager.

Deploy the Avaya Media Server OVA using Disk Format - Thick Provision Lazy Zeroed. Avaya Media Server does not support thin provisioning.

WebLM OVA

Deploy the Avaya WebLM OVA to provide solution licensing. You can deploy the Avaya WebLM OVA on the same VMware host server as the Avaya Contact Center Select Voice and Multimedia Contact Server OVA and the Avaya Media Server OVA. Alternatively, you can also deploy the Avaya WebLM OVA standalone on a separate VMware host server.

After you have deployed the WebLM OVA, you can apply WebLM patches, feature packs, or service packs. For example, you can install a WebLM patch to upgrade WebLM from Release 6.3.2 to Release 6.3.8.

Each Avaya Contact Center Select supports one WebLM license manager server. Each WebLM license manager server supports one Avaya Contact Center Select. For increased efficiency and flexibility, the WebLM licensing manager supports the VMware Virtual Appliance and Open Virtualization Archive (OVA) deployment mechanisms. In a virtualized Avaya Contact Center Select environment, you can use VMware to load the WebLM OVA package onto a separate virtual machine in your contact center solution. The virtualized Avaya Contact Center Select server can then use the virtualized WebLM server as the license manager.

The WebLM OVA contains a hardened Linux operating system.

The Avaya WebLM OVA requires the following:

vCPU	Minimum CPU speed	Virtual memory reservation	Number of NICs	Virtual disk storage reservation
1	_	1 GB	1 shared	30 GB



Note:

Do not change any of these Avaya WebLM OVA VMware guest settings.

The WebLM OVA uses the following network mapping:

WebLM Server VM Interface	Application
Eth0	License management

The WebLM server for VMware is packaged as a vAppliance ready for deployment using either VMware vSphere Client or VMware vCenter.

Deploy the WebLM OVA using Disk Format - Thick Provision Lazy Zeroed. WebLM does not support thin provisioning in production environments.

VMware host server specification

The Avaya Contact Center Select software appliance is a set of VMware Open Virtual Appliance (OVA) virtualized servers; an Avaya Contact Center Select OVA, an Avaya Media Server OVA, and a WebLM OVA. You can deploy the Avaya Contact Center Select software appliance (3x OVAs) on a VMware ESXi host server that meets the 8–core or 10–core High-end Platform Vendor Independence server specifications.

Platform Vendor Independence (PVI) gives the customer the flexibility to purchase a server that meets the Avaya Contact Center Select server requirements and conforms with the customer's own corporate standards. To use the Avaya Contact Center Select software appliance deployment option, the customer must provide VMware ESXi host hardware that meets the Avaya Contact Center Select PVI specification.

The Avaya Contact Center Select software appliance is supported on VMware ESXi hosts that meet the following PVI specifications:

- High-end dual 8-core server specification
- High-end dual 10-core server specification

These high-end server specifications support the same maximum agent capacity and call rate figures. The Avaya Contact Center Select software appliance is not supported on the High-end dual 6–core, Mid-range, or Entry-level specifications.



Provision only vCPUs up to the number of physical cores on the VMware host.

High-end dual 8-core server specification

The following table lists the minimum specifications for a high-end server with dual 8–core CPU.

High-end server specification for servers with dual 8–core CPU		
Specification	Configuration	Comment
CPU	Dual Intel Xeon E5-2670 2.60GHz (or faster)	Select a CPU that equals or exceeds the benchmark rating for the Dual 8–core Intel Xeon E5-2670 2.60GHz CPU. Relative benchmark comparisons only apply for CPUs with the same number of cores. You can make CPU comparisons by viewing the benchmarked CPU passmark rankings here: http://www.cpubenchmark.net • AMD processors are not supported.
RAM	32 GB minimum	For maximum performance, Avaya recommends that all DIMM slots are populated.
Disk Type and Speed	ESATA, SAS, minimum 10000 RPM	 15000 RPM disks recommended. IDE drives are not supported. Solid State Drives (SSDs) are not supported.

Table continues...

High-end server specification	High-end server specification for servers with dual 8–core CPU							
Specification	Configuration	Comment						
Total Disk size	900 GB							
RAID	Hardware RAID-1	Battery backed hardware RAID controller and duplicate drives with identical specifications required.						
DVD Drive	One dual-layer DVD drive	16X or faster recommended. DVD and Bluray combo drives are supported.						
Network Interface	Dual 1 Gbit/s or faster	Only Ethernet is supported.						
		Quad NICs are required for virtualized environments where this server is a VMware ESXi host.						
		Avaya Media Server configurations require a NIC that supports Receiver Side Scaling (RSS) with a minimum of 4 queues.						

High-end dual 10-core server specification

The following table lists the minimum specifications for a high-end server with dual 10-core CPU.

High-end server specifica	High-end server specification for servers with dual 10–core CPU							
Specification	Configuration	Comment						
CPU	Dual Intel Xeon E5-2680 v2 2.8GHz (or faster)	Select a CPU that equals or exceeds the benchmark rating for the Dual 10–core Intel Xeon E5-2680 v2 2.8GHz CPU. Relative benchmark comparisons only apply for CPUs with the same number of cores. You can make CPU comparisons by viewing the benchmarked CPU passmark rankings here: http://www.cpubenchmark.net • AMD processors are not supported. ** Note: CPUs based on more than ten cores are not supported						
RAM	32 GB minimum	For maximum performance, Avaya recommends that all DIMM slots are populated.						
Disk Type and Speed	ESATA, SAS, minimum 10000 RPM	15000 RPM disks recommended.IDE drives are not supported.						

High-end server specif	High-end server specification for servers with dual 10–core CPU						
Specification	Configuration	Comment					
		Solid State Drives (SSDs) are not supported.					
Total Disk size	900 GB						
RAID	Hardware RAID-1	Battery backed hardware RAID controller and duplicate drives with identical specifications required.					
DVD Drive	One dual-layer DVD drive	16X or faster recommended. DVD and Bluray combo drives are supported.					
Network Interface	Dual 1 Gbit/s or faster	Only Ethernet is supported.					
		 Quad NICs are required for virtualized environments where this server is a VMware ESXi host. 					
		Avaya Media Server configurations require a NIC that supports Receiver Side Scaling (RSS) with a minimum of 4 queues.					

Virtualization considerations

Using virtualization in a contact center enterprise solution requires careful up-front planning, engineering, and implementation. While the technical and business advantages are clear, virtualization imposes extra considerations when designing the contact center solution architecture. Environmental isolation allows multiple operating systems to run on the same VMware host machine. While virtualization offers these forms of isolation, virtualization environments do not provide performance isolation. The behavior of one virtual machine can adversely affect the performance of another virtual machine on the same host. Most modern virtualization environments provide mechanisms that you can use to detect and reduce performance interference. You must carefully engineer your virtualized contact center solution to avoid performance interference.

If you plan to install non-Contact Center software applications on the other guests of a host server with Contact Center installed, you must carefully analyze the impact of these applications on the contact center solution and provide extra performance isolation to safeguard Contact Center functionality.

Important:

Deploy Contact Center on an enterprise-grade virtual environment with the most recent hardware that supports hardware-assisted virtualization. Avaya recommends that you apply virtualization planning, engineering, and deployment with full organizational support for virtualization rather than organically growing a virtualization infrastructure.

VMware features

Avaya Contact Center Select is a collection of real-time applications running on the MS Windows Server 2008 R2 SP1 operating system. Avaya Contact Center Select provides real-time call control, multimedia handling, and statistical reporting.

Avaya Media Server is a real-time media processing application running on the Red Hat Enterprise Linux (RHEL) operating system. Avaya Media Server provides the real-time conferencing and media processing capabilities for Avaya Contact Center Select.

Some VMware features require CPU, Disk I/O, or networking resources to function. Running these VMware features can cause resource constraints and impact the real-time performance of the Avaya Contact Center Select and Avaya Media Server Virtual Machines (VMs). These features are therefore not supported while Avaya Contact Center Select or Avaya Media Server are active.

Some VMware features are not supported by Avaya Contact Center Select or Avaya Media Server. Some other VMware features are supported only while the Avaya Contact Center Select or Avaya Media Server Virtual Machines are stopped for maintenance.

The following table shows the Avaya Contact Center Select and Avaya Media Server level of support for VMware features.

VMware Feature	Supported on active Avaya Contact Center Select VM	Supported during Avaya Contact Center Select VM maintenance window	Supported on active Avaya Media Server VM	Supported during Avaya Media Server VM maintenance window
Cloning	No	Yes	No	No
Distributed Power Management (DPM)	No	Yes	No	Yes
Distributed Resources Scheduler (DRS)	No	Yes No Yes		Yes
Distributed Switch	Yes	Yes	No	No
Fault Tolerance	No	No	No	No
High Availability (HA)	No	No	No	No
Snapshots	No	See Avaya Contact Center Select VMware snapshot considerations on page 81	No	See Avaya Media Server VMware snapshot considerations on page 81
Storage DRS	No	Yes	No	Yes
Storage Thin Provisioning	No	N/A	No	N/A
Storage vMotion	No	Yes	No	Yes

VMware Feature	Supported on active Avaya Contact Center Select VM	Supported during Avaya Contact Center Select VM maintenance window	Supported on active Avaya Media Server VM	Supported during Avaya Media Server VM maintenance window
Suspend & Resume	No	N/A	No	N/A

VMware vSphere Host considerations

When planning virtual machines (guests) on your host system, the total resources needed by the virtual machines running on the host server must not exceed the total capacity of the host. It is good practice to under-commit CPU and memory resources on the host. If the host CPU capacity is overloaded, Contact Center does not function correctly.

Important:

Avaya Contact Center Select is not supported on an over-committed host where the total virtual resources from all virtual machines hosted exceeds the physical resources of the host.

Hardware-Assisted Virtualization

Most recent enterprise-level processors from Intel support virtualization. There are two generations of virtualization support: the first generation introduced CPU virtualization; the second generation included CPU virtualization and added memory management unit (MMU) virtualization. For the best performance, make sure your system uses processors with at least second-generation hardware-assist features.

Virtual Machine File System (VMFS)

VMware virtual machines and snapshots are stored in a Virtual Machine File System (VMFS) datastore. To support Avaya Contact Center Select on a virtual machine, the VMware datastore containing Contact Center must be VMFS 5.54 or later. If you upgrade an existing VMware host server, ensure the associated datastore is upgraded to VMFS 5.54 or later.

Hardware-Assisted CPU Virtualization (Intel VT-x)

The first generation of hardware virtualization assistance includes VT-x from Intel. These technologies automatically trap sensitive interrupts, eliminating the overhead required to do so in software. This allows the use of a hardware virtualization (HV) virtual machine monitor (VMM).

Hardware-Assisted MMU Virtualization (Intel EPT)

More recent enterprise-level processors also include a feature that addresses the overheads due to memory management unit (MMU) virtualization by providing hardware support to virtualize the MMU. VMware vSphere supports this feature in Intel processors, where it is called Extended Page Tables (EPT).

Storage Area Network (SAN)

A Storage Area Network (SAN) is a dedicated storage network that provides access to consolidated block level storage. SANs are used to make storage devices such as disk arrays, accessible to servers so that the devices appear as locally attached to the operating system.

When Avaya Contact Center Select is installed on virtual machines it supports a SAN. You must monitor the Contact Center demand on the SAN storage device. Adhere to your vendor-specific SAN configuration recommendations to ensure the SAN storage device meets the demands of Contact Center.

Disk drive provisioning

Provision sufficient hard disk drive space on the host server to support all the guest virtual machines, an ISO library, and provision additional space for snapshot image storage.

Server performance and BIOS settings

The Basic Input Output System (BIOS) of a server configures the hardware components and boots the operating system from a storage device. The server operating system (OS) then uses the BIOS to control the server hardware. You must configure the server BIOS settings to ensure optimum performance from the underlying server hardware. For most BIOS settings, you must choose between optimizing a server for power savings or for server performance. For real-time applications such as Avaya Contact Center Select, you must always choose the server BIOS settings that ensure the optimum performance from the underlying server hardware.

Server manufacturers provide their own motherboards, BIOS, hardware, and firmware. Determining the BIOS configuration for your server's hardware can be challenging. There are several BIOS settings that can significantly impact the system performance. When optimizing for system performance, you must select the BIOS settings that enhance the system performance over those that contribute to power savings. Other BIOS settings and recommendations are not as straight forward. Start by consulting the manufacturer's technical data for your server. Avaya recommends that you then test your solution in order to make the best BIOS configuration decisions.

Configure the server hardware, firmware, and Operating System settings to select system performance over power savings.

Server firmware

Firmware is a computer program that is stored on the server motherboard or on an add-on hardware controller. The firmware stored on the server motherboard is called the Basic Input Output System (BIOS). The BIOS is responsible for the behaviour of the system when it is first switched on and for passing control of the server to the operating system. Firmware is also stored in hardware components such as Redundant Array of Independent Disks (RAID) controllers.

Routinely consult the manufacturer's technical data for your servers and, where appropriate, apply the most recent BIOS and firmware updates. The steps required to update firmware or a system BIOS vary depending on the hardware vendor and the component to be updated. Typically, the manufacturer supplies a firmware updating utility. Keeping your server BIOS and firmware at a supported level can improve reliability, serviceability, and help ensure optimum performance.

Power and performance management

For real-time applications such as Avaya Contact Center Select, you must always select the hardware, BIOS, firmware, and Operating System settings that enhance the system performance over those that contribute to power savings.

Intel Xeon CPUs offer two main power management options: C-states and Intel Turbo Boost.

- Disabling C-states lowers latencies to activate the CPUs from halt or idle states to full power on.
- Intel Turbo Boost steps up the internal frequency of the processor if the workload requires more power.

These settings depend on the OEM make and model of the server. The BIOS parameter terminology for current Dell and HP servers are described below. Other server makes and models can have other terminology but equivalent BIOS settings.

The following are the recommended BIOS settings for the Dell PowerEdge servers:

- Set the Power Management Mode to Maximum Performance.
- Set the CPU Power and Performance Management Mode to Maximum Performance.
- Processor Settings: set Turbo Mode to enabled
- · Processor Settings: set C States to disabled

The following are the recommended BIOS settings for the HP ProLiant servers:

- Set the Power Regulator Mode to Static High Mode.
- Disable Processor C-State Support
- Disable Processor C1E Support
- Disable QPI Power Management
- Enable Intel Turbo Boost

Configure the server hardware, firmware, and Operating System settings to select system performance over power savings.

Disk caching and RAID

Hard disk drives use cache memory to improve read and write access to the disk drives. In write-back mode caching, the disk or RAID controller writes data from the server to cache memory and acknowledges write completion to the server. The server is free to perform other tasks while the disk controller transfers the data from the write cache to the disk drives. This approach significantly increases write performance.

Avaya Contact Center Select supports hardware RAID-1 and RAID-5. RAID technology provides disk data redundancy as well as error detection and correction. For maximum security and mission-critical solutions, Avaya recommends that all Contact Center servers contain a RAID controller. Hardware RAID-1 and RAID-5 are the only levels and types of RAID supported.

Read the hardware documentation for your server to determine how to configure disk caching. Typically, disk caching can be configured as a BIOS setting, a RAID setting, a RAID controller

setting, or as an Operating System setting. Some RAID controllers expose the ability to manipulate the Caching Policy through the OS and therefore the OS level setting can override the BIOS level setting. Refer to your hardware documentation for more information about configuring disk caching. Avaya Contact Center Select does not support Operating System level disk caching, software disk caching, or software RAID. Avaya Contact Center Select requires battery backed hardware RAID caching to avoid data loss and possible database corruption on power outage.

Non-Uniform Memory Architecture (NUMA) and memory

Non-uniform memory access (NUMA) is a computer memory design used in multiprocessing, where the memory access time depends on the memory location relative to the processor. Using NUMA, a processor can access its own local memory faster than non-local memory (memory local to another processor or memory shared between processors). For Avaya Contact Center Select, the server must support and implement NUMA.

In the server BIOS settings, configure the memory operating mode for performance optimization and disable Node Interleaving. For example, for a Dell server configure "Memory Operating Mode" as "Optimizer Mode", and configure "Node Interleaving" as "Disabled". Refer to your hardware documentation for more information about NUMA and memory performance.

Performance management and VMware

For VMware host servers, to allow the VMware kernel to control CPU power saving while maximizing server performance when required, it is possible to set power management in the BIOS to "OS Control Mode". The VMware hypervisor can then provide balanced performance and power management. This BIOS setting and VMware feature combination does not meet the real-time performance requirements of Avaya Contact Center Select. Avaya Contact Center Select does not support the BIOS "OS Control Mode" settings or its equivalents.

Virtualization technology

When virtualization technology is enabled, the BIOS enables processor virtualization features and provides virtualization support to the operating system through the DMAR table. In general, only virtualized environments such as VMware take advantage of these features.

For VMware host servers, enable all available Virtualization Technology options in the hardware BIOS. For Intel based hosts: Enable Intel virtualization (VT-x) and if available enable Extended Page Tables (EPT)The available virtualization settings vary by hardware provider and BIOS version. Read your hardware provider's documents covering virtualization support to determine which settings to configure.

Hyper-Threading

Hyper-Threading is Intel's proprietary technology for increasing parallel computational power (processor multi-tasking) by allowing the operating system (OS) to see and address each physical processor core as if it were two virtual processors. It also enables the OS and applications to share work between those virtual processors whenever possible, thereby making full use of the available resources.

Enable Hyper-Threading to improve server and Avaya Contact Center Select performance.

Unused hardware devices

On the server, disconnect or disable unused and unnecessary physical hardware devices such as: COM ports, LPT ports, USB controllers, Network interfaces, and Storage controllers. You must retain some USB devices for the mouse and keyboard. Disabling unnecessary hardware devices improves server performance and security. Consult the manufacturer's technical data for your servers for information about disabling unused hardware devices in the BIOS.

Summary

For real-time applications such as Avaya Contact Center Select, choose server BIOS settings that optimize for performance in preference to power savings. Start by consulting the manufacturer's technical data for your server. Avaya recommends that you then test your solution in order to make the best BIOS configuration decisions. Avaya recommends that you enable CPU Hyper-Threading. By enabling BIOS options such as CPU Prefetchers and CPU Hyper-Threading, the system performance can be improved effectively. When tuning system BIOS settings for performance, you must consider the various processor and memory options. Experiment with other options to find the optimum setting for your specific hardware and Contact Center solution.

Configure the server hardware, BIOS, firmware, and Operating System settings to select system performance over power savings.

VMware networking best practices

There are many different ways of configuring networking in a VMware environment. Review the VMware networking best practices documentation before deploying Avaya applications on an ESXi host. This section is not a substitute for the VMware documentation. For improved performance and best practice, Contact Center uses Network Adapter type VMXNET 3.

The following are some suggested networking best practices:

- Separate network services to achieve greater security and performance. Create a vSphere Standard Switch with dedicated NICs for each service. Separate VMware Management, iSCSI (SAN traffic), and VM networks to separate physical NICs. If separate switches are not possible, consider port groups with different VLAN IDs.
- All physical NICs that are connected to the same vSphere *Standard Switch* must be connected to the same physical network.
- Configure all VMkernal vNICs to the same MTU (IP Maximum Transmission Unit).
- Configure Contact Center to use Network Adapter type VMXNET 3.

For more information about VMware networking best practices, refer to the VMware documentation.

Avaya Contact Center Select VMware snapshot considerations

VMware snapshots save the current state of the virtual machine, so you can return to it at any time. Snapshots are useful when you need to revert a virtual machine repeatedly to the same state, but you don't want to create multiple virtual machines.

The following considerations apply when using snapshots with Avaya Contact Center Select on VMware:

- Snapshots must be taken during an Avaya Contact Center Select maintenance window. Do not
 take a snapshot of a Contact Center virtual machine while Contact Center is running.
 Snapshots have a negative impact on the performance of a virtual machine over time. You
 must Consolidate snapshots at the end of the maintenance window, before putting the Contact
 Center virtual machine back into production. For more information about consolidating
 snapshots, refer to VMware documentation.
- Create a snapshot for the Contact Center virtual machines all at the same time. Likewise, when
 you restore a snapshot, restore all snapshots to ensure the data is consistent across the
 Contact Center suite.
- When restoring snapshots, carefully consider the possible impact from out-of-date antivirus definitions, missed Microsoft Windows OS and security updates, and lapsed domain accounts on the contact center. Isolate the restored virtual machine until these issues are resolved.
- By default, a Windows Server 2008 machine account password is changed every 30 days. This
 is an important consideration when reverting to a snapshot of a virtual machine that has been
 in use for more than 30 days, as it can cause the machine to lose its connection to the
 Windows domain. If this issue occurs, rejoin the Windows Server 2008 virtual machine to the
 domain.

VMware snapshots are not a replacement for Avaya Contact Center Select database backup (and restore) procedures and practices. You must continue to perform regular and frequent Contact Center backups. For more information about maintenance, see *Deploying Avaya Contact Center Select Software Appliance*.

Avaya Media Server VMware snapshot considerations

VMware snapshots save the current state of the virtual machine, so you can return to it at any time. Snapshots are useful when you need to revert a virtual machine repeatedly to the same state, but you don't want to create multiple virtual machines.

The following considerations apply when using snapshots with Avaya Media Server on VMware:

Snapshots must be taken during an Avaya Media Server maintenance window. Do not take a
snapshot of an Avaya Media Server virtual machine while the contact center is running.
Snapshots have a negative impact on the performance of a virtual machine over time. You
must Consolidate snapshots at the end of the maintenance window, before putting the Avaya
Media Server virtual machine back into production. For more information about consolidating
snapshots, refer to VMware documentation.

 When restoring snapshots, carefully consider the possible impact from out-of-date antivirus definitions, missed Linux operating system updates and security updates. Isolate the restored virtual machine until these issues are resolved.

VMware snapshots are not a replacement for Avaya Media Server database backup (and restore) procedures and practices. For more information about maintenance, see *Deploying Avaya Contact Center Select Software Appliance*.

Guidance for storage requirements

Input/Outputs per Second (IOPS) is a measure of the maximum number of reads and writes to *non-contiguous* storage locations performed per second. IOPS measurements are associated with smaller files and more continuous changes, and comprise the workloads most typical in real-time enterprise applications such as Avaya Contact Center Select.

In a virtualized environment, any given storage array must be designed to have an IOPS capacity exceeding the sum of the IOPS required for all resident applications.

For a fully loaded Avaya Contact Center Select instance, the IOPS is:

Average: 105Maximum: 1488

These IOPS figures include Avaya Contact Center Select and the underlying operating system loads.

Performance monitoring and management

You must continuously monitor and measure the performance of the Contact Center host server. You can use VMware vSphere vCenter to measure the critical host performance metrics in real-time. VMware vCenter aggregates and archives performance data so that data can be visualised and reported on.

Configure VMware vCenter statistics collection to collect 5 minute and 30 minute Interval Duration data for the host at Statistics Level 3. Retain the 5 minute Interval Duration data for 3 days and retain the 30 minute Interval Duration for 1 week.

Generate performance reports using vCenter Report Performance and archive these reports to provide a baseline performance reference. Generate and store 1-day and 1-week reports. Store the associated vCenter Report Summary with the performance reports. You must analyze performance reports after changes to the host to assess the impact of the change on the host.

Monitor, acknowledge, and resolve VMware vCenter alarms. In particular, you must immediately investigate and resolve host CPU usage and host memory usage alarms.

In addition, the command-line tools "esxtop" and "resxtop" are available to provide a fine-grained look at real-time metrics. There are a number of critical CPU-related counters to watch out for:

- If the load average listed on the first line of the CPU Panel is equal to or greater than the number of physical processors in the system, this indicates that the system is overloaded.
- The usage percentage of physical CPUs on the PCPU line can indicate an overloaded condition. In general, 80 percent usage is a reasonable ceiling in production environments. Use 90 percent as an alert to the VMware administrator that the CPUs are approaching an overloaded condition, which must be addressed.
- %RDY The percentage of time a schedulable entity was ready to run but is not scheduled to a core. If %RDY is greater than 10 percent, then this can indicate resource contention.
- %CSTP The percentage of time a schedulable entity is stopped from running to allow other vCPUs in the virtual machine to catch up. If %CSTP is greater than 5 percent, this usually means the virtual machine workload is not using VCPUs in a balanced fashion. High %CSTP can be an indicator of a system running on an unconsolidated snapshot.

For more information about using esxtop or resextop, see the *VMware Resource Management Guide*.

Memory Reservations

Use VMware Reservations to specify the minimum amount of memory for a Contact Center virtual machine. VMware Reservations maintain sufficient host memory to fulfill all reservation guarantees. ESX does not power-on a virtual machine if doing so reduces the amount of available memory to less than the amount reserved. Using reservations can reduce the total number of virtual machines that can be hosted on a VMware host server. After all resource reservations have been met, ESX allocates the remaining resources based on the number of shares and the resource limits configured for your virtual machine.

Troubleshooting VMware

Virtualization platform performance issues can result with Contact Center performance problems. The virtualization platform includes the host and the running virtual machines on the host. The Contact Center performance problems can include (but are not limited to) high CPU usage, link instability, defaulted or abandoned calls.

You must logically and systematically investigate any Contact Center performance issues to rule out virtualization performance problems. All deviations from the published specifications must be investigated and resolved before the Contact Center software investigation is initiated. For more information, refer to the VMware vSphere documentation.

To support troubleshooting VMware resourcing issues, collect information about the following VMware Key Performance Indicators (KPIs).

VMware vSphere Host KPIs:

- Physical CPU
 - PCPU Physical CPU usage.
 - CPU load average Average CPU load average of host.

- Physical Memory
 - SWAP/MB Memory swap usage statistics.

VMware vSphere Virtual Machine (VM) KPIs:

- vCPU
 - CPU RDY Time VM was ready to run, but was not provided CPU resource.
 - CPU WAIT Percentage of time spent in the blocked or busy wait state.
 - AMIN Reservation allocated.
 - ASHRS CPU shares allocated.
 - CPU CSTP Amount of time a Symmetric Multi-Processing (SMP) VM was ready to run, but was delayed due to co-vCPU scheduling contention.
- Disk I/O
 - GAVG Average guest operating system read latency per read operation.
 - DAVG/rd Average device read latency per read operation.
 - DAVG/wr Average device write latency per write operation.
 - RESETS/s Number of commands reset per second.
 - ABRTS/s Number of disk commands abandoned per second.
- Network
 - %DRPTX Percentage of packets dropped when transmitting.
 - %DRPRX Percentage of packets dropped when receiving.
- Memory
 - MCTLSZ Amount of physical memory reclaimed memory balloon statistics.

Software Appliance Licensing

Contact Center License Manager supports only the Virtualized Environment deployment of Avaya WebLM server.

When Contact Center License Manager starts, it extracts WebLM license keys from the remote WebLM server. Contact Center License Manager then converts the WebLM license keys into local PLIC license keys and distributes the keys to the Avaya Contact Center Select applications as required. Contact Center License Manager distributes PLIC license keys to Contact Center Manager Server, Contact Center Manager Administration, Communication Control Toolkit, Contact Center Multimedia, and Avaya Media Server as required.

When Contact Center License Manager requests licenses from a remote Avaya WebLM server, it reserves all the Contact Center licenses available on that server. Contact Center therefore supports only the PLDS standard license file (SLF) type. Avaya Contact Center Select does not support the

WebLM Enterprise model. Contact Center supports WebLM in nodal contact centers. WebLM does not support Contact Center corporate licensing.

Contact Center License Manager distributes nodal license keys to all configured Avaya Media Servers in the solution. Configure Avaya Media Server as a Media Server in Contact Center Manager Administration. Contact Center License Manager, when restarted, pushes license keys to that Avaya Media Server. Do not configure WebLM licensing on Avaya Media Server servers.

How to obtain a license

Avaya Contact Center Select uses a remote WebLM server to provide nodal licensing control.

- 1. Obtain the Avaya WebLM host ID from the WebLM user interface.
- 2. Use the WebLM host ID to obtain WebLM license keys from the Avaya Product Licensing and Delivery System (PLDS).
- Enter these license keys on the remote Avaya WebLM server. Contact Center License
 Manager connects to the remote WebLM server and uses the Contact Center-specific
 license keys from it to control Contact Center licensed features. Contact Center does not
 import the license file to a Contact Center server; WebLM stores the license file on the
 WebLM server.

You can use the License Manager Configuration Utility to check which Contact Center features are licensed and how many agent licenses are available.


Chapter 6: Avaya Contact Center Select hardware appliance

This section describes the Avaya Contact Center Select hardware appliance. The Avaya Contact Center Select hardware appliance is a physical rack mount server with the application software already loaded and partially preconfigured.

To deploy the Avaya Contact Center Select hardware appliance, you must activate the Windows operating system using the provided MS Windows product key, configure the server network setting, and then use a simple configuration wizard to rapidly commission the solution. At install time, the Avaya Contact Center Select hardware appliance server automatically launches a simple configuration wizard that you use to rapidly deploy a functional contact center solution. The Avaya Contact Center Select hardware appliance server is preloaded with sample users, skillsets, and contact center parameters. You can use this sample data to rapidly commission the solution and make the first routed call and email contact. The Avaya Contact Center Select hardware appliance server delivers quick and simplified contact center deployment. After the basic telephony and email features are working, you can then configure multimedia contacts, multiplicity, custom prompts, and other enhanced features and functions to improve your customer's experience.

You must activate the Microsoft Windows operating system on the Avaya Contact Center Select hardware appliance using the provided Microsoft Windows product key. The provided Microsoft Windows product key is displayed on a sticker attached to the top of the Avaya Contact Center Select hardware appliance server.

The following diagram shows the topology of a typical Avaya Contact Center Select hardware appliance solution:



- Hardware Appliance server specifications on page 87
- Avaya Contact Center Select hardware appliance software specifications on page 89
- Hardware Appliance Licensing on page 95

Hardware Appliance server specification

The Contact Center Hardware Appliance is a Dell R620 rack mount server preconfigured to support Contact Center.

Contact Center is a collection of real-time applications running on the Microsoft Windows Server 2008 R2 SP1 operating system. Contact Center provides real-time call control, multimedia handling, and real-time statistical reporting.

Important:

The Contact Center Hardware Appliance server supplied by Avaya is optimized to provide the real-time computational, networking, and logging resources required by Contact Center. You must not modify the Hardware Appliance server, unless instructed to do so by Avaya:

- Do not add additional internal hardware devices to this server.
- Do not change or upgrade the server BIOS version or settings.

- Do not change the server hardware settings.
- · Do not update the server firmware.
- Do not change or upgrade the device drivers.
- Do not modify the hard disk partitions.
- Do not change the *Windows Update* application settings on the server.
- Do not upgrade the Java Runtime Environment (JRE) supplied on the Hardware Appliance.

Due to the real-time processing that Contact Center applications perform, you must not install any other application class software on the server. You can install only the supported antivirus and remote support utility class software on this server.

Install only the Microsoft Windows Server 2008 R2 SP1 Operating System patches and hotfixes supported by Contact Center. For more information about the supported Operating System patches, see the *Contact Center Portfolio Service Packs Compatibility and Security Hotfixes Compatibility List* on www.avaya.com/support.

The following table lists the server specifications for the Contact Center Hardware Appliance Dell R620 server.

Specification	Quantity	Configuration	Comment
Form factor	1	Rack mount, 1U chassis	PowerEdge R620 rack mount server.
CPU	2	Intel Xeon E5-2670 2.60GHz, 20M Cache, 8.0GT/s QPI, Turbo, 8C, 115W, DDR3-1600MHz	_
RAM	8	4GB RDIMM, 1333 MHz, Low Volt, Dual Rank	_
Hard Disk	2	900 GB, SAS 6 Gbps, 2.5 inch, 10K RPM Hard Drive	The 900 GB hard disk is pre-configured with Operating System, application, and database partitions.
RAID Controller	1	PERC H710 Integrated RAID Controller, 512MB NV Cache	_
RAID Type	N/A	RAID-1	2x 900 GB hard disk drives
Optical Drive	1	16X DVD +/-RW Drive SATA with SATA Cable	_
Network Interface	4	1 Gbps NICs on motherboard	Only Ethernet supported.
Power supply	2	750 Watt AC auto-sensing, hot pluggable Power Supply	_
Power cables	2	Power cables	Localized to region.
Additional		2 front USB ports	_
interfaces		2 back USB ports	

Specification	Quantity	Configuration	Comment
		Front video connector	
Additional hardware	1	Rack mount kit	_
Weight		55 lbs approximately	
		25 kilograms approximately	
BTU/HR		2891 BTU/hr maximum per 750 W power supply.	

Avaya Contact Center Select hardware appliance software specifications

Avaya Contact Center Select is offered as a hardware appliance server. The Avaya Contact Center Select hardware appliance server contains the following software:

- Microsoft Windows 2008 Release 2 with Service Pack 1 64—bit operating system. The operating system is not activated until the end customer applies the Microsoft Windows license attached to the server.
- Contact Center Manager Server (CCMS)
- Contact Center Manager Administration (CCMA)
- Communication Control Toolkit (CCT)
- Contact Center License Manager (LM)
- Contact Center Manager Server Utility (SU)
- Orchestration Designer (OD)
- Contact Center Multimedia (CCMM)
- Avaya Media Server (Avaya MS) with Quick Fix Engineering (QFE) patches
- Default Avaya Contact Center Select configuration data
- Service Packs
- Firewall policy
- · Configuration wizard

The Windows 2008 operating system on the shipped hardware appliance server is not activated. The Contact Center hardware appliance provides a Microsoft Windows Server 2008 product license key. The Microsoft Windows Server 2008 product license key is printed on a label attached to the top of the Contact Center Hardware Appliance server. You must activate the Microsoft Windows operating system within 30 days of the initial power-up. Otherwise the Avaya Contact Center Select hardware appliance server stops working.

The following table shows the operating system on the Avaya Contact Center Select hardware appliance server.

Operating System	International Versions Supported	Minimum Service Pack Supported		
Windows Server 2008 Release 2, 64-bit, Service Pack 1.	English	Service Pack 1		

Server naming requirements

Server names must adhere to RFC1123 (Requirements for Internet Hosts), which specifies that a host name must adhere to the following:

- Use only characters a to z, A to Z, and 0 to 9 can be used in a host name.
- You can use a hyphen (-), but not to start or end the host name.
- Host names must be 6 to 15 characters in length.
- · Host names must not start with a number.
- Do not use the underscore character (_) and period character (_).
- Do not use spaces in the host name.

The Contact Center server must be able to resolve the host name or computer name of all other servers within the configuration. If you have a Domain Name Service (DNS) server, make sure an entry exists for each server. If you do not have a DNS server, manually update the HOSTS file on each server with the host name or computer name of all other servers to ensure that all clients can interpret the server names.

If network connectivity on your network requires the use of Fully Qualified Domain Names (FQDN), then the FQDN of each computer must be resolvable between all servers associated with Contact Center.

Microsoft security hotfixes

You must operate your server with the most current Microsoft patches.

- Review the Contact Center Portfolio Service Packs Compatibility and Security Hotfixes Applicability List (available from Technical Support Web site) for the list of applicable Microsoft security hotfixes to apply.
- Back up the entire server, and then shut down all Contact Center services before you apply any Microsoft security hotfixes using the Microsoft instructions.
- Apply Microsoft security updates on a timely basis.

Operating system updates

Operating system updates includes service updates and service packs.

Service updates

Given the number of operating system security service updates and the complexity inherent in any network, create a systematic and accountable process for identifying and applying service updates. To help create such a process, you can follow a series of best practices guidelines, as documented in the National Institute of Standards and Technology (NIST) Special Bulletin 800-40, Procedures for Handling Security Patches.

This bulletin suggests that if an organization has no central group to coordinate the storage, evaluation, and chronicling of security service updates into a library, then system administrators or the contact center administrator must fulfill this role. In addition to these guidelines, whenever possible, follow Microsoft recommendations regarding newly discovered vulnerabilities and that you promptly install Microsoft security service updates.

Whenever possible, Avaya incorporates the most recent operating system security recommendations and service updates in an integrated solutions testing strategy during each test cycle. However, due to the urgent nature of security service updates when vulnerabilities are discovered, follow Microsoft guidelines as they are issued, including any Microsoft installation procedures and security service update rollback processes.

Finally, you must perform a full system backup before you update the system to ensure that a rollback is possible, if required. If a Contact Center application does not function properly after you apply a Microsoft security service update, you must remove the service update and revert to the previous version of the application (from the backup you made before applying the service update). For added security, always determine whether Avaya verified the Microsoft service update for compatibility with Contact Center Manager.

For more information about updating, see the *Contact Center Portfolio Service Packs Compatibility* and *Security Hotfixes Compatibility List* on www.avaya.com/support.

Service packs

Avaya has a policy to implement co-residency testing of all new operating service packs for compatibility with the suite of Contact Center applications as soon as they are available. In practice, because a service pack can contain a significant amount of new content, Avaya requires that you wait until compatibility testing is complete before you apply the service pack. Note that operating system service packs are typically tested with the most recent Contact Center application SP and, therefore, an upgrade to a new service pack requires an upgrade to the most recent Avaya SP.

Before you upload a new service pack, you must perform a full system backup (for system rollback as in the updating scenario).

Important:

Service pack compatibility for all Contact Center applications is documented in the *Contact Center Portfolio Service Packs Compatibility and Security Hotfixes Applicability List* on the Web site at www.avaya.com/support.

Java Runtime Environment updates

Contact Center supports only specific versions of Java Runtime Environment (JRE). The Contact Center Installer installs a supported JRE version, and Contact Center service packs install required JRE updates. During installation, Contact Center disables JRE automatic updates on the contact center servers.

Important:

Updating to an unsupported version of JRE can cause the contact center to stop working and can require the reinstallation of the contact center server.

Dynamic Host Configuration Protocol support

Contact Center applications (CCMS, CCMA, CCT, CCMM, LM, and Avaya Media Server) do not support Dynamic Host Configuration Protocol (DHCP). All Contact Center servers must have a static IP address.

Agent Desktop client computers support both DHCP and static IP addresses.

Third-party software requirements

Due to the mission-critical, real-time processing that Contact Center applications perform, you must not install any other application class software on the server. You can install certain utility class software on the server, providing it conforms to the guidelines in this section.

Application class software generally requires a certain amount of system resources and must not be installed on a server running Contact Center applications. The installation of third-party applications can cause Contact Center applications to operate outside of the known engineering limits and can create potential unknown system problems (for example, CPU contentions, increased network traffic loading, disk access degradations).

Certain third-party utility class software applications, such as hardware diagnostics or backup tools, generally require less system resources during the normal operation of Contact Center applications and are permitted. Exceptions are utilities such as screen savers, which can cause system problems and degrade performance.

Antivirus software is classified as a utility and is subject to the generic guidelines in the following section.

Generic guidelines for utility-class software applications

The following are generic guidelines for utility-class software:

- During run-time, the utility must not degrade the contact center application beyond an average percentage of CPU use (see each specific application section in this document for the recommended maximum CPU usage level). Furthermore, the utility must not lower the minimum amount of free hard disk space required by contact center application and the Windows Operating system.
- The utility must not cause improper software shutdowns or out-of-sequence shutdowns.
- The utility must not administer the contact center application.

- If the utility has a database, it must not affect the contact center application database.
- Disk compression utilities must not be used.
- Memory tweaking utilities used to reclaim memory that is unused by Microsoft must not be used.
- The installation or uninstallation of the third-party software must not impact or conflict with the contact center application (for example, it must not cause DLL conflicts). If such conflicts are discovered, a server rebuild might be necessary.
- The implementation personnel must perform tests to ensure these conditions and recommendations are met before you place the Contact Center application into production. Support personnel can ask for the results of the testing during fault diagnosis. As part of fault diagnosis, the distributor or end user might be asked to remove third-party software.
- HyperTerminal must not be installed on the server as it interferes with the operation of Contact Center.

Guidelines for the use of antivirus software

This section describes the Avaya Contact Center Select antivirus software requirements.

Avaya Contact Center Select supports the following antivirus products:

- Symantec AntiVirus 11.0.5, 11.0.6, or 12
- McAfee 8.8
- Microsoft ForeFront 2010

You can deploy antivirus products from other vendors subject to the following guidelines:

- Infected file quarantine policy on the server and client: antivirus software can be configured to
 clean up the detected virus automatically and files must be quarantined if infected files cannot
 be cleaned. Contact Avaya to verify whether the quarantine file is part of our product files or
 dependent system file. If a virus is detected, remove the server from the network immediately
 during virus eradication to prevent further virus propagation.
- Do not connect a contact center application platform directly to the Internet to download virus
 definitions or updated files. Furthermore, Avaya recommends that you do not use a contact
 center application client PC to connect to the Internet. Instead, download virus definitions and
 updated files to another location on the customer network and manually load them from this
 interim location onto the contact center application platform.
- Perform the previous steps to download Contact Center application service packs (SP). This
 method limits access to the Internet, and thus reduces the risk of downloading infected files.
- Scan all SP files, DVD-ROMs, and floppy disks before you upload or install to the server. This practice minimizes any exposure to infected files from outside sources.
- Capacity considerations: running virus scan software can place an additional load on a contact center application platform. The implementation personnel must run the performance monitor tool on the server to gauge CPU usage. If the antivirus software scan causes the platform

average CPU usage to exceed the recommended percentage for longer than 20 minutes, the antivirus software must not be loaded onto the contact center application platform.

- Product Support do not provide support on the configuration of antivirus software, but offer guidance where possible. Direct questions or problems on antivirus software to the appropriate vendor.
- If performance or functionality issues are raised to Avaya support personnel as part of the fault diagnosis, you might be asked to remove third-party utility software or antivirus software.

Several maintenance tasks are automatically activated at 12:00 midnight. Therefore, you must schedule virus scans at a time other than midnight.

Avaya recommends that you exclude the following files and folders from scans (both real-time and scheduled):

- F:\Avaya\Contact Center\Database\
- <additional database drive>:\Avaya\Database\
- TSM OAM files located in the following folders:
 - D:\Avaya\Contact Center\Manager Server\iccm\bin\data
 - D:\Avaya\Contact Center\Manager server\iccm\data
 - D:\Avaya\Contact Center\Manager Server\iccm\sdm\log
- OAMContainer*.log located at D:\Avaya\Contact Center\Common Components\CMF
- D:\Avaya\Contact Center\Manager Server\bin\tools2.exeFile access errors occur in the Scan Activity log if you do not exclude this file from scanning.
- D:\Avaya\Contact Center\Manager Server\iccm\logs (SIP logs)
- D:\Avaya\Contact Center\Manager Server\iccm\sgm\config\(SIP log configuration files)
- D:\Avaya\Contact Center\Common Components\CMF
- The folder where you store Server Packs and patches

Contact Center Multimedia interacts with an external email system and enables agents to send attachment files from their computers to the Avaya Contact Center Select server. Both methods of retrieving data are potential sources of software infection.

Avaya recommends the following guidelines for antivirus software:

- Antivirus software must be installed on the email server to ensure that problems are caught at source.
- Agent computers require antivirus software to ensure that attachments sent to the Avaya Contact Center Select server do not have a virus. Contact Center Multimedia does not block specific attachment file types. Third-party antivirus software must be installed on the Portal Server according to guidelines in this document for such utilities.
- Ensure the antivirus software is configured to permit outbound email messages. For example, configure the McAfee antivirus software Access Protection option not to block Prevent mass mailing worms from sending mail.

- Exclude the Contact Center Multimedia partition from being scanned.
- If firewalls on individual computers are enabled on the Agent Desktop computer, the Report Listener might be flagged as trying to access the Internet. The properties must be configured to allow access for the Report Listener to Contact Center Multimedia through the firewall.
- You must not enable the Microsoft Updater to Auto-Run. Microsoft Updater is configured to alert level so you can schedule updates for off- peak hours.



Marning:

Running a Virus Scan on the Contact Center Multimedia attachment folder, which contains thousands of files, can use significant CPU time on a server and can cause drastic slowdown in agent's response times. Avaya recommends that you run scans, if necessary, during off-peak hours.

To avoid database integrity problems, Avaya recommends that you exclude all CACHE.DAT files, journal files, the cache.cpf file, and any Caché-related files from antivirus scans.

Caché software is installed in <Install drive>:\Avaya\Cache\CacheSys. Databases and journal files are installed in <Install drive>:\Avaya\Contact Center\Databases.

Hardware Appliance Licensing

The Avaya Contact Center Select Hardware Appliance deployment option uses a Nodal Enterprise license delivered as a WebLM XML file. This license file is used to control access to licensed features such as multimedia contacts and multiplicity.

Contact Center License Manager provides central control and administration of licensing for Avaya Contact Center Select. Each Contact Center License Manager includes a local instance of WebLM. When the Contact Center License Manager service starts, it extracts WebLM license keys from the local WebLM instance. Contact Center License Manager then converts the WebLM license keys into local PLIC license keys and distributes the keys the Avaya Contact Center Select applications as required.

- Obtain the network interface MAC address of the Avaya Contact Center Select server. The Hardware Appliance server has a pull-out information tag on the server's front panel. The Avaya Contact Center Select server networking MAC address is printed on the underside of this information tag.
- Use the MAC address to obtain a nodal WebLM license file from the Avaya Product Licensing and Delivery System (PLDS).
- You load the license file onto the Avaya Contact Center Select server as you run the configuration utility when you are deploying the Avaya Contact Center Select server. When Contact Center License Manager loads the license, if the unique number in the license does not match the Avaya Contact Center Select server MAC address, then License Manager shuts down and Avaya Contact Center Select cannot process contacts. If the unique number in the

license matches the Avaya Contact Center Select server MAC address, then License Manager provides license keys, and Avaya Contact Center Select processes customer contacts.

Chapter 7: Solution capacity limits and supported features

This section specifies the maximum capacity limits of Avaya Contact Center Select. This section also specifies the telephony features and devices supported by Avaya Contact Center Select.

- Avaya Contact Center Select maximum capacity limits on page 97
- Avaya Contact Center Select maximum configuration limits on page 100
- Avaya Contact Center Select supported features on page 101
- <u>Supported Telephony Features</u> on page 107
- Supported Telephony Devices on page 115
- Remote access support on page 117
- Communication Control Toolkit supported functionality on page 117

Avaya Contact Center Select maximum capacity limits

The maximum capacity for your solution is determined by your Avaya Contact Center Select deployment and the IP Office voice and call recording platform.

Avaya Contact Center Select (ACCS) supports the following deployment options:

- Avaya Contact Center Select DVD installed on an Entry-level single 4-core CPU PVI server.
- Avaya Contact Center Select DVD installed on a Mid-range dual 4-core CPU PVI server.
- Avaya Contact Center Select DVD installed on a High-end dual 6-core PVI server.
- Avaya Contact Center Select DVD installed on a High-end dual 8-core PVI server.
- Avaya Contact Center Select DVD installed on a High-end dual 10-core PVI server.
- Avaya Contact Center Select Software Appliance (3x OVAs) deployed on a VMware ESXi host server that meets the High-end dual 8-core PVI server specification.
- Avaya Contact Center Select Software Appliance (3x OVAs) deployed on a VMware ESXi host server that meets the High-end dual 10-core PVI server specification.
- Avaya Contact Center Select Hardware Appliance.

You can install the Avaya Contact Center Select DVD on any server that meets the Platform Vendor Independence (PVI) server specifications. The Avaya Contact Center Select DVD supports three

levels of PVI server specification; Entry-level, Mid-range, and a High-end PVI server specification. The maximum capacity figures for the Avaya Contact Center Select DVD depend on which PVI server specification is used. The High-end specification supports Avaya Contact Center Select to its maximum rated capacity.

The Avaya Contact Center Select software appliance is a set of VMware Open Virtual Appliance (OVA) virtualized servers; an Avaya Contact Center Select OVA, an Avaya Media Server OVA, and a WebLM OVA. You can deploy the Avaya Contact Center Select software appliance (3x OVAs) on a VMware ESXi host server that meets the High-end 8–core or 10-core server specifications. These high-end server specifications support the same maximum agent capacity and call rate figures.

The Avaya Contact Center Select hardware appliance is a physical rack mount server with the application software already loaded and partially preconfigured. The supplied rack mount server supports Avaya Contact Center Select to its maximum rated capacity.

The following table specifies the maximum capacity values supported by the Avaya Contact Center Select deployment types for each supported IP Office configuration.

Туре	Maximum Capacity	IP Office (IPO) configuration						
		IPO SE - R620	IPO SE - DL360	IPO SE - DL120	IPO 500V2 SIP trunks no CR	IPO 500V2 SIP trunks with CR	IPO 500V2 TDM trunks no CR	IPO 500V2 TDM trunks with CR
Entry- Level	Maximum logged-in agents	60	60	60	60	30	40	30
Server (ACCS	Maximum CCMA supervisors	10	10	10	10	10	10	10
DVD)	Maximum System Contact Rate See Note 1	1200	1200	1200	1200	600	800	600
	Maximum multimedia rate (WCph / Eph) ^{See} Note 2	150 / 300	150 / 300	150 / 300	150 / 300	150 / 300	150 / 300	150 / 300
Mid- Range	Maximum logged-in agents	150	150	125	60	30	40	30
Server (ACCS	Maximum CCMA supervisors	30	30	30	30	30	30	30
DVD)	Maximum System Contact Rate ^{See} Note 1	3000	3000	2500	1200	600	800	600
	Maximum multimedia rate	300 / 600	300 / 600	300 / 600	300 / 600	300 / 600	300 / 600	300 / 600

Туре	Maximum Capacity	IP Office	IP Office (IPO) configuration					
		IPO SE - R620	IPO SE - DL360	IPO SE - DL120	IPO 500V2 SIP trunks no CR	IPO 500V2 SIP trunks with CR	IPO 500V2 TDM trunks no CR	IPO 500V2 TDM trunks with CR
	(WCph / Eph) ^{See} Note 2							
High-End Server	Maximum logged-in agents	250	250	125	60	30	40	30
(ACCS DVD or	Maximum CCMA supervisors	50	50	50	50	30	40	30
3x OVA ESXi host)	Maximum System Contact Rate ^{See} Note 1	5000	5000	2500	1200	600	800	600
See Note 3	Maximum multimedia rate (WCph / Eph) ^{See} Note 2	600 / 1200	600 / 1200	600 / 1200	600 / 1200	600 / 1200	600 / 1200	600 / 1200
Hardware Appliance	Maximum logged-in agents	250	250	125	60	30	40	30
	Maximum CCMA supervisors	50	50	50	50	30	40	30
	Maximum System Contact Rate ^{See} Note 1	5000	5000	2500	1200	600	800	600
	Maximum multimedia rate (WCph / Eph) ^{See} Note 2	600 / 1200	600 / 1200	600 / 1200	600 / 1200	600 / 1200	600 / 1200	600 / 1200

- **Note 1:** The System Contact Rate is the total maximum combined contact rate across all supported contact types.
 - For System Contact Rate calculations, Web chat contacts have a weighting equivalent to 2 email messages. One Web chat is equivalent to two email messages.
 - For System Contact Rate calculations, the total maximum number of supported contacts per hour = (Voice + Email + (Web chat * 2))
- **Note 2:** Multimedia contact rates are applicable only if Contact Center Multimedia (CCMM) is part of the solution. Email contacts per hour (Eph). Web chats per hour (WCph). Web chat capacity is based on a maximum of 500 simultaneous chat sessions with an average chat duration of 5 minutes.
- **Note 3:** The Avaya Contact Center Select software appliance is supported only on the High-end 8–core or 10-core servers. Provision only vCPUs up to the number of physical cores on the VMware host.
- The rated capacities for the high end server types are the same whether virtualized or non-virtualized.

J 1 -	laximum apacity	IP Office (IPO) configuration						
		IPO SE - R620	IPO SE - DL360	IPO SE - DL120	IPO 500V2 SIP trunks no CR	IPO 500V2 SIP trunks with CR	IPO 500V2 TDM trunks no CR	IPO 500V2 TDM trunks with CR

IP Office Call Recording (CR) is supported with IP Office 500V2. Avaya Contact Center Select supports
Call Recording up to the maximum number of supported logged-in agents. Above this maximum limit, no
one can leave a voicemail or record any other calls.

		IP Office platform						
ACCS Deployment type	ACCS specification	IPO SE R620	IPO SE DL360	IPO SE DL120	IPO 500V2 SIP Trunks No CR	IPO 500V2 SIP Trunks With CR	IPO 500V2 TDM Trunks No CR	IPO 500V2 TDM Trunks With CR
Entry-level	Logged-in agents	60	60	60	60	30	40	30
Server	CCM A Supervisors	10	10	10	10	10	10	10
	System Contact Rate	1200	1200	1200	1200	600	800	600
(DVD)	MM Rate (WCph/Eph)	150 / 300	150 / 300	150 / 300	150 / 300	150 / 300	150 / 300	150/300
Mid-range	Logged-in agents	150	150	125	60	30	40	30
Server	CCM A Supervisors	30	30	30	30	30	30	30
	System Contact Rate	3000	3000	2500	1200	600	800	600
(DVD)	MM Rate (WCph/Eph)	300 / 600	300 / 600	300 / 600	300 / 600	300 / 600	300 / 600	300 / 600
High-end	Logged-in agents	250	250	125	60	30	40	30
Server	CCM A Supervisors	50	50	50	50	30	40	30
	System Contact Rate	5000	5000	2500	1200	600	800	600
(DVD or ESXi)	MM Rate (WCph/Eph)	600 / 1200	600 / 1200	600 / 1200	600 / 1200	600 / 1200	600 / 1200	600 / 1200
	Logged-in agents	250	250	125	60	30	40	30
Hardware	CCM A Supervisors	50	50	50	50	30	40	30
Appliance	System Contact Rate	5000	5000	2500	1200	600	800	600
	MM Rate (WCph/Eph)	600 / 1200	600 / 1200	600 / 1200	600 / 1200	600 / 1200	600 / 1200	600 / 1200

Figure 4: The maximum capacity values supported by the ACCS deployment types for each supported IP Office (IPO) configuration

Avaya Contact Center Select maximum configuration limits

The following table specifies the maximum overall configuration values supported by Avaya Contact Center Select.

Parameter	Maximum value	
Maximum configured agents	1000	
Maximum agents skillsets	500	

Parameter	Maximum value	
Maximum skillsets per agent	20	
Maximum agents per skillset	250	
Maximum supervisors per skillset	50	
Maximum supervisors per system	50	

Avaya Contact Center Select supported features

The following table specifies the main features supported by Avaya Contact Center Select:

Feature	Supported	Provider
Voice Skills Based Routing	Yes	Avaya Contact Center Select
FIFO Queuing	Yes	Avaya Contact Center Select
Longest Idle Agent queuing	Yes	Avaya Contact Center Select
ANI Number Available	Yes	Avaya Contact Center Select
ANI Number Routing	Yes	Avaya Contact Center Select
DNIS Number Available	Yes	
DDI Number Routing	Yes	Avaya Contact Center Select
Night Service	Yes	Avaya Contact Center Select
Threshold overflow for skills	Yes	Avaya Contact Center Select
Visual External Alarm for exceeded threshold	Yes	Avaya Contact Center Select
Voice Contact Classification	Yes	Avaya Contact Center Select and Agent Desktop
Multi-parameter Screen Pop per contact type per skillset	Yes	Avaya Contact Center Select
Music On Hold	Yes	IP Office
Multi Source Music on Hold	No	
On–Hold Announcements	No	
Skill Announcements	Yes	Avaya Contact Center Select
Agent Ext In/DN Key	Yes	Avaya Contact Center Select and IP Office with three line appearance
Coverage to Voicemail Pro	Yes	Direct calls to an agent station receive the configured coverage treatment. Calls routed from Avaya Contact Center Select to

Feature	Supported	Provider
		Agents do not receive coverage treatment.
Play Prompt and Collect Digits	Yes	Avaya Contact Center Select
Wallboards with API	Yes	Dev Connect and Avaya Contact Center Select
Activity /Work Codes	Yes	Avaya Contact Center Select
Aux/Not Ready Reason Codes	Yes	Avaya Contact Center Select
After Call Work Codes	Yes	Avaya Contact Center Select
Real Time Display Indication ACW/Act/AUX/NotRdy Codes	Yes	Avaya Contact Center Select
Three Line Operation (3 call appearance lines)	Yes	Avaya Contact Center Select and IP Office
Browser Based Agent Desktop	Yes	Avaya Contact Center Select and Agent Desktop
		Agent client uses .NET-based Agent Desktop thick client.
Browser Based Supervisor Desktop	Yes	Avaya Contact Center Select and Agent Desktop
		Supervisor Administration client use Internet Explorer based CCMA.
		Supervisor Agent client uses .NET-based Agent Desktop thick client.
Toll Free Queuing	Yes	Avaya Contact Center Select
Telephone Only Mode operation	No	
TLS transport type	Yes	Between IP Office Release 9.1 and Avaya Contact Center Select
Report Creation Wizard	No	
Media Server Zoning	No	
Contact Center Network Based Routing	No	
Mission Critical High Availability	No	Avaya Contact Center Select Business Continuity is supported.
Remote/Off-Site agent support	Yes	
IPv6 networking	No	
Database customization – import new Customer defined fields	No	

The following table specifies the multimedia features supported by Avaya Contact Center Select:

Feature	Sub feature	Supported	Provider
Multimedia Skills Based Routing		Yes	
Multimedia Management & Reporting		Yes	Avaya Contact Center Select
Multiplicity		Yes	Avaya Contact Center Select
Email Contact Handling		Yes	Avaya Contact Center Select
	Email Auto Response	Yes	Avaya Contact Center Select
	Email Auto Acknowledge	Yes	Avaya Contact Center Select
	Customer Contact History	Yes	Avaya Contact Center Select
	Email Real Time Reporting	Yes	Avaya Contact Center Select
	Screen Pop based on Email	Yes	Avaya Contact Center Select
	Fax Contact Types	Yes	Avaya Contact Center Select
	Scanned Documents	Yes	Avaya Contact Center Select
	SMS Contact Inbound	Yes	Avaya Contact Center Select
Web Communications		Yes	Avaya Contact Center Select
	Web Chat	Yes	Avaya Contact Center Select
	Web Call-back	Yes	Avaya Contact Center Select
	Co-browsing	No	
Outbound	Preview/Progressive	Yes	Avaya Contact Center Select
Self Service Integration			
	Self Service Data and CTI to external IVR	No	
	On board Avaya Media Server IVR - play prompt and collect digits		
Workforce Optimization			

Feature	Sub feature Supported		Provider
	Bulk Voice Recording	No	Avaya Contact Center Select
	Selective Recording	No	Using IP Office buton
	Agent Initiated	No	Using IP Office buton
	Quality Monitoring	No	
Workforce Management/ Forecasting		No	
External Threshold Alerter/Alarms		No	
Multi-Site Reporting		Yes	For distributed agents in an SCN network.
Supervisor /Agent Instant Messaging		No	
OPEN QUEUE Contact Types		No	
SOA Enabled IPO-CC		No	
IM (Routed) Contact Types		No	
Predictive Outbound		No	
Agent Desktop Softphone – H.323 or SIP		No	
Agent Greeting		No	

The following table specifies the reporting features supported by Avaya Contact Center Select:

Feature	Sub feature	Supported	Provider
Unified Multi Channel Real-time and Historical Reporting		Yes	Avaya Contact Center Select
Predefined Real-time and Historical Reports		Yes	Avaya Contact Center Select
Customer Customizable Reports		Yes	Avaya Contact Center Select
Customer Definable Reports		Yes	Using third-party tools interfacing using Avaya Contact Center Select ODBC
Report Creation Wizard (RCW)		No	
Historical Reports			

Feature	Sub feature	Supported	Provider
	Scheduled	Yes	Avaya Contact Center Select
	Interval	Yes	Avaya Contact Center Select
	Daily	Yes	Avaya Contact Center Select
	Weekly	Yes	Avaya Contact Center Select
	Monthly	Yes	Avaya Contact Center Select
	Quarterly	No	
	Skillset	Yes	Avaya Contact Center Select
	Trunk	No	
	Agents	Yes	Avaya Contact Center Select
	Abandoned Contacts	Yes	Avaya Contact Center Select
	Overflow Contacts	Yes	Avaya Contact Center Select
	Threshold Exceeded	Yes	Avaya Contact Center Select
	Contact Classification	Yes	Avaya Contact Center Select
	Source Of Disconnect	Yes	Avaya Contact Center Select
	Agent Station Key	No	
	Email Report Notifications	Yes	Avaya Contact Center Select
	System Status Reports	Yes	Avaya Contact Center Select

The following table specifies Avaya Contact Center Select product interoperability:

Product name	Supported
Avaya Aura® Workforce Optimization (WFO)	No. Use IP Office call recording.
Proactive Outreach Manager (POM)	No
Avaya Aura® Experience Portal	Yes, Release 7.0.1. Only when using IP Office Release 9.1.

Product name	Supported
Avaya IQ Reporting	No
Avaya Control Manager Agent and Supervisor Administration	No
Avaya Proactive Contact	No
Avaya one-X® Agent	No
Social Media Manager	No
Avaya Aura® Presence Services	No
Avaya Communicator for Windows	Yes, softphone support.
Microsoft Lync (Release 2010 and 2013)	Peer-to-peer IMs are supported. Routed IMs are not supported.

The following table specifies the Open Interfaces supported by Avaya Contact Center Select:

Open Interface name	Supported
Real-time Statistics Multicast (RSM)	Yes
Real-Time Display (RTD)	Yes
Database Integration Wizard (DIW) and Host Data Exchange (HDX)	Yes
Contact Center Multimedia (CCMM) Advanced Email Services	Yes
Contact Center Manager Administration (CCMA) Open Interfaces	Only for IP Office user data synchronization with Avaya Contact Center Select
Contact Center Multimedia Open Interfaces	Only for standard Web Chat communications. (Not supported for Agent Desktop or Outbound.)
Contact Center Multimedia Outbound Open Interfaces	No
Communication Control Toolkit (CCT) Open Interfaces	No
Open Queue	No
Open Networking	No
Meridian Link Services (MLS)	No
Communication Control Toolkit .NET SDK	Yes
Contact Center Manager Server (CCMS) Open Interfaces	No
Avaya Contact Recording APIs	No
Salesforce Server Side support	Yes

Supported Telephony Features

The following tables list the IP Office telephony features available to a non-agent IP Office user and specify which features are supported on an Avaya Contact Center Select agent station.

Basic Call Handling:

IP Office telephony feature name	IP Office user station support		Avaya Contact Center Select agent station support		Notes
	Personal calls	CC calls	Personal calls	CC calls	
Tones	Yes	Yes	No	No	Agent Desktop does not play specific tones dependent on geography.
Caller ID	Yes	Yes	Yes	Yes	
Call Screening	Yes	No	No	No	
Hold	Yes	Yes	Yes	Yes	
Toggle Calls	Yes	Yes	No	No	Toggle calls is not applicable to Avaya Contact Center Select agents with 3-line appearance.
Hold Call Waiting	Yes	Yes	No	No	Same as Auto-hold-allowed.
Hold Music (Music on Hold)	Yes	Yes	Yes	Yes	Provided by IP Office.
Park	Yes	No	No	No	
Automatic Callback	Yes	No	No	No	
Direct Inward Dialing (DID/ DDI)	Yes	Yes	Yes	Yes	
Transfer	Yes	Yes	Yes	Yes	
Distinctive and Personalized Ringing	Yes	No	No	No	
Personalized Ringing	Yes	Yes	No	No	
Message Waiting Indication	Yes	No	No	No	Supported on some physical stations. Not supported by Agent Desktop.
(MWI)					Contact Center (CC) calls are prevented from going to voicemail so cannot result in

IP Office telephony feature name	IP Office user station support		Avaya Contact Center Select agent station support		Notes
	Personal calls	CC calls	Personal calls	CC calls	
					MWI light on telephone. However, an agent handling a CC call sees the MWI light on their telephone if a personal call results in a new voicemail message while handling the CC call.
Visual Voice	Yes	No	No	No	Supported on some IP Office stations only and not by Agent Desktop.
					Contact Center (CC) calls are prevented from going to voicemail so cannot result in messages that can be processed using Visual Voice on telephone. However, an agent servicing a CC call can use Visual Voice on their telephone while servicing the CC call.

Advanced Call Handling:

IP Office telephony feat ure name	IP Office user station support		Avaya Contact Center Select agent station support		Notes
	Personal calls	CC calls	Personal calls	CC calls	
Absence Text	Yes	Yes	No	No	
Call Tagging	Yes	Yes	No	No	The Call Tagging feature is equivalent to the Avaya Contact Center Select Call Attached Data feature.
Reclaim Call	Yes	No	No	No	
Hunt Group Enable/Disable	Yes	Yes	No	No	Ability of a user to enable and disable their membership of hunt groups.
Call Waiting	Yes	N/A	Yes	N/A	If an Avaya Contact Center Select agent is active on a call,

IP Office telephony feat ure name	IP Office user s support	station	Avaya Contact Select agent sta support		Notes
	Personal calls	CC calls	Personal calls	CC calls	
					then another CC call is not routed to that agent.
					If an Avaya Contact Center Select agent is active on personal call, a CC call is not routed to the agent.
Do Not Disturb (DND)	No	No	No	No	Avaya Contact Center Select agents use NotReady (with reason code).
Dial Plan	N/A	N/A	N/A	N/A	Refers to the dial plan configuration on the IP Office. Configure a dial plan to route calls to extensions and agents.
Paging	Yes	Yes	No	No	Telephone must have a loudspeaker.
Intrude	Yes	Yes	No	No	Avaya Contact Center Select Supervisors can use Observe or Barge-in features.
Inclusion	Yes	Yes	No	No	
Private Call	Yes	Yes	No	No	
Hot Desking	Yes	Yes	N/A	N/A	This feature allows a number of users non-exclusive use of the same extension. Once logged in, any calls to that user are routed to the physical extension they are logged in at.
Remote Hot Desking	Yes	Yes	N/A	N/A	This feature is the same as 'Hot Desking' but refers specifically to a user configured on a particular node logging in to an extension configured on another node in the Small Community Network (SCN).
Relay On/Off/ Pulse	N/A	N/A	N/A	N/A	
Pickup	Yes	No	No	No	
Call Recording	Yes	Yes	No	No	

IP Office telephony feat ure name	IP Office user station support		Avaya Contact Center Select agent station support		Notes
	Personal calls	CC calls	Personal calls CC calls		
Telecommuter Mode	No	No	No	No	
Twinning and Mobility	No	No	No	No	

Key and Lamp Operation:

IP Office telephony feat ure name	IP Office user s support	Avaya Contact Center Select agent station support			Notes
	Personal calls	CC calls	Personal calls	CC calls	
Appearance Buttons	N/A	N/A	N/A	N/A	
Line Appearance	N/A	N/A	N/A	N/A	Three lines maximum. A Line Appearance is a representation of a trunk line on the IP Office system where the indicator tracks the activity on the Line. Only external calls can be answered or made on Line Appearances.
Call Appearance Buttons	Yes	Yes	No*	No*	Individual calls are represented individually on Agent Desktop, but there is no concept of selecting a particular call appearance button which corresponds to the telephone.
Alerting/Ring Tone for Covered Calls	Yes	No	No	No	IP Office blocks Avaya Contact Center Select calls from covering.
Bridged Appearance Buttons	No	No	No	No	
External Call Lamp Indication	Yes	No	No	No	
Call Coverage	Yes	No	Yes	No	IP Office blocks Avaya Contact Center Select calls from covering.

IP Office telephony feat ure name	IP Office user s support	tation	Select agent station support CC Personal calls CC calls		Notes
	Personal calls	CC calls			
Call Coverage Buttons	Yes	N/A	No	N/A	

Outbound Call Handling:

IP Office telephony feat ure name	IP Office user station support		Avaya Contact Center Select agent station support		Notes
	Personal calls	CC calls	Personal calls	CC calls	
Account Codes	Yes	Yes	No	No	
Authorization Codes	Yes	Yes	No	No	
Dial Emergency	Yes	N/A	No	No	The Dial Emergency feature is equivalent to the ACCS Emergency Call feature.
Call Barring	N/A	N/A	N/A	N/A	Avaya Contact Center Select independent

Alternate Route Selection (ARS):

IP Office telephony feat ure name	IP Office user station support		Avaya Contact Center Select agent station support		Notes
	Personal calls	CC calls	Personal calls	CC calls	
Maximum Call Length	Yes	Yes	Yes	Yes	Avaya Contact Center Select independent
Transferable Dial Out Privilege	Yes	N/A	No	N/A	Avaya Contact Center Select independent
Idle Line Preference	Yes	N/A	No	N/A	Avaya Contact Center Select independent
Alternate Route Selection	N/A	N/A	N/A	N/A	Configure IP Office to select appropriate trunk to route calls on.

Forwarding:

IP Office telephony feat ure name	telephony feat support		Avaya Contact Select agent st support		Notes
	Personal calls	CC calls	Personal calls	CC calls	
Coverage to Operator	Yes	No	No	No	
Forward on Busy	Yes	No	No	No	
Forward on No Answer	Yes	No	No	No	
Forward Unconditional	Yes	No	No	No	
Unconditional Forward to Voicemail	Yes	No	No	No	
Forward Hunt Group	Yes	No	No	No	
Follow Me	Yes	No	No	No	

Avaya telephone features:

IP Office telephony feat ure name	ony feat support		Avaya Contact Center Select agent station support		Notes
	Personal calls	CC calls	Personal calls	CC calls	
Programmable Buttons	Yes	Yes	No	No	
Busy Lamp Field (BLF) Indicators	Yes	Yes	No	No	Avaya Contact Center Select independent
Call History	Yes	Yes	No	No	
Language	Yes	Yes	No	No	Agent Desktop language is determined by the OS settings on the Agent Desktop client computer, not from the language configured for the IP Office extension.
Centralized Personal Directory	Yes	Yes	No	No	

IP Office telephony feat ure name	IP Office user station support		Avaya Contact Center Select agent station support		Notes
	Personal calls	CC calls	Personal calls	CC calls	
Centralized System Directory	Yes	Yes	No	No	
Self- Administration	No	No	No	No	Avaya Contact Center Select agents are not allowed to modify telephone properties.
On Hook Dialing	Yes	Yes	Yes	Yes	

Inbound Call Handling. Applies only in Failover Mode to IP Office Hunt Groups:

IP Office telephony feat ure name	IP Office user station support		Avaya Contact Select agent sta support		Notes
	Personal calls	CC calls	Personal calls	CC calls	
Incoming Call Routing	Yes	Yes	Yes	Yes	IP Office system configuration decides where incoming calls are routed. Once call routing is configured, calls to agents are displayed on the telephone and in Agent Desktop.
Hunt Groups	Yes	N/A	Yes	N/A	
Multi-site Networking/ Small Community Networking (SCN) Distributed Hunt	Yes	N/A	Yes	N/A	
Night Service	Yes	N/A	Yes	N/A	
Time Profiles	Yes	No	Yes	No	
Queuing	Yes	N/A	Yes	N/A	Configure system to limit the number of calls that can be waiting to be serviced in a hunt group. For example, when all parties in the group are busy.
Announcements	Yes	N/A	Yes	N/A	Configure system to play announcements to calls waiting to be services in a hunt group.

Contact Center features:

IP Office telephony feat ure name	IP Office user station support		Avaya Contact Center Select agent station support		Notes
	Personal calls	CC calls	Personal calls	CC calls	
Acquire Call (Call Steal)	Yes	No	No	No	Acquire Call can behave like 'Reclaim Call' or 'Call Pickup' depending on how it is invoked and the state of the two users involved.
Monitor Calls	Yes	No	No	No	A user can monitor other party's calls by listening in.
Queue Threshold Alert	N/A	N/A	N/A	N/A	Queue Threshold Alert applies only in Failover Mode to IP Office Hunt Groups.
Login	N/A	N/A	N/A	N/A	Login applies only in Failover Mode to IP Office Hunt Groups.

System Short Codes:

IP Office telephony feat ure name	IP Office user station support		Avaya Contact Center Select agent station support		Notes
	Personal calls	CC calls	Personal calls	CC calls	
User Short Codes	Yes	Yes	No	No	
System Short Codes	Yes	Yes	No	No	
Post-Dialing Short Codes	Yes	Yes	No	No	
Incoming Number Short Codes	Yes	Yes	No	No	

Miscellaneous Features:

IP Office telephony feat ure name	IP Office user station support		Avaya Contact Center Select agent station support		Notes
	Personal calls	CC calls	Personal calls	CC calls	
Conference Calls	Yes	Yes	Yes	Yes	

IP Office telephony feat ure name	IP Office user station support		Avaya Contact Center Select agent station support		Notes
	Personal calls	CC calls	Personal calls	CC calls	
Coaching/Silent Intrusion/ Whisper Page	Yes	Yes	No	No	
Dial On Pickup	No	No	No	No	This IP Office feature is also known as Hotline. The feature automatically dials a specified extension when the telephone is taken off hook. Do not configure this feature for Avaya Contact Center Select agents.
Off Hook Operation	N/A	N/A	N/A	N/A	Analog station feature not supported by Avaya Contact Center Select.
E911 Emergency Call	Yes	N/A	Yes	N/A	

Supported Telephony Devices

This section specifies the telephony connection types and devices supported in an Avaya Contact Center Select solution. The Avaya Contact Center Select solution supports all of the IP Office platform trunks types. There is no direct integration between the Avaya Contact Center Select and IP Office trunking interfaces. The Avaya Contact Center Select contact center functionality is independent of these IP Office trunks.

The following table list the stations and telephone types supported by Avaya Contact Center Select.

Agent Phone	Phone Model	Avaya Contact Center Select Supported	Notes
Analogue – All Models		No	
Digital	9500 Series	Yes	
	1400 Series	Yes	
	5400 Series	Yes	
	2400 Series		
IP: H.323	96x1	Yes	

Agent Phone	Phone Model	Avaya Contact Center Select Supported	Notes
	96x0	Yes	
	1600 Series	Yes	
	5600 Series	Yes	
	4610/4620x		
IP: SIP	IP Phone 1140E Model NTYS05 IP Phone 1230 Model NTYS20	Yes	Supported when running IP Office Release 9.1 SIP firmware.
DECT – All Models		No	
Wi-Fi Wireless – All Models		No	
Avaya Communicator for Windows		Yes	Softphone support with IP Office Release 9.1.
IP Office Softphone		Yes	Supported as co-resident softphone on agent workstation with Agent Desktop. Not supported as integrated softphone.

The following table shows the Avaya Contact Center Select agent experience for various phone types.

Phone Type	Skillset on Ag	ent Desktop	Skillset on the phone		PSTN Recording	
	Ringing	Connected	Ringing	Connected	Number	Indication
96x0 (9640)	Yes	Yes	Yes	Yes	Yes	Yes
96x1 (9641)	Yes	Yes	Yes	Yes	Yes	Yes
56xx (5610)	Yes	Yes	Yes	No	Yes	Yes
46xx (4610)	Yes	Yes	Yes	No	Yes	Yes
16xx (1616)	Yes	Yes	Yes	Yes	Yes	Yes
Softphone	Yes	Yes	Yes	Yes	Yes	No
95xx (9504)	Yes	Yes	Yes	Yes	Yes	No
54xx (5410)	Yes	Yes	Yes	No	Yes	Yes
24xx (2420)	Yes	Yes	Yes	No	Yes	Yes
14xx (1408)	Yes	Yes	Yes	Yes	Yes	Yes

Remote access support

Avaya Contact Center Select supports remote access using the following:

- Microsoft Windows Remote Desktop
- IP Office Support Services (IPOSS)

Both of these support remote troubleshooting and technical support.

Communication Control Toolkit supported functionality

This section compares the features supported by Avaya Contact Center Select using Avaya IP Office with the features supported by Avaya Aura[®] Contact Center using Avaya Aura[®] Communication Manager or Avaya Communication Server 1000 (CS 1000).

Communication Control Toolkit and Agent Desktop implement and use these features. Agent Desktop is a client of Communication Control Toolkit so they support the same features.

The following tables list the basic Communication Control Toolkit call control functions.

Table 1: Basic Communication Control Toolkit and Avaya Aura® Agent Desktop functions

Event	SIP-enabled Avaya Aura [®] Contact Center with Avaya Aura [®] or CS 1000	AML-based Avaya Aura [®] Contact Center using CS 1000	Avaya Contact Center Select using IP Office
Make Call	Yes	Yes	Yes
Hold Current Call	Yes	Yes	Yes
	The CS 1000 Swap Hold switch feature is not supported. For CS 1000, the Auto Hold Allowed (AHA) feature must be configured.	The CS 1000 Swap Hold switch feature is not supported.	
Unhold Call	Yes (Retrieve Call)	Yes (Retrieve Call)	Yes
Drop Current Call (Release)	Yes	Yes	Yes
Blind Transfer Call	No	Yes	No
Initiate Supervised Transfer	Yes	Yes	Yes
Complete Transfer	Yes	Yes	Yes
Initiate Conference Call	Yes (up to six parties on CS 1000)	Yes (up to six parties)	Yes

Event	SIP-enabled Avaya Aura [®] Contact Center with Avaya Aura [®] or CS 1000	AML-based Avaya Aura® Contact Center using CS 1000	Avaya Contact Center Select using IP Office
Complete Conference Call	Yes	Yes	Yes
Call Forward	No	Yes	No
Cancel Call Forward	No	Yes	No
Join Conference	Yes, Avaya Aura [®] only	No	Yes
Deflect Calls	No	No	No
Get Status	Yes	Yes	Yes
Get Call Capabilities	Yes	Yes	Yes
Get Data	Yes	Yes	Yes
Delete Data	Yes	Yes	Yes
Append Data	Yes	Yes	Yes
Make Set Busy (Do Not Disturb)	No	Yes (on Agent Terminals only)	No
Get/Set UUI	Yes	No (UUI attached as call data)	Yes
Send DTMF (for example, credit card number to IVR)	Yes	Yes DTMF is not supported in Knowledge Worker solutions.	Yes
Mute/Unmute	No	No	No
Consult	Yes	Yes (but must designate as transfer or conference)	Yes
Park/Unpark	No	No	No
Message Waiting Indicator	No	No	No
HER (Host Enhanced Routing)	No	Yes	No
Answer	Yes	Yes	Yes

The fast transfer functionality does not support completing a fast transfer call to an external trunk number. This functionality is for predictive dialing environments in which the application sends a MakeCall request to an external customer number and, when the customer answers, the application sends the FastTransfer request to blind transfer the customer to a live agent.

The following table lists the Contact Center specific functions supported by Agent Desktop and Communication Control Toolkit.

Table 2: Contact Center-specific functions

Event	SIP-enabled Avaya Aura [®] Contact Center with Avaya Aura [®] or CS 1000	AML-based Avaya Aura® Contact Center using CS 1000	Avaya Contact Center Select using IP Office
Agent Login	Yes	Yes	Yes
Agent Logout	Yes	Yes	Yes
Set Ready	Yes	Yes	Yes
Set Not Ready	Yes	Yes	Yes
ACD Set Activity Code	Yes	Yes	Yes
ACD Set Not Ready/Reason Code	Yes	Yes	Yes
ACD Set After Call Work Item Code	Yes	Yes	Yes
Work Ready Key support	No	No	No
Agent Whisper	No	No	No
Observe call	Yes	No	Yes
Set Call treatment	No	Yes	No
Barge In	Yes	No	Yes
Call Supervisor	Yes	Yes	Yes
Emergency Key	Yes	Yes	Yes
Redirect to another skillset	No, must transfer to a CDN (Route Point)	No	No, must transfer to a CDN (Route Point)
Return a call to the queue skillset that it came from	No	No	No
Redirect to another skillset	No	No	No
Return a call to the queue skillset that it came from	No	No	No

The following table lists the events delivered by Communication Control Toolkit.

Table 3: Communication Control Toolkit events

Event	SIP-enabled Avaya Aura [®] Contact Center with Avaya Aura [®] or CS 1000	AML-based Avaya Aura® Contact Center using CS 1000	Avaya Contact Center Select using IP Office
Ringing Event	Yes	Yes	Yes
Dialtone Event	No	No	No
Busy Event	No	No	No

Event	SIP-enabled Avaya Aura® Contact Center with Avaya Aura® or CS 1000	AML-based Avaya Aura® Contact Center using CS 1000	Avaya Contact Center Select using IP Office
Offering Event	Yes	Yes	Yes
Ringback Event	Yes	Yes	Yes
Inbound Connected Event	Yes	Yes	Yes
Outbound Connected Event	Yes	Partial	Yes
Connected Event	Yes	Yes	Yes
Disconnected Event	Yes	Yes	Yes
Held Event	Yes	Yes	Yes
Unheld Event	Yes	Yes	Yes
OnHold Pending Conference Event	Yes	Yes	Yes
Onhold Pending Transfer Event	Yes	Yes	Yes
Transferred Event	Yes	Yes	Yes
Conference Event	Yes	Yes	Yes
Initiated Transfer Event	Yes	Yes	Yes
Initiated Conference Event	Yes	Yes	Yes
Session Disconnect Event (includes shutdown)	Yes	Yes	Yes
Device Forward Event	No	No	No
Status Change Event	Yes	Yes	Yes
Notice Message Waiting Event	No	No	No
Notice No Message Waiting Event	No	No	No
Agent Logged out Event	Yes	Yes	Yes
Agent Logged in Event	Yes	Yes	Yes
Agent Ready Event	Yes	Yes	Yes
Agent Not Ready Event	Yes	Yes	Yes
Agent Busy Event	No	No	No
Agent Work Ready Event	No	No	No
Activity Code Entered	Yes	Yes	Yes
WalkAway Activated	No	No	No
WalkAway Return	No	No	No
Emergency Invoked	No	No	No
Call Supervisor Invoked	No	No	No

Chapter 8: Avaya Aura® Experience Portal Integration

Avaya Aura[®] Experience Portal is an open standards-based self-service software platform which offers industry leading reliability and scalability to help reduce costs and simplify operations.

Avaya Aura[®] Experience Portal Release 7.0.1 is deployed on standard Linux servers and it supports integration with SIP-enabled systems, including Avaya Contact Center Select and IP Office.

The Avaya Aura® Experience Portal system consists of an Experience Portal Manager (EPM), which controls the Experience Portal system and Media Processing Platform (MPP) servers, which process all calls. The Experience Portal system typically includes an Automatic Speech Recognition (ASR) server, Text-to-Speech (TTS) speech servers, and application servers.

Avaya Contact Center Select supports the following types of integration with Avaya Aura® Experience Portal Release 7.0.1:

- Front-end Avaya Aura® Experience Portal with SIP-enabled Contact Center
- Back-end Avaya Aura® Experience Portal with SIP-enabled Contact Center using SIP header information
- Back-end Avaya Aura[®] Experience Portal with SIP-enabled Contact Center using Context Creation

In a front-end Avaya Aura® Experience Portal integration, the customer call is processed first by Avaya Aura® Experience Portal and then by Avaya Contact Center Select. In a back-end Avaya Aura® Experience Portal integration, the customer call is processed first by Avaya Contact Center Select and then by Avaya Aura® Experience Portal. Avaya Contact Center Select supports front-end and back-end Avaya Aura® Experience Portal integration in a single solution.

The following mechanisms support transferring calls and call data between Avaya Aura® Experience Portal and Contact Center:

- SIP header information. SIP includes a number of message headers in each SIP message.
 These headers contain information that enables the receiver to understand and use the
 message properly. In a contact center solution, SIP headers can be used to transfer small
 amounts of call-related information between SIP-enabled applications. Avaya Contact Center
 Select supports the User-to-User Information (UUI) SIP header and the Avaya custom PIntrinsics SIP private header.
- SIP INFO message body using Context Creation: If your call-related context information does
 not fit in a SIP User-to-User Information (UUI) header or in the larger P-Intrinsics header, you
 can use the sample Context Creation application to pass more context information from Avaya
 Aura® Experience Portal to Avaya Contact Center Select. This sample Context Creation

application can return multiple values from Avaya Aura® Experience Portal, rather than the single value returned by the sample Play and Collect application. The Context Creation sample application can return call-related context information in a SIP INFO message body. A SIP INFO message body holds and transfers much more information than a SIP header.

In an IP Office platform based solution, Avaya Contact Center Select supports the following methods of integration with Avaya Aura[®] Experience Portal:

- SIP header information
- SIP INFO message using Context Creation

There are no additional licensing requirements for Avaya Contact Center Select and Avaya Aura® Experience Portal integration.

Data transfer methods

The following table shows the maximum amount of data supported by each transfer type:

Transfer method	Maximum data supported by Contact Center	
UUI SIP header using ASAI	96 bytes maximum.	
P-Intrinsics SIP header	Depends on your solution. Note 1	
SIP INFO message body using	8K bytes total maximum:	
Context Ceation	Maximum of 10 ASCII key-value pairs.	
	And 1K characters of Call Attached Data (CAD) within the CC application.	

Note 1 The following limitations apply to P-Intrinsics SIP header information:

• The amount of P-Intrinsics information associated with a call depends on the other SIP headers in the call and on the call flow path. Typically, Contact Center supports up to 10 ASCII key-value pairs of P-Intrinsics.

Contact Center supports ASCII key-value pairs with a key name of up to 25 characters and a value size of up to 80 characters.

Avaya Aura® Experience Portal Orchestration Designer

Avaya Aura® Experience Portal Orchestration Designer is an Eclipse-based application development environment which supports the development of Voice XML and CCXML speech applications. Orchestration Designer generates Avaya Aura® Experience Portal compliant XML-based applications which are deployed on software application servers such as Apache Tomcat Server in a self-service solution.

Voice XML

Voice XML (VXML) is a standard XML format for specifying interactive voice dialogs between a human and a computer. Voice XML is designed for creating audio dialogs that feature synthesized speech, digitized audio, recognition of spoken and DTMF key input, recording of spoken input, telephony, and mixed initiative conversations. A typical Voice XML play and collect application plays voice prompts to customers asking them to enter digits using their phone. The application then collects the customer digits and returns them for processing to the contact center.

Call Control XML

Call Control XML (CCXML) is a standard markup language for controlling how phone calls are placed, answered, transferred, conferenced, and more. CCXML works with Voice XML to provide an XML-based solution for any telephony application. Voice XML and CCXML are two separate languages and are not required in an implementation of either language. For example, CCXML can be integrated with a more traditional Interactive Voice Response (IVR) system and Voice XML dialog systems can be integrated with other call control systems.

SIP-enabled Avaya Contact Center Select

Avaya Contact Center Select uses Session Initiation Protocol (SIP) architecture to provide maximum interoperability and flexibility. SIP-enabled Avaya Contact Center Select simplifies solution architecture and CTI deployments. Avaya Contact Center Select SIP-enabled architecture and Contact Intrinsic data make it easy to develop screen pop applications, reducing the time, effort, and cost required to launch new capabilities.

Contact Center Manager Server (CCMS) contains a SIP Gateway Manager (SGM) component which is the call processor in a SIP-enabled Contact Center. The SIP Gateway Manager is a standalone SIP element that can receive and process calls from SIP-enabled communication systems such as IP Office.

Avaya Contact Center Select supports User-to-User Information (UUI) SIP header information and P-Intrinsic SIP header information. Contact Center uses the header information in each SIP call to generate call-related Contact Intrinsic information and Call Attached Data (CAD). This Contact Intrinsic data can contain information relevant to that call, the calling customer, and other information retrieved by self-service or third party applications. Contact Intrinsics are key-value pairs of relatively small amounts of data. Call Attached Data is a longer unstructured amount of data.

In a SIP-enabled contact center solution, the information stored in some SIP INFO messages can be used to transfer call-related information between SIP-enabled components. This call-related information enables the receiver to better understand and handle the call. If your call-related context information does not fit in a SIP User-to-User Information (UUI) header or in the larger P-Intrinsics header, you can use the sample Context Creation application to pass more context information from

Avaya Aura® Experience Portal to Avaya Contact Center Select. The Context Creation sample application can inject multiple pieces of context information (Intrinsics and Call Attached Data) into Avaya Contact Center Select, where as the Play and Collect sample application can retrieve only a single piece of data, for example collected digits. The call-related context information is returned in a SIP INFO message body. A SIP INFO message body holds and transfers much more information than a SIP header.

Contact Intrinsic data enriches the context and information presented to agents with each customer contact. Contact Intrinsic data makes it easy to develop screen pops, reducing the time, effort and cost required to launch new capabilities. Avaya recommends that you use Contact Intrinsic data.

P-Intrinsic SIP Header

Avaya Contact Center Select supports the custom P-Intrinsics private header. The Session Initiation Protocol (SIP) includes a number of message headers in each SIP message. These headers contain information that enables the receiver to understand and use the message properly. In a contact center solution, you can use SIP headers to transfer small amounts of call-related information between SIP-enabled applications. The application receiving this SIP message reads these headers and performs some action based on the contents of the headers. SIP header information can provide additional data about a call that applications can use to process that call.

You can use P-Intrinsics header information to pass context information between SIP-enabled applications. Avaya Contact Center Select parses the P-Intrinsics SIP header information and uses it to create Contact Intrinsics or Call Attached Data. You can use P-Intrinsics in conjunction with User-to-User (UUI) information if backwards compatibility with existing applications is required.

SIP private headers (P-Headers) are purely informational. They do not create new commands and they do not interfere with the regular transmission of SIP messages. SIP private headers are used only to pass extra information that the receiving application can use. Avaya Contact Center Select supports the P-Intrinsics SIP header in incoming SIP INVITE messages.

Components that support this private header include front-end IVRs systems such as Avaya Aura[®] Experience Portal and other SIP-enabled entities in the call flow.

P-Intrinsics information is not restricted by legacy limitations like UUI. P-Intrinsics information can grow in size, depending on other headers in the call, and on the call flow path. It can also be used to inject call attached data. It is therefore more flexible than UUI data. You can use both headers together, and customers can retain backwards compatibility with applications that already use UUI data.

Typical solution using P-Intrinsics

A front-end Avaya Aura® Experience Portal system uses XML speech applications and SIP header information to integrate with Avaya Contact Center Select. A self-service Voice XML speech application running on the Avaya Aura® Experience Portal – Application Server answers customer calls and gathers call-associated information based on customer's answers and inputs. Experience Portal then transfers the customer call, complete with this call-associated information stored in the P-Intrinsics SIP header, to Avaya Contact Center Select.

Contact Center uses the P-Intrinsics header to generate Contact Intrinsic and/or Call Attached Data specific to that call. If this call is ultimately answered by an agent, the agent can use the call-related Contact Intrinsic data to access customer details. The agents might receive the Contact Intrinsic data in a screen pop, or they might need to access these details manually using Agent Desktop.

P-Intrinsics reduce the amount of time the agents spend on each call, improve the customer experience, and make Contact Center more efficient.

User-to-User Information

SIP-enabled systems can use User-to-User Information (UUI) to transmit small amounts of data between systems within SIP header messages.

Voice XML applications can use SIP header information to collect, store, and transport customer call-related information. Voice XML application can use customer interview data to modify the SIP header, and then pass the customer call along with updated header data to the next application in the solution. Voice XML applications can also use SIP header information to make processing decisions about a customer call. Examples of SIP header UUI data include a customer account number obtained during a self-service customer interview.

Agent Desktop and Avaya Aura® Contact Center Orchestration Designer can also modify User-to-User Information.

This SIP header UUI data can be used to support Avaya Aura® Application Sequencing.

Universal Call Identifier

Universal Call Identifier (UCID) is an Avaya proprietary call identifier used to help correlate call records between different systems. Universal Call Identifier information, where enabled, is added to the User-to-User Information (UUI) data in SIP calls.

This identifier can be generated by Avaya Aura[®] Experience Portal MPP server. Universal Call Identifier can be passed to Avaya Aura[®] Experience Portal through an application's SIP headers.

Front-end Avaya Aura[®] Experience Portal and SIP-enabled Contact Center

A combined Avaya Aura[®] Experience Portal self-service system and Avaya Contact Center Select solution gives your customers exceptional service and improved efficiency. Front-end self-service automation reduces contact center operating costs and improves Customer Satisfaction (CSAT).

Avaya Aura[®] Experience Portal uses XML speech applications and SIP messaging-based information to integrate with Avaya Contact Center Select. A self-service Voice XML speech application running on the Avaya Aura[®] Experience Portal Tomcat application server answers

customer calls and modifies the call-associated User-to-User Information (UUI) based on customer answers and inputs. When customer calls are transferred to Contact Center agents, the agents use the call-related Contact Intrinsic data to access customers details. This reduces the amount of time the agents spend on each call, improves customer experience, making Contact Center more efficient.

Avaya recommends that you create your XML speech applications with Avaya Aura® Orchestration Designer. Avaya Aura® Experience Portal automatically includes all Orchestration Designer applications in the Application Summary report and Application Detail report. If you want these reports to display messages and status information from an application developed in a third-party tool, you must manually log the messages and status information from that application using the Application Logging Web service.

The following diagram shows a typical solution layout of a front-end Avaya Aura[®] Experience Portal self-service integration with Avaya Contact Center Select and IP Office.

Customer call Avaya Aura Application Avaya Contact Center Select Experience Server (Apache Tomcat) **Portal** Experience Portal Management System Media VoiceXML Contact Center **PSTN** Processing Application Manager Platform Server SIP Trunk SIP Trunk Avava IP Office

Front-end Avaya Aura Experience Portal and Avaya Contact Center Select solution

Figure 5: Example of front-end Avaya Aura® Experience Portal and SIP-enabled Contact Center

Agent phones

Call flow example for front-end Avaya Aura® Experience Portal and SIP-enabled Contact Center

This call flow example shows how the Avaya Aura® Experience Portal system interacts with Avaya Contact Center Select to handle a typical automated front-end self-service customer transaction.

- 1. Incoming customer calls are routed to a Media Processing Platform (MPP) server in the Avaya Aura® Experience Portal system.
- 2. The MPP server checks the Dialed Number Identification Service (DNIS) for the incoming call and uses the configuration information downloaded from the Experience Portal Manager (EPM), server to match the number to a speech application on Avaya Aura[®] Experience Portal.
- 3. The Experience Portal Management System starts an Avaya Voice Browser session and passes it the Universal Resource Indicator (URI) specified for the selected speech application.
- 4. The Avaya Voice Browser contacts the application server and passes it the URI.
- 5. The application server returns a Voice XML page to the Avaya Voice Browser.
- 6. Based on instructions on the Voice XML application, the MPP uses prerecorded audio files, Text-to-Speech (TTS), or both to play a prompt to start interaction with the caller.
- 7. If the customer responds by entering Dual-Tone Multi-Frequency (DTMF) digits, the MPP establishes a connection to a TTS server and the ASCII text in the speech application is forwarded for processing. The TTS server renders the text as audio output in the form of synthesized speech which the MPP then plays for the caller.
- 8. The customer chooses to speak to an agent.
- 9. The Voice XML application connects to the Contact Center Manager Server. The Voice XML application specifies a destination Controlled Directory Number (CDN) or Agent, transfer type (blind, bridged, or consult transfer), contact ID number, and UUI data generated Contact Intrinsics.
- 10. The Experience Portal Media Processing Platform (MPP) server completes the blind transfer of the customer call to the destination CDN.
- 11. The Contact Center Manager Server SIP Gateway Manager (SGM) is now controlling the customer call. The SGM routes the call to an appropriate agent skillset.
- 12. A Contact Center agent is offered the call. The agent can access customer details and Contact Intrinsics before answering the call.
- 13. The Contact Center agent receives the (customer and call) context information in a screen pop and answers the customer call.
- 14. The XML application terminates the call when it finishes execution or when the caller hangs up.

A combined Avaya Aura[®] Experience Portal self-service system and Avaya Contact Center Select solution gives customers exceptional service and improved efficiency. Front-end self-service automation reduces contact center operating costs and improves Customer Satisfaction (CSAT).

Avaya Aura® Experience Portal uses Voice XML applications and SIP header (UUI and P-Intrinsics) information to integrate with Avaya Contact Center Select. This gives enterprises complete flexibility and control of the integrated solution. The front-end Avaya Aura® Experience Portal self-service system and Avaya Contact Center Select solution is highly flexible and efficient. Avaya supplies sample Voice XML applications for the rapid integration of a front-end Avaya Aura® Experience Portal system with Avaya Contact Center Select.

Back-end Avaya Aura® Experience Portal and SIP-enabled Contact Center

Avaya Aura® Experience Portal provides back-end Interactive Voice Response (IVR) services like text-to-speech, digit collection, music, and speech recognition. A combined Avaya Aura® Experience Portal system andAvaya Contact Center Select solution gives your customers exceptional service and improved efficiency. Back-end Interactive Voice Response (IVR) reduces contact center operating costs and improves Customer Satisfaction (CSAT).

In a typical back-end Avaya Aura® Experience Portal solution, customer calls to Avaya Contact Center Select are routed to Experience Portal applications for automated processing. Avaya Aura® Experience Portal applications play voice prompts asking the customer to select items from a menu, or to input account numbers. The customer responds by entering digits on their phone, or by speaking (Experience Portal supports optional Automatic Speech Recognition servers). The Experience Portal applications then collect the customer's response and return it to Avaya Contact Center Select for further treatments, or routing to the next available and appropriate Agent.

The following diagram shows a typical solution layout of Avaya Contact Center Select with a backend Avaya Aura® Experience Portal integration.

Application Customer call Avaya Contact Avaya Aura Center Select Experience Server (Apache Tomcat) Portal Voice XML Experience Avaya Media Play and Collect Portal Management Application Server System SIG Contact Center Media CC XML Manager Processing Dialog Platform Application Server **GIVE IVR** Avaya IP Office Agent phones

Avaya Contact Center Select solution and back-end Avaya Aura Experience Portal

Figure 6: Example of back-end Avaya Aura® Experience Portal and SIP-enabled Contact Center

Call flow example using back-end Avaya Aura® Experience Portal and SIP-enabled Contact Center

This call flow example shows how the Avaya Aura[®] Experience Portal system interacts with Avaya Contact Center Select to handle a typical automated back-end Interactive Voice Response (IVR) customer transaction.

- 1. Incoming customer calls to the IP Office are routed to Avaya Contact Center Select.
- Avaya Contact Center Select answers the call and runs a flow application, script, and/or
 optional primary scripts. A primary script is an application ran or referenced by the Master
 Script. Contact Center Manager Server records Master script and Primary script actions in
 statistical records.

- 3. The Avaya Contact Center Select script issues a GIVE IVR for an external media server (XDIALOG), supplying the URI identifier of the Avaya Aura® Experience Portal.
- 4. Avaya Contact Center Select retains control of the call and sends a SIP INVITE message to Avaya Aura® Experience Portal. Avaya Contact Center Select specifies treatment parameters in the SIP INVITE message.
- 5. Avaya Aura® Experience Portal passes the call to a CCXML dialog application on the Apache Tomcat application server.
- 6. The CCXML dialog application accepts and retrieves IVR parameters from the SIP INVITE message.
- 7. The CCXML dialog application invokes the Play and Collect Voice XML application (PlayAndCollect) with the parameters retrieved from Avaya Contact Center Select. If available, SIP header UUI data is also extracted and passed to the Voice XML application.
- 8. The Play and Collect Voice XML application streams Real-time Transport Protocol (RTP) streams into the associated Avaya Media Server conference, and prompts the customer to enter digits on their phone.
- 9. The Play and Collect Voice XML application collects the digits entered by the customer.
- 10. The Play and Collect Voice XML application then passes the customer's digits back to the CCXML dialog application.
- 11. The CCXML dialog application returns the collected digits to Avaya Contact Center Select in a SIP INFO message.
- 12. The CCXML dialog application then drops out (BYE).
- 13. The Avaya Contact Center Select script retrieves the IVR collected digits.

A combined Avaya Contact Center Select and Avaya Aura[®] Experience Portal solution gives customers exceptional service and improved efficiency. Back-end Avaya Aura[®] Experience Portal automation reduces contact center operating costs and improves Customer Satisfaction (CSAT).

Avaya Contact Center Select uses Call Control XML and Voice XML applications to integrate with Avaya Aura® Experience Portal. This gives enterprises complete flexibility and control of the solution integration. The Avaya Aura® Experience Portal system and Avaya Contact Center Select solution is highly flexible and efficient. Avaya supplies sample Voice XML applications for the rapid integration of a back-end Avaya Aura® Experience Portal system with Avaya Contact Center Select.

Back-end Avaya Aura® Experience Portal using Context Creation and SIP-enabled Contact Center

Avaya Aura® Experience Portal provides back-end Interactive Voice Response (IVR) services like text-to-speech, digit collection, music, and speech recognition. A combined Avaya Aura® Experience Portal system and Avaya Contact Center Select solution gives your customers exceptional service and improved efficiency.

Avaya Contact Center Select provides generic sample applications to demonstrate how it integrates with Avaya Aura® Experience Portal. You can select a sample application that suits your integration, review the sample code, and customize it to your solution before deploying it in production.

In a SIP-enabled contact center solution, the information stored in some SIP INFO messages can be used to transfer call-related information between SIP-enabled components. This call-related information enables the receiver to better understand and handle the call. If your call-related context information does not fit in a SIP User-to-User Information (UUI) header or in the larger P-Intrinsics header, you can use the sample Context Creation application to pass more context information from Avaya Aura® Experience Portal to Avaya Contact Center Select.

The Context Creation sample application can inject multiple pieces of context information (Intrinsics and Call Attached Data) into Avaya Contact Center Select, whereas the Play and Collect sample application can retrieve only a single piece of data, for example collected digits.

In a typical back-end Avaya Aura® Experience Portal solution, customer calls to Avaya Contact Center Select are routed to Avaya Aura® Experience Portal applications for automated processing. Avaya Aura® Experience Portal applications play voice prompts asking the customer to select items from a menu, or to input account numbers. The customer responds by entering digits on their phone, or by speaking (Avaya Aura® Experience Portal supports optional Automatic Speech Recognition servers). The Avaya Aura® Experience Portal applications then collect the customer's response and return it to Avaya Contact Center Select for further treatments, or routing to the next available and appropriate Agent.

In a back-end integration where Avaya Aura® Experience Portal is using the Context Creation sample application, the Avaya Contact Center Select Orchestration Designer script sends a GIVR IVR (SIP INVITE) message into the Avaya Aura® Experience Portal system. The SIP INVITE message has "treatmenttype" set to "contextcreation". Avaya Aura® Experience Portal passes the SIP call to a sample Dialog CC XML application. The Dialog CC XML and Context Creation VoiceXML applications process the call, and return hex-encoded call-related information. Because the "treatmenttype" was set to "contextcreation", the Dialog application returns a SIP INFO message of type "application/x-aacc-info" to the Contact Center. The Contact Center SIP Gateway Manager (SGM) recognizes this SIP message type and converts the context information in the call into Contact Intrinsics. The Orchestration Designer script can then access and use the Contact Intrinsics for the call, and Contact Center can pass them on to Agent Desktop.

This sample Dialog and Context Creation applications can return multiple values from Avaya Aura® Experience Portal, rather than the single value returned by the Avaya Contact Center Select sample Play and Collect VoiceXML application. The Context Creation sample application supports more complex data. The call-related context information is returned in a SIP INFO message body. A SIP INFO message body holds and transfers much more information than a SIP header.

When using the Context Creation sample application, the SIP message body data is hex-encoded and XML-formatted (using the same encoding as P-Intrinsics).

Example of a single intrinsic in VoiceXML code (Note: spaces are not supported):

<cc><i>CUSTOMER_SESSION_ID=12345</i></c>

Example of the single intrinsic when Hex-encoded:

3c63633e3c693e435553544f4d45525f53455353494f4e5f49443d31323334353c2f693e3c2f63633e

The following diagram shows a typical solution layout of an Avaya Contact Center Select with a back-end Avaya Aura® Experience Portal integration.




Figure 7: Example of back-end Avaya Aura® Experience Portal using the Context Creation sample application

Call flow example using back-end Avaya Aura® Experience Portal with the Context Creation sample application

This call flow example shows how the Avaya Aura[®] Experience Portal system interacts with Avaya Contact Center Select to handle a typical automated back-end Interactive Voice Response (IVR) customer transaction.

- 1. Incoming customer calls to IP Office are routed to Avaya Contact Center Select.
- 2. Avaya Contact Center Select answers the call and runs a script, and/or optional primary scripts. A primary script is an application ran or referenced by the Master Script. Contact

Center Manager Server records Master script and Primary script actions in statistical records.

- 3. The Avaya Contact Center Select script issues a GIVE IVR for an external media server (XDIALOG), supplying the URI identifier of the Avaya Aura® Experience Portal.
- 4. Avaya Contact Center Select retains control of the call and sends a SIP INVITE message to Avaya Aura® Experience Portal. Avaya Contact Center Select specifies treatment parameters in the SIP INVITE message. The SIP INVITE message has "treatmenttype" set to "contextcreation".
- 5. Avaya Aura® Experience Portal passes the call to the sample CCXML dialog application on the Apache Tomcat application server.
- 6. The CCXML dialog application accepts and retrieves IVR parameters from the SIP INVITE message.
- 7. The CCXML dialog application invokes the Context Creation Voice XML application with the parameters retrieved from Avaya Contact Center Select.
- 8. The Context Creation Voice XML application streams Real-time Transport Protocol (RTP) streams into the associated Avaya Media Server conference, and prompts the customer to enter digits on their phone.
- 9. The Context Creation Voice XML application collects the digits entered by the customer.
 - If the digits match the first account number (AccountA=123123) in the application's config.properties file, the Context Creation application uses the "Context Data for account A" data from the configuration file and hex encodes it.
 - If the entered digits match the second account (AccountB=456456) in the application's config.properties file, the Context Creation application uses the "Context Data for account B" data from the configuration file and hex encodes it.

The sample Context Creation application uses the account number details from the configuration files for illustration purposes. In a real solution, you can extract the context data from anywhere; be it an external database, a Customer Relationship Management (CRM) system, or from context gathered within the Orchestration Designer application.

- 10. The Context Creation Voice XML application then passes the encoded hex data back to the CCXML dialog application.
- 11. The CCXML dialog application returns the encoded hex data to Avaya Contact Center Select in a SIP INFO message. Because "treatmenttype" was set to "contextcreation", the dialog application sets the type of the SIP message body to 'application/x-aacc-info'.
- 12. The CCXML dialog application then drops out (BYE).
- 13. The Avaya Contact Center Select SIP Gateway Manager (SGM) recognizes this SIP message type and creates context information for the call by converting the hex encoded data in the SIP INFO message body into Contact Intrinsics.
- 14. The Avaya Contact Center Select script logs the returned value.

Avaya Contact Center Select uses Call Control XML and Voice XML applications to integrate with Avaya Aura® Experience Portal. This gives enterprises complete flexibility and control of the solution

integration. The Avaya Aura[®] Experience Portal system and Avaya Contact Center Select solution is highly flexible and efficient. Avaya supplies sample Voice XML applications for the rapid integration of a back-end Avaya Aura[®] Experience Portal system with Avaya Contact Center Select.

Avaya DevConnect

The Avaya DevConnect Program provides a wide range of developer resources, including access to APIs and SDKs for Avaya products, developer tools, technical support options, and training materials. Registered membership is free to anyone interested in designing Avaya-compatible solutions. Enhanced Membership options offer increased levels of technical support, compliance testing, and co-marketing of innovative solutions compatible with standards-based Avaya solutions.

Avaya Contact Center Select supplies generic sample Avaya Aura[®] Experience Portal applications for demonstration purposes. If you plan to use these sample applications, you must review the sample code and customize it to your solution prior to deploying in production.

For more information, and to download the complete Avaya Aura® Experience Portal front-end self-service and Avaya Contact Center Select using SIP header sample files, see Orchestration Designer Sample Applications on www.avaya.com/devconnect.

Chapter 9: Administration client computer requirements

This section provides the configuration requirements for the browser-based Avaya Contact Center Select administration client computers. Install this client computer to configure and administer Avaya Contact Center Select resources, to monitor performance, and to generate (real-time and historical) reports. You can also use this client computer to upload and download data using the Configuration Tool spreadsheets.

Administrator computer hardware requirements

The following table lists the minimum hardware requirements for the Administrator client computer.

Table 4: Client computer minimum hardware requirements

Hardware item	Minimum requirements	Additional information
CPU	1 Gigahertz (GHz) or faster CPU with support for PAE, NX, and SSE2	Physical Address Extension (PAE), NX processor bit (NX), and Streaming SIMD Extensions 2 (SSE2) are features of the processor. These CPU features are required to run Microsoft Windows 7.0 and Microsoft Windows 8.1.
		Dual- and quad-CPU systems are supported with or without Hyper-Threading enabled.
		AMD processors of the same or higher specification are also supported.
RAM	1 Gigabyte (GB) (32-bit) or 2 GB (64-bit)	Additional memory is required, if you run other memory intensive applications.
Hard disk space	16 GB (32-bit) or 20 GB (64-bit)	
Hard disk partitioning	No specific partitioning requirements	_
Hard disk speed	2.5 inch disk minimum speed: 10000 RPM	_

Hardware item	Minimum requirements	Additional information
	3.5 inch disk minimum speed: 7200 RPM	
Floppy drive	Not required	If a floppy drive is installed, it must be A.
DVD ROM	Not required	
Network interface	One network interface card	100 Mb/s Ethernet or higher is recommended.
Video card	Microsoft DirectX 9 graphics device with WDDM driver	1024 x 768 pixels minimum resolution
Keyboard	One keyboard	_
Mouse	One mouse	_

Client operating system requirements

The following table lists the operating system requirements for client computers.

Table 5: Client operating system requirements

Operating system	International versions supported	Minimum service pack
Windows 7 (32-bit and 64-bit)	English	
	French (FR)	
	German (DE)	
	Italian (IT)	
	Japanese (JA)	
	Korean (KO)	
	Latin Spanish (ES)	
	Brazilian Portuguese (PT-BR)	
	Russian (RU)	
	Simplified Chinese (Zh-CN)	
Windows 8.1	English	
	French (FR)	
	German (DE)	
	Italian (IT)	
	Japanese (JA)	
	Korean (KO)	

Operating system	International versions supported	Minimum service pack
	Latin Spanish (ES)	
	Brazilian Portuguese (PT-BR)	
	Russian (RU)	
	Simplified Chinese (Zh-CN)	
Windows Server 2008 Release 2	English	
Standard Edition and Enterprise Editions 64-bit	French (FR)	
	German (DE)	
	Italian (IT)	
	Japanese (JA)	
	Korean (KO)	
	Latin Spanish (ES)	
	Brazilian Portuguese (PT-BR)	
	Russian (RU)	
	Simplified Chinese (Zh-CN)	

Administration Client Citrix support

Contact Center Manager Administration (CCMA) is supported in Citrix deployments. A Citrix server solution uses software to deliver on-demand Windows applications to physical desktops. This allows client users to access and use programs which are available on the Windows Server 2008 operating system of the Citrix server. Contact Center Manager Administration is supported only with Citrix XenApp 6.5.

Users access Contact Center Manager Administration through a Citrix client on their client computer, connecting through an Internet Explorer browser that runs on the Citrix server. The browser is available to users through a Citrix client on their client computer. In a client Citrix deployment of CCMA, you must install ActiveX controls on the Citrix server. For more information about installing ActiveX controls on the Citrix server, see *Avaya Contact Center Select Advanced Administration*.

For more information about Citrix application publishing, see your Citrix documentation. For more information on how to configure your Citrix server to allow users to access CCMA, see *Avaya Contact Center Select Advanced Administration*.

Avaya Contact Center Select supports only the Multicast option for Real-Time Displays (RTDs) in a Citrix environment. Avaya Contact Center Select does not support the Unicast option for Real-Time Displays (RTDs) in a Citrix environment.

Important:

No Avaya Contact Center Select client components, other than Agent Desktop and Contact Center Manager Administration, are supported in a Citrix deployment. This includes Orchestration Designer (OD), Outbound Campaign Management Tool (OCMT), and the CCMM Administration utility.

Third-party software requirements

This section describes the third-party software requirements for the administration client computer.

The following components are required on the administration client PC:

• Microsoft Internet Explorer 8.0 (32-bit version only), 9.0 (32-bit version only), 10.0 (32-bit version only), and 11.0 (32-bit version only).

Note:

You must run Internet Explorer in compatibility mode for Contact Center Manager Administration and Communication Control Toolkit.

Microsoft Excel 2007 or later (for Configuration Tool only)

Contact Center Manager Administration supports only the 32-bit version of Microsoft Internet Explorer.

Chapter 10: Agent Desktop computer requirements

This section provides the configuration requirements for the Agent Desktop client computers. Agent Desktop is a single-interface client application used by contact center agents to interact with customers. Agents download and install Agent Desktop client software from the Avaya Contact Center Select server. Avaya Contact Center Select agents use the Agent Desktop software in conjunction with an IP Office provisioned telephone.



Agent Desktop does not support touch screen devices or tablets.

Note:

Agent Desktop does not support Network Address Translation (NAT).

Agent Desktop localized languages

Agent Desktop is supported in the following localized languages:

- English
- French
- German
- Italian
- Japanese
- Korean
- Latin Spanish
- Brazilian Portuguese
- Russian
- Simplified Chinese

A single Avaya Contact Center Select solution, with the localization language patches installed, supports all of the Agent Desktop localized languages. For example, a single English language Voice and Multimedia Contact Server supports the English, Chinese, French, and Russian language versions of Agent Desktop client software.

Avaya Contact Center Select supports Agent Desktop client operating systems that use a different language family to the Contact Center server.

Agent Desktop computer hardware requirements

The following table lists the minimum hardware requirements for a computer running Agent Desktop software.

Table 6: Agent Desktop computer minimum hardware requirements

Hardware item	Minimum requirements	Additional information
CPU	1 Gigahertz (GHz) or faster CPU with support for PAE, NX, and SSE2	Physical Address Extension (PAE), NX processor bit (NX), and Streaming SIMD Extensions 2 (SSE2) are features of the processor. These CPU features are required to run Microsoft Windows 7.0 and Microsoft Windows 8.1.
		Dual- and quad-CPU systems are supported with or without Hyper-Threading enabled.
RAM	1 Gigabyte (GB) (32-bit) or 2 GB (64-bit)	Additional memory is required, if you run other memory intensive applications at the same time as Agent Desktop.
Hard disk space	16 GB (32-bit) or 20 GB (64-bit)	
Hard disk partitioning	No specific partitioning requirements	_
Hard disk speed	2.5 inch disk minimum speed: 10000 RPM	_
	3.5 inch disk minimum speed: 7200 RPM	
Floppy drive	Not required	If a floppy drive is installed, it must be A.
DVD ROM	Not required	
Network interface	One network interface card	100 Mb/s Ethernet or higher is recommended.
Video card	Microsoft DirectX 9 graphics device with WDDM driver	1024 x 768 pixels minimum resolution
Keyboard	One keyboard	_
Mouse	One mouse	_

Agent Desktop does not support touch screen devices or tablets.

Client operating system requirements

The following table lists the operating system requirements for client computers.

Table 7: Client operating system requirements

Operating system	International versions supported	Minimum service pack
Windows 7 (32-bit and 64-bit)	English	
	French (FR)	
	German (DE)	
	Italian (IT)	
	Japanese (JA)	
	Korean (KO)	
	Latin Spanish (ES)	
	Brazilian Portuguese (PT-BR)	
	Russian (RU)	
	Simplified Chinese (Zh-CN)	
Windows 8.1	English	
	French (FR)	
	German (DE)	
	Italian (IT)	
	Japanese (JA)	
	Korean (KO)	
	Latin Spanish (ES)	
	Brazilian Portuguese (PT-BR)	
	Russian (RU)	
	Simplified Chinese (Zh-CN)	
Windows Server 2008 Release 2	English	
Standard Edition and Enterprise Editions 64-bit	French (FR)	
	German (DE)	
	Italian (IT)	
	Japanese (JA)	
	Korean (KO)	
	Latin Spanish (ES)	
	Brazilian Portuguese (PT-BR)	

Operating system	International versions supported	Minimum service pack
	Russian (RU)	
	Simplified Chinese (Zh-CN)	

Agent Desktop client network infrastructure requirements

Agent Desktop is a client application which communicates with the Avaya Contact Center Select server. For optimal Agent Desktop operation, the underlying contact center network infrastructure must provide adequate latency and bandwidth between the agent computer and the Avaya Contact Center Select server.

This section provides a high-level overview of the data that is passed between Agent Desktop and the Avaya Contact Center Select server. It also sets out the recommended network values and likely impacts on agents if these values are not met. This section also describes the performance of Agent Desktop in varying Round Trip Time (RTT) and bandwidth environments.

Important:

Agent Desktop performance degrades as network Round Trip Time increases and network bandwidth decreases.

Network Latency

Network latency is a measure of the time delay experienced in a system, measured in Round Trip Time (RTT). RTT is the average Round Trip (packet) Time as measured using the ping command for a 1024-byte (1KB) data size.

For optimal performance, Avaya recommends a RTT of less than 80ms from the Agent Desktop client computer to the following Avaya Contact Center Select components:

- Communication Control Toolkit (CCT)
- Contact Center Multimedia (CCMM)
- Contact Center Manager Server (CCMS)

The RTT from the Agent Desktop client PC to the Avaya Contact Center Select server must be less than 120ms. For network environments with an RTT greater than 120ms, refer to the Citrix deployments of Agent Desktop in the next section.

RTT impacts on Voice traffic

This section describes how the underlying RTT and latency of the network affects the experience of handling voice traffic in Agent Desktop.

Agent Desktop used with a physical desk phone

The CCT component sends Computer Telephony Integration (CTI) signals to Agent Desktop, for example to prompt Agent Desktop to alert an incoming contact. These CTI signals are passed

across the network as data. However, if the agent is using a physical desk phone, voice packets are transported across a network.

The following table details the time taken for the contact to alert on the Agent Desktop, compared to the time taken for the same contact to ring on the agent's phone, where the phone is subject to a constant RTT of 1ms.

RTT (ms)	Delay between desk phone ring and call alert on Agent Desktop	Delay between clicking Accept button on Agent Desktop and active voice path
1ms LAN	<0.5 Seconds	<0.5 Seconds
50ms	0.5 Seconds	1.0 Seconds
120ms	1.0 Seconds	2.5 Seconds

RTT impact on Multimedia Contacts

Contact Center Multimedia contacts are also affected by network latency. Agent Desktop downloads Customer contacts from the Avaya Contact Center Select server and displays their contents as soon as they are fully retrieved.

The table below shows how varying RTTs affect multimedia contact display times – in this case, email contacts – on Agent Desktop. The "Customer Details/Customer History Display" column indicates how much time passes between the email being opened on the Agent Desktop and the additional context information being loaded and displayed. These sample times are for ideal laboratory conditions.

RTT (ms)	Email Display	Customer Details/Customer History Display
1ms LAN	2 Seconds	0 Seconds
50ms	3 Seconds	Additional 3 Seconds
100ms	4 Seconds	Additional 4 Seconds
120ms	4 Seconds	Additional 5 Seconds

This data was generated using a 20KB email message, a customer history containing 30 contacts of 20KB each, in a network where bandwidth is not limiting the data transfer. Email messages of different sizes generate different results.

Bandwidth

The network bandwidth available to Agent Desktop client computers for communication with Avaya Contact Center Select servers is critical to Agent Desktop performance. If voice traffic is carried on the same network, this traffic is often prioritized above other network traffic – this bandwidth is therefore not available to Agent Desktop. In many cases agents use other third party applications over the same network. The bandwidth requirements of these third party applications must be considered as part of the overall bandwidth calculations (in addition to bandwidth allocated for voice soft phones and for Agent Desktop).

Several factors affect the recommended bandwidth for Agent Desktop. Depending on which Contact Center Multimedia (CCMM) features are in use on a given Customer deployment, not all factors apply. Indicative calculations to estimate the actual bandwidth usage are presented below for the various contact types and features. To calculate the required bandwidth, the relevant figures for the deployed features and supported contact types can be combined to derive an overall figure.

The network usage can be one of two types:

Constant traffic	These require dedicated, permanently available network use for the lifetime of the consumption. Examples of this type of traffic include; statistics display in Agent Desktop, update of live Web chat contacts.
	Many factors influence constant traffic levels, for example the number of agents with a large number of assigned skillsets, the number of active supervisors running RTDs in unicast mode, and large numbers of skillsets in use (large data packet) even for multicast.
Bursty traffic	The display of multimedia contacts and multimedia contact history is bursty traffic. A significant amount of data is downloaded to the Agent Desktop over a number of seconds. The frequency of these download is driven by agent activity.
	These require high usage of the available network for short times to download bursts of data. The time window that this data takes to download depends on the available network bandwidth at that time. Since this is not constant network consumption, a Kilo bits per second value is not reflective of the bandwidth required and a Kilo bit value has been provided instead.

Bandwidth impacts on Voice

If the agents are using a physical desk phone for voice or any other application which utilizes network bandwidth, this needs to be factored into the engineering of the network to meet the expected performance levels on Agent Desktop.

Retrieve Customer History on voice contacts

The Agent Desktop Customer History feature enables agents to retrieve voice callers' multimedia Customer history, from the Avaya Contact Center Select server, when a voice contact is accepted. Agent Desktop Customer History is an optional feature which is enabled in the CCMM Administration tool. These historical contacts can be of any multimedia contact type. Agent Desktop Customer History requires adequate bandwidth to function and it must be included in your network bandwidth planning calculations.

To calculate the impact of a voice callers' multimedia Customer history on bandwidth, consider voice contacts as an additional Multimedia contact type and add the number of voice contacts to your multimedia calculation for bandwidth calculations.

Multimedia Contact bandwidth requirements

This section details the bandwidth requirement of Agent Desktop Customer History for the following multimedia contact types:

- Email messages
- Fax messages
- Scanned Documents (SD)
- SMS text messages
- · Outbound contacts
- Web Communications (WCs)

This section also details the bandwidth requirement for voice contact types if multimedia history display is enabled.

Some multimedia contact supports attachments and these attachments must also be included in network calculations:

- Email contacts are of variable size. The average email size is a reasonable estimate, and is used for Agent Desktop calculations.
- Fax messages are delivered as email attachments. Fax messages must be included in the attachment size and rate estimates.
- Outbound contacts from Avava Contact Center Select solution do not have attachments.
- SMS test messages from customers. SMS test messages do not have attachments.
- Web chat messages do not have attachments.

The Agent Desktop Customer History feature enables agents to retrieve multimedia Customer history (containing up to 30 previous contacts), from the Avaya Contact Center Select server, when a multimedia contact is accepted. Agent Desktop Customer History requires adequate bandwidth to function and it must be included in your network bandwidth planning calculations. Retrieving Agent Desktop Customer history from the Avaya Contact Center Select server uses the bursty type of network data, and where the Customer history feature is enabled, it must be included in all network bandwidth calculations.

Example of calculating the bandwidth requirements of Agent Desktop Customer history downloads (based on ideal laboratory conditions):

N = Number of agents working on multimedia (MM) contacts. If the feature to display multimedia history with voice calls is activated, then N must include voice agents.

C = Maximum number of multimedia contacts per hour for the entire contact center solution. If the feature to display multimedia history with voice calls is activated, then C must include voice traffic per hour to all those agents.

avg contact size = average size of a contact in Kbits (not Kbytes). (Kbits = KBytes * 8). In many cases this is the average size of the incoming or outgoing email.

att_rate_in = percentage of incoming contact attachments. Contact attachments apply to email messages and fax messages.

att rate out = percentage of incoming email messages that are responded to with agent attached attachments in the reply.

avg_att_size = average size of an attachment in Kbits . Contact attachments apply to email messages and fax messages.

Note:

In-line attachments must also be included in the bandwidth calculations as regular attachments.

A key factor in calculating the minimum bandwidth for processing multimedia contacts is an assessment of the number of active agents that accept contacts in any one second period. The available bandwidth is shared across all of these agents in this time period.

The long term average number of agents active in any one second is calculated as follows:

 $n_{\text{average}} = \text{Roundup}(C / 3600)$

This equates to the average number of agents clicking the Accept button on the Agent Desktop at any one time. However, since the length of time it takes an agent to handle a contact is random, the number of agents clicking the Accept button is random. It is incorrect to engineer a bandwidth solution based solely on this average, as nearly 50% of the time more than $n_{average}$ agents are clicking the Accept button.

Therefore the number of active agent per second is calculated with a factor F as follows:

$$n_{\text{active}} = \text{Roundup}(F^* C / 3600)$$

where F is an engineering factor between 3 and 10. A higher value for F must be used when N, the total number of agents processing multimedia contacts and multimedia history with voice contact, is lower than 50. The choice of value F is your decision. F reflects the amount of extra bandwidth to build into your network to handle both the inherently random distribution of agent activity which results in natural peaks of use and any data spike events attributable to your particular Contact Center business models, such as initial shift start times, promotions and emergencies. A higher value reduces the level of bandwidth limitation caused by the overlapping of multiple agent download of multimedia contacts.

Once F is defined, the minimum bandwidth (in Kbits per second) can be estimated as follows:

BWMM_{min} =

n_{active} * ((avg_contact_size * 64) + 2000) + avg_att_size * (att_rate_in% + att_rate_out%) / 100) **Kbps**

Important:

The minimum recommended bandwidth available for processing multimedia contacts **BWMM**_{min} must be greater than 10 Mbits per second.

The time to download and display contacts on Agent Desktop is directly impacted by the bandwidth available between the Avaya Contact Center Select server and Agent Desktop at the time when the contact is accepted in Agent Desktop. The impact of bandwidth limitation is observed as a delayed display of contact and contact history in the Agent Desktop.

The following table demonstrates the impact of limiting bandwidth on multimedia contact display times on Agent Desktop. The data was generated using a 20KB email message, a Customer history of 30 contacts of 20KB size each, with a fixed RTT of 80ms.

Available bandwidth	Email display	Customer Details/Customer History Display
1Mbps	3 Seconds	Additional 6 Seconds
3Mbp	3 Seconds	Additional 3 Seconds
5Mbps	3 Seconds	Additional 2 Seconds

Retrieve Customer History on Voice contacts

This optional feature enables Agent Desktop to retrieve voice callers' multimedia Customer history (containing up to 30 previous contacts), from the Avaya Contact Center Select server, at the time a voice contact is accepted. These historical contacts can be of any multimedia contact type. If this feature is activated, the size of this history can be added to your network planning by considering

voice as an additional multimedia contact type and adding the number of voice contacts to your multimedia calculation.

Web Communication (WC) network bandwidth calculation

Processing web communications, after they have been received by the agent requires a constant level of bandwidth.

Network usage type: Constant

c = Number of WC contacts per hour

avg_session_length = Average length in seconds of WC session

Data size: 50 Kbps per active WC contact

WC network bandwidth requirement (Kbps):

WC_{BW} = (c * 50Kbps * avg_session_length)/ 3600

Presence network bandwidth calculation

Presence updates require a constant level of bandwidth.

Network usage Type: Constant

N = Number of agents working on MM contacts

avg_pres = Average number of presence updates per user per hour

Data size: 7 Kb per Presence update

Presence network bandwidth requirement (in Kbps) = (N* 7Kb * avg_pres)/ 3600

CCMM Search network bandwidth calculation

Bandwidth must be provided for an agent carrying out multimedia searches.

Network usage Type: Bursty

N = Number of agents running searches

average search = Average number of searches per hour

Data transmitted: 1280Kb per search

CCMM Search bandwidth requirement (in Kbps) = (1280Kb * average_search * N)/3600

CCMM Pull Mode network bandwidth calculation

Pull Mode allows agents to work outside the normal Avaya Contact Center Select routing mode. They personally select individual contacts from the Avaya Contact Center Select queues. Their view of the Avaya Contact Center Select queue is automatically updated using the same web services as the Avaya Contact Center Select CCMM search feature, and so uses the same bandwidth.

N = Number of agents working in Pull Mode

c = Number of contacts per hour per agent

Data transmitted: 1280Kb per search

CCMM Pull Mode search bandwidth requirement (in Kbps) = (1280Kb * c * N)/3600

Web Statistics network bandwidth calculation

Network usage Type: Bursty

N = Number of agents

avg_skills = Average number of skillsets per agent
Data transmitted: 3.2 Kb per skillset once a minute

Web Statistics bandwidth requirement: (3.2 Kb * avg skills * N)/60

Agent Desktop downloads by agent

Agent Desktop is a smart client which is downloaded from the Avaya Contact Center Select server over the network onto each agent computer on initial install. On each software update (service pack or patch) the updated Agent Desktop is re-downloaded onto each agent computer. The download requirements of Agent Desktop must be considered when planning the bandwidth requirements to remote agents.

Summary of total bandwidth requirements

You must sum up all the applicable bandwidth demands listed above to arrive at a minimum bandwidth for the site. Calculate the cumulative bandwidth for all multimedia features.

Client Citrix support

Agent Desktop is supported as a Citrix-published application. A Citrix server solution uses software to deliver on-demand Windows applications to physical desktops. This allows client users (agents in this case) to access and use programs which are available on the Windows Server 2008 operating system of the Citrix server. Agent Desktop is supported only with Citrix XenApp 6.5.

On the Avaya Contact Center Select server the Agent Desktop folder is typically located in:

D:\Avaya\Contact Center\Multimedia Server\Agent Desktop\client

This folder contains the entire Agent Desktop application. Copy this folder on the Agent Desktop server to the Citrix server. Then configure your Citrix server to publish Agent Desktop as a published application, accessed from this Agent Desktop folder on the Citrix server. On the Citrix server select the users (agents) allowed to run the Agent Desktop published application. For more information about Citrix application publishing, see your Citrix documentation. For more information on how to configure your Citrix server to publish Agent Desktop as a published application, see *Avaya Contact Center Select Advanced Administration*.

The Citrix server publishing Agent Desktop must be located in the same Local Area Network (LAN) as the Avaya Contact Center Select server.

Avaya Contact Center Select supports only the Multicast option for Real-Time Displays (RTDs) in a Citrix environment. Avaya Contact Center Select does not support the Unicast option for Real-Time Displays (RTDs) in a Citrix environment.

Agent Desktop network ports

Agent Desktop uses the following network ports to communicate with Contact Center components.

Feature	Component	Port number
HTTP (Web services)	ССММ	80
HTTP (Web services)	ССММ	443 (if SSL is enabled for CCMM)
CCT	CCT	29373
Voice History	CCMS	57772
Web Statistics	CCMS	9086

Chapter 11: Avaya Contact Center Select port matrix

This section lists the ports used by Avaya Contact Center Select. The Avaya Contact Center Select server contains the following components:

- Contact Center Manager Server (CCMS)
- Contact Center Manager Administration (CCMA)
- Communication Control Toolkit (CCT)
- Contact Center License Manager (LM)
- Contact Center Manager Server Utility (SU)
- Orchestration Designer (OD)
- Contact Center Multimedia (CCMM)
- Avaya Media Server (Avaya MS)

These components use the following ports.

Contact Center Manager Server port requirements

Contact Center Manager Server uses ports for communication between its own components. Most ports do not have implications for external network components like firewalls; however some ports might be used externally and therefore can affect an external firewall. In particular, port 10000 is a hard-coded port used to enable interoperability between Contact Center applications and external third-party applications (applications developed using the Real-Time Data (RTD) API).

No third-party application installed on Contact Center Manager Server can use the ports listed in the following table as it can cause the Contact Center Manager Server application to malfunction.

The following table shows the ports that Contact Center Manager Server uses.

Table 8: Contact Center Manager Server port usage

CCMS port number	Functionality	
445	TCP port used Windows File and Printer Sharing for Microsoft Networks. Required when copying data between active and standby servers using Windows File Sharing.	
1550	HDX CAPI	
1972	Caché database, and Caché shadowing	
4422	HDX NameService	
12668–12670	TraceControl	
10000	Hardcoded Toolkit Name Service	
10001–10082	Networking	
10038	NCP_CHANNEL—This channel is used to communicate between the NCP of one node to the NCP of another node. The NCP on one node sends sanity messages to the other node through this port.	
10039	ASM_CHANNEL—Different modules like NCP and TFE send messages to ASM through this channel.	
10040	NCP_ASM_CHANNEL—ASM uses this channel to send messages to NCP.	
10060	ASM_Service—The ASM service runs on this port. The Service Control Manager can send messages such as START, STOP, and RESTART to the ASM service through this port.	
10062	NCP_Service—The NCP service runs on this port. The Service Control Manager can send messages such as START, STOP, and RESTART to NCP on this port.	
3998	License Manager destination port—This is the first of 10 consecutive ports required for license management.	
3999–4007	License Manager client source port	
3389	Remote Desktop Connection for support	
5060–5061	SIP Proxy	
5070	For communication with coresident Avaya Media Server	
9080–9083	Web Services Open Interfaces	
9086	CC Web Statistics	
9100	XMPP Web Service Server Port	
9120	XMPP Web Service Client Port	
57012	System Management and Monitoring Component (SMMC) system tray.	

Contact Center Manager Administration port requirements

The following table shows the ports that Contact Center Manager Administration uses.

Table 9: Contact Center Manager Administration port usage

CCMA port number	Functionality	
TCP 80	For Internet Explorer communication.	
TCP 443	For secure HTTP communication (only applicable if SSL is enabled for secure Internet Information Services (IIS) communication).	
TCP Ports 389 and 636	For Active Directory Lightweight Directory Services (AD-LDS) functionality. Port 389 is for LDAP, and port 636 is for SSL.	
	When you install CCMA on a server that runs Window Server 2008, these ports usually appear by default in the Port Configuration for AD-LDS installation window. If the values 50000 and 50001 appear instead, port numbers 389 and 636 are already taken. In this case, you can either accept the new values, or choose other ports for security reasons.	
TCP Port 445	Windows File and Printer Sharing for Microsoft Networks. Required when copying data between active and standby servers using Windows File Sharing.	
TCP Port 3389	For remote desktop connection.	
TCP Port 25 (SMTP)	For the Historical Reporting component to send email notifications when reports are printed and saved.	
3899, 6366	For AD-LDS when CCMA is co-resident with Avaya Media Server.	
TCP Port 8200	For the Emergency Help component on the client PC.	
UDP ports 6020, 6030, 6040, 6050, 6060, 6070, 6080, 6090, 6100, 6110, 6120, 6130	For the CCMA server to receive IP multicasting data from CCMA Server (needed for Real-Time Reporting and Agent Desktop Displays).	
UDP ports 7020, 7030, 7040, 7050, 7060, 7070, 7080, 7090, 7100, 7110, 7120, 7130	For the CCMA server to send IP multicasting data to client PCs (needed for Real-Time Reporting and Agent Desktop Displays).	
UDP ports 7025, 7035, 7045, 7055, 7065, 7075, 7085, 7095, 7105, 7115, 7125, 7135, 7140, 7150, 7145 and 7155	For the CCMA server to send IP unicast data to client PCs. This is an optional method of sending the data required for Real-Time Reporting. If you do not use the multicast method, then you must configure the unicast option. You can also use a combination of the two methods.	
TCP Port 10000	Used by the Nameservice process on the CCMA server (nbnmsrvc.exe). It permits communication between the CCMA server and the server in Contact Center Manager Server.	
	Important:	
	The default port for the third-party software. This conflicts with the default port used by the CCMA Toolkit NameService. To avoid issues with CCMA functionality when using Veritas Backup Exec, you must change the default port of Veritas Backup Exec to another port number that is not being used by the network.	
Default UDP port 3998	License Manager destination port.	

CCMA port number	Functionality
Default UDP ports 3999 - 4007	License Manager destination source port.

Communication Control Toolkit port requirements

The following table shows the port numbers required for Communication Control Toolkit (CCT).

Table 10: Communication Control Toolkit port usage

CCT port number	Functionality	
1972	Caché database, and Caché shadowing solutions.	
3998	License Manager (LM) destination port, which is the first of 10 consecutive ports required for license management.	
3999 - 4007	LM client source ports.	
5000	To connect to the server in CCMS.	
8081	Default port of the Apache Tomcat Server which hosts the CCT Web Administration.	
8085	For CCT services to access the CCT database.	
8098	For the Contact Management Framework on the CCT server.	
8099	For the Contact Management Framework on the CCT server.	
8087	For CCT CMF component.	
9000	For CCT WebAdmin component.	
9010	For CCT CMF component.	
11110	Used by the CCT Server service for the CMF Web Service - Callback port.	
11111	Used by the CCT Server service for the CMF Web Service - Web server port.	
29373	Listens for requests from CCT client applications.	
29374	Data Access Layer Service listens for requests from CCT Remote Administration Console.	

Contact Center Multimedia port requirements

The following table lists the configurable Multimedia ports.

Table 11: Contact Center Multimedia ports

Port	Host	Client	Network interface	Functionality
1972	Contact Center Multimedia	Contact Center Manager Administration Server	Contact Center Multimedia Caché database	Port opened on database for reporting. Caché database, and Caché shadowing.
445	Windows File and Printer Sharing for Microsoft Networks.	Windows File and Printer Sharing for Microsoft Networks.	Windows File and Printer Sharing for Microsoft Networks.	Windows File and Printer Sharing for Microsoft Networks. Required when copying data between active and standby servers using Windows File Sharing.
110	Email server	Email Manager	Email server POP3	Receiving email
143	Email server	Email Manager	Email server IMAP	Receiving email
995	Email server	Email Manager	POP3 over SSL (optional)	Receiving secure email (optional)
993	Email server	Email Manager	IMAP over SSL (optional)	Receiving secure email (optional)
110	Email server	Email Manager	POP3 over TLS (optional)	Receiving secure email (optional)
143	Email server	Email Manager	IMAP over TLS (optional)	Receiving secure email (optional)
25	Email server	Email Manager	SMTP	Sending email
25	Email server	Email Manager	SMTP over TLS (optional)	Sending secure email (optional)
80	Contact Center Multimedia Server	Any Web services client (Agent Desktop, OCMT, and third-party Web services)	SOAP protocol	Accessing http Web services
29373	Communication Control Toolkit Server	Agent Desktop	Communication Control Toolkit	Remote access from clients to Communication Control Toolkit server (for Agent Desktop application)
57012	System Management and Monitoring	System Management and Monitoring	System Management and Monitoring	Database shadowing

Port	Host	Client	Network interface	Functionality
	Component (SMMC) system tray	Component (SMMC) system tray	Component (SMMC) system tray	

Avaya Media Server port requirements

The following table shows the port numbers required for Avaya Media Server on Windows Server 2008.

Table 12: Avaya Media Server port usage-Windows Server 2008

Port	Туре	Permit in TCP Filter	Description
1027	TCP	Yes	License Server
1028	TCP	No	System Monitor mchb
3306	TCP	Yes	MySQL
3389	TCP	Yes	Remote Desktop
3867	SCTP	No	Diameter over SCTP
3868	TCP	No	Diameter over TCP
3869	TCP	No	Diameter over TLS
4001	TCP	No	IvrMP MSLink
4004	TCP	No	Sip UA MSLink
4005	TCP	No	Resource Manager ExtSess
4014	TCP	No	SIP UA cmd i/f
4015	TCP	No	Resource Manager and i/f
5060	TCP	Yes	SIP over TCP
5060	UDP	No	SIP over UDP
5061	TCP	Yes	SIP over TLS
6080	TCP	No	Agent Greeting
7080	TCP	No	ConfMP MSLink
7410	TCP	Yes	SoapServer
7411	TCP	Yes	SoapServer TLS
8080	TCP	Yes	EM/UCM HTTP
8443	TCP	Yes	EM/UCM HTTP(s)
11004	TCP	No	DiamC MSLink
11014	TCP	No	DiamC and i/f

Port	Туре	Permit in TCP Filter	Description
19899	TCP	Yes	Resource Manager CPLink
19999	TCP	Yes	IvrMP ssdata
20005	TCP	Yes	CStore MSLink
20007	TCP	Yes	CStore RTFT
20009	TCP	Yes	IvrMP RTFT
21000	TCP	No	Voice XML Interpreter IPC
51000	TCP	No	Resource Manager IPC
51001	TCP	No	Legacy MPS Alarm deamon
51003	TCP	No	CCXML Interpreter IPC

The following table shows the port numbers required for Avaya Media Server on Linux.

Table 13: Avaya Media Server port usage-Linux

Port	Туре	Permit in TCP Filter	Description
1027	TCP	Yes	License Server
1028	TCP	No	System Monitor mchb
3306	TCP	Yes	MySQL
3867	SCTP	No	Diameter over SCTP
3868	TCP	No	Diameter over TCP
3869	TCP	No	Diameter over TLS
4001	TCP	No	IvrMP MSLink
4004	TCP	No	Sip UA MSLink
4005	TCP	No	Resource Manager ExtSess
4014	TCP	No	SIP UA cmd i/f
4015	TCP	No	Resource Manager cmd i/f
5060	TCP	Yes	SIP over TCP
5060	UDP	No	SIP over UDP
5061	TCP	Yes	SIP over TLS
6080	TCP	No	Agent Greeting
7080	TCP	No	ConfMP MSLink
7410	TCP	Yes	SoapServer
7411	TCP	Yes	SoapServer TLS
8080	TCP	Yes	EM HTTP
8443	TCP	Yes	EM HTTP(s)

Port	Туре	Permit in TCP Filter	Description
11004	TCP	No	DiamC MSLink
11014	TCP	No	DiamC and i/f
19899	TCP	Yes	Resource Manager CPLink
19999	TCP	Yes	IvrMP ssdata
20005	TCP	Yes	CStore MSLink
20007	TCP	Yes	CStore RTFT
20009	TCP	Yes	IvrMP RTFT
20011	TCP	No	Resource Manager IPC
21000	TCP	No	Voice XML Interpreter IPC

UDP Port Range is required for media processing. All starting UDP ports are configurable.

Table 14: Required UDP Port Range

Operating System	UDP Port Range
Windows Server 2008	20000 to 45499
Linux	6000 to 32599

Index

Numerics	E	
10-core CPU	email message flow example	<u>34</u>
6-core CPU	Entry-level server	<u>46</u>
8–core CPU	ESXi host specification	<u>71</u>
	Experience Portal	<u>13</u> , <u>128</u> , <u>130</u>
A	external server interactions	<u>33</u>
A word Dooldon	_	
Agent Desktop	F	
Citrix support	£	FO 77
Agent Desktop requirements	firmware	
antivirus software <u>58, 67, 93</u>	functions of telephony server	<u>11/</u>
application sequencing		
Avaya Aura Experience Portal	G	
Avaya Media Server <u>69</u>		
Avaya Media Server port requirements 155		<u>55, 64, 90</u>
Avaya Security Advisory38	guidelines for Java Runtime Environment	
	guidelines for service packs	
В	guidelines for service updates	
	guidelines for utility software	
BIOS51, 77	9 .	<u> </u>
Business Continuity	н	
С	H.323	125
O .	hardware	
Call Control XML123	hardware appliance	
call disconnect 39	Hardware Appliance	
call recording	hardware-assisted virtualization	
capacity limits		
CCMA	hardware requirements, Administrator	
Citrix		
CCMA port requirements	hardware requirements, Agent Desktop	
	High-end solution	
CCMM port requirements	host considerations vmware	
CCMS port requirements	Hyper-Threading	<u>53</u> , <u>79</u>
CCT port requirements		
CCT supported functionality	I	
CCXML 123		
Citrix support	interactions with external multimedia servers	
Agent Desktop	IOPS	
client requirements	IP Office support	<u>26</u>
configuration27		
D	J	
data aurahanni-atian	Java Runtime Environment guidelines	<u>56, 66, 92</u>
data synchronization22		
Data transfer	I	
DHCP	L	
disk caching <u>53</u> , <u>78</u>	licensing	60 84 95
domain3 <u>37</u>	Licensing	
DVD	limitations	
	localized languages	
	100u1120u 1a11uuau03	

Lync 2013	<u>14</u>	S	
М		sample flows	<u>30</u>
IVI		Screen Pop	<u>12</u> 4
maximum capacity	97	SDK	<u>13</u>
Mid-range server		security	38
multimedia external server interactions		server name requirements	
multimedia external server interactions	<u>50</u>	service packs guidelines	
		service updates guidelines	
N		Session Initiation Protocol	
		SGM	
naming server requirements		SIP	
network requirements		SIP Gateway Manager	
New in this release	<u>12</u>	SIP signaling	
NUMA	<u>53</u> , <u>79</u>	snapshot considerations	
		SOCD	
0		software	
O .		software appliance	·
Open Virtual Appliance	63	software specifications	
operating system Java Runtime Environment g			
operating system dava realitime Environment g		software utility guidelines	
operating system packs guidelines		support	
operating system requirements		supported main features	
		supported multimedia features	
operating system service update guidelines	<u>55, 65, 91</u>	supported reporting features	<u>10</u> 1
P		T	
Patch Scanner utility		Telephony Devices	
performance		telephony features	<u>107</u>
performance management		telephony server functions	<u>117</u>
P-header	<u>124</u>	third-party software	<u>138</u>
P-Intrinsics		TLS	<u>15</u>
port matrix		touchscreen	140
port requirements Avaya Media Server	<u>155</u>	touch screen	<u>14</u> 0
port requirements CCMA	<u>151</u>		
port requirements CCMM	<u>153</u>	11	
port requirements CCMS	<u>150</u>	U	
port requirements CCT	<u>153</u>	Universal Call Identifier	124
ports	<u>149</u>	unused hardware	
Private Header	124		
PVI		utility software guidelinesUUI	
R		V	
RAID	<u>53</u> , <u>78</u>	videos	47
remote access support	<u>117</u>	virtualization	
Remote Agents	<u>36</u>	Virtualization	
requirements Java Runtime Environments		virtualization considerations	·
requirements port Avaya Media Server			
requirements port CCMA		VMware	
requirements port CCMM		vmware host	
requirements port CCMS		VMware host specification	
requirements port CCT		VMXNET	
requirements server name		voice platform resiliency	
requirements service packs		Voice XML	the state of the s
requirements service updates		VXML	<u>123</u>
requirements utility software			
roquirornorno dunty software	<u>57</u> , <u>57</u> , <u>32</u>		

Index

W

WebLM <u>15</u>	, <u>71</u>
Windows domain	. 14
workaroup	37